


# Reduction RSD-MS-Ex with o-ring

Item number 1078503250



## Technical data

|                      |                                          |
|----------------------|------------------------------------------|
| Material             | Nickel-plated brass                      |
| Material o-ring      | NBR                                      |
| Protection class     | IP 68 - 10 bar , IP 69 K                 |
| Ex-protection level  | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Temperature range    | -20 °C to +95 °C                         |
| Tightening torque    | 24 Nm                                    |
| Variant              | Metric                                   |
| External thread (AG) | M50 x 1,5                                |
| Internal thread (IG) | M32 x 1,5                                |
| Thread length (GL)   | 10 mm                                    |
| Height (H)           | 14 mm                                    |
| Wrench size (SW)     | 54 mm                                    |



# Reduction RSD-MS-Ex with o-ring

Item number 1078503250

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 10            |
| EAN code              | 4033878401828 |
| Weight                | 0.14654 kg    |
| ETIM 7                | EC000938      |
| ETIM 8                | EC000938      |
| ETIM 9                | EC000938      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 74122000      |

Note:

