


# DIN 46320 Z

Item number 1105210101



## Technical data

|                              |  |
|------------------------------|--|
| <b>Version</b>               | with cut-out sealing ring  |
| <b>Material</b>              | Nickel-plated brass  |
| <b>Seal</b>                  | NBR  |
| <b>Protection class</b>      | IP 54 , IP 65 in case of additional flat seal at connection thread |
| <b>Temperature range</b>     | -20°C to +80°C   |
| <b>Variant</b>               | PG   |
| <b>External thread (AG)</b>  | PG 21  |
| <b>Cable diameter</b>        | 13 - 20 mm   |
| <b>Thread length (GL)</b>    | 7 mm   |
| <b>Height (H)</b>            | 33 mm  |
| <b>Wrench size (SW1/SW2)</b> | 33/30 mm   |



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)

# DIN 46320 Z

Item number 1105210101

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878404737 |
| Weight                | 0.0902 kg     |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 74198090      |

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)