


# HSK-K-Ex-Active

Item number 1292121770



## Technical data

<b>Material</b>	Polyamide, fiber reinforced
<b>Seal</b>	NBR
<b>Material o-ring</b>	NBR
<b>Protection class</b>	IP68 - 10bar/30min
<b>Ex-protection level</b>	Class I Div 2 Groups A,B,C,D , Class II Div 1 Groups E,F,G , II 1D Ex ta III C Da , II 2G Ex eb IIC Gb
<b>Temperature range</b>	-20°C to +85°C
<b>Colour</b>	blue-black
<b>RAL</b>	5012 , 9005
<b>Variant</b>	NPT
<b>External thread (AG)</b>	NPT 1/2"
<b>Cable diameter</b>	10 - 14 mm
<b>Thread length (GL)</b>	13 mm
<b>Height (H)</b>	28 mm
<b>Wrench size (SW1/SW2)</b>	27/27 mm
<b>Tightening torque</b>	4.5 Nm

# HSK-K-Ex-Active

Item number 1292121770

## Commercial data

Packaging Unit	50
EAN code	4033878415979
Weight	0.0116 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-34
Customs tariff number	39269097

Note:

