


HSK-K-Ex-Active

Item number 1292540270



Technical data

| | |
|------------------------------|--|
| Material | Polyamide, fiber reinforced |
| Seal | NBR |
| Material o-ring | NBR |
| Protection class | IP68 - 10bar/30min |
| Ex-protection level | Class I Div 2 Groups A,B,C,D , Class II Div 1 Groups E,F,G , II 1D Ex ta III C Da , II 2G Ex eb IIC Gb |
| Temperature range | -20 °C to +85 °C |
| Colour | blue-black |
| RAL | 5012 , 9005 |
| Variant | NPT |
| External thread (AG) | NPT 1 1/4" |
| Cable diameter | 18 - 25 mm |
| Thread length (GL) | 16 mm |
| Height (H) | 39 mm |
| Wrench size (SW1/SW2) | 42/46 mm |
| Tightening torque | 6.5 Nm |

HSK-K-Ex-Active

Item number 1292540270

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 25 |
| EAN code | 4033878416723 |
| Weight | 0.0467 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-34 |
| Customs tariff number | 39269097 |

Note:

