

# HSK-K-PVDF

Item number 1299480014



## Technical data

|                              |   |
|------------------------------|---|
| <b>Material</b>              | PVDF V0 according to UL94   |
| <b>Seal</b>                  | FKM   |
| <b>Protection class</b>      | IP 54 , IP 68 with additional O-ring:IP68 - 10bar/30min , IP 69 K |
| <b>Type Rating by</b>        | 12 , 4 , 4X , 6 (with additional O-ring) , UL 50E                 |
| <b>Temperature range</b>     | -35°C to +150°C   |
| <b>Colour</b>                | natural   |
| <b>Variant</b>               | PG  |
| <b>External thread (AG)</b>  | PG 48   |
| <b>Cable diameter</b>        | 37 - 44 mm  |
| <b>Thread length (GL)</b>    | 14 mm   |
| <b>Height (H)</b>            | 49 mm   |
| <b>Wrench size (SW1/SW2)</b> | 65/65 mm  |
| <b>Tightening torque</b>     | 18 Nm   |



# HSK-K-PVDF

Item number 1299480014

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 5             |
| EAN code              | 4033878418710 |
| Weight                | 0.14089 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 39269097      |

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)