


# HSK-K-MULTI-Ex-Active

Item number 1581320051



## Technical data

|                       |  |
|-----------------------|--|
| Material              | Polyamide, fiber reinforced  |
| Seal                  | Elastomer  |
| Material o-ring       | NBR  |
| Protection class      | IP68 - 10bar/30min   |
| Ex-protection level   | Class I Div 2 Groups A,B,C,D , Class II Div 1 Groups E,F,G , II 1D Ex ta III C Da , II 2G Ex eb IIC Gb |
| Temperature range     | -20 °C to +85 °C   |
| Colour                | black  |
| RAL                   | 9005   |
| Variant               | Metric   |
| External thread (AG)  | M32 x 1,5  |
| Thread length (GL)    | 11 mm  |
| Height (H)            | 39 mm  |
| Wrench size (SW1/SW2) | 42/42 mm   |
| Number of holes x d   | 6 x 6,5  |
| Tightening torque     | 6.5 Nm   |

# HSK-K-MULTI-Ex-Active

Item number 1581320051

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878000168 |
| Weight                | 0.04675 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 39269097      |

Note:

