


# HSK-K-FLAKA-Ex-Active

Item number 1582320051



## Technical data

|                       |   |
|-----------------------|---|
| Material              | Polyamide, fiber reinforced   |
| Seal                  | Elastomer   |
| Material o-ring       | NBR   |
| Protection class      | IP68 - 10bar/30min  |
| Ex-protection level   | Class I Div 2 Groups A,B,C,D , Class II Div 1 Groups E,F,G , II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Temperature range     | -20 °C to +85 °C  |
| Colour                | black   |
| RAL                   | 9005  |
| Variant               | Metric  |
| External thread (AG)  | M32 x 1,5   |
| Thread length (GL)    | 11 mm   |
| Height (H)            | 39 mm   |
| Wrench size (SW1/SW2) | 42/42 mm  |
| B x H                 | 22 x 8 mm   |
| Tightening torque     | 6.5 Nm  |

# HSK-K-FLAKA-Ex-Active

Item number 1582320051

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878000250 |
| Weight                | 0.06136 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 39269097      |

Note:

