


# HSK-K-FLAKA-Ex-Active

Item number 1582400052



## Technical data

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| Material              | Polyamide, fiber reinforced                                            |
| Seal                  | Elastomer                                                              |
| Material o-ring       | NBR                                                                    |
| Protection class      | IP68 - 10bar/30min                                                     |
| Ex-protection level   | Class II Div 1 Groups E,F,G , II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Temperature range     | -20°C to +85°C                                                         |
| Colour                | blue-black                                                             |
| RAL                   | 5012 , 9005                                                            |
| Variant               | Metric                                                                 |
| External thread (AG)  | M40 x 1,5                                                              |
| Thread length (GL)    | 13 mm                                                                  |
| Height (H)            | 48 mm                                                                  |
| Wrench size (SW1/SW2) | 53/53 mm                                                               |
| b x h                 | 28,5 x 10 mm                                                           |
| Tightening torque     | 10 Nm                                                                  |



ATEX



# HSK-K-FLAKA-Ex-Active

Item number 1582400052

## Commercial data

|             |             |
|-------------|-------------|
| ETIM 7      | EC000441    |
| ETIM 8      | EC000441    |
| ETIM 9      | EC000441    |
| eCl@ss 10.1 | 27-14-44-34 |

## Note:



ATEX

