

# HSK-M

Item number 1609200031



## Technical data

|                              |                                |
|------------------------------|--------------------------------|
| <b>Material</b>              | Nickel-plated brass            |
| <b>Clamping insert</b>       | Polyamide VO according to UL94 |
| <b>Seal</b>                  | NBR                            |
| <b>Material o-ring</b>       | NBR                            |
| <b>Protection class</b>      | IP68 - 10bar/30min , IP 69 K   |
| <b>Type Rating by</b>        | 4 , 4X , 6 , UL 50E            |
| <b>Temperature range</b>     | -40 °C to +100 °C              |
| <b>Variant</b>               | Metric-long                    |
| <b>External thread (AG)</b>  | M20 x 1,5                      |
| <b>Cable diameter</b>        | 5 - 9 mm                       |
| <b>Thread length (GL)</b>    | 10 mm                          |
| <b>Height (H)</b>            | 23 mm                          |
| <b>Wrench size (SW1/SW2)</b> | 22/22 mm                       |
| <b>Tightening torque</b>     | 8 Nm                           |



# HSK-M

Item number 1609200031

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 50            |
| EAN code              | 4033878429617 |
| Weight                | 0.03244 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 74198090      |

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)