


# HSK-M

Item number 1609320051



## Technical data

|                              |                                |
|------------------------------|--------------------------------|
| <b>Material</b>              | Nickel-plated brass            |
| <b>Clamping insert</b>       | Polyamide VO according to UL94 |
| <b>Seal</b>                  | NBR                            |
| <b>Material o-ring</b>       | NBR                            |
| <b>Protection class</b>      | IP68 - 10bar/30min , IP 69 K   |
| <b>Type Rating by</b>        | 4 , 4X , 6 , UL 50E            |
| <b>Temperature range</b>     | -40 °C to +100 °C              |
| <b>Variant</b>               | Metric                         |
| <b>External thread (AG)</b>  | M32 x 1,5                      |
| <b>Cable diameter</b>        | 13 - 20 mm                     |
| <b>Thread length (GL)</b>    | 8 mm                           |
| <b>Height (H)</b>            | 31 mm                          |
| <b>Wrench size (SW1/SW2)</b> | 40/40 mm                       |
| <b>Tightening torque</b>     | 15 Nm                          |



# HSK-M

Item number 1609320051

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878429822 |
| Weight                | 0.10696 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 74198090      |

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)