

# HSK-M-Ex

Item number 1610120070



## Technical data

|                       |  |
|-----------------------|--|
| Material              | Nickel-plated brass                      |
| Clamping insert       | Polyamide VO according to UL94           |
| Seal                  | NBR                                      |
| Material o-ring       | NBR                                      |
| Protection class      | IP68 - 10bar/30min , IP 69 K             |
| Ex-protection level   | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Type Rating by        | 4 , 4X , 6 , UL 50E                      |
| Temperature range     | -20 °C to +95 °C                         |
| Variant               | NPT                                      |
| External thread (AG)  | NPT 1/2"                                 |
| Cable diameter        | 6 - 12 mm                                |
| Thread length (GL)    | 13 mm                                    |
| Height (H)            | 24 mm                                    |
| Wrench size (SW1/SW2) | 22/24 mm                                 |
| Tightening torque     | 8 Nm                                     |



# HSK-M-Ex

Item number 1610120070

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 50            |
| EAN code              | 4033878430323 |
| Weight                | 0.04052 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 74198090      |

Note:

