

HSK-M-Ex

Item number 1610130060



Technical data

| | |
|------------------------------|--|
| Material | Nickel-plated brass |
| Clamping insert | Polyamide VO according to UL94 |
| Seal | NBR |
| Material o-ring | NBR |
| Protection class | IP68 - 10bar/30min , IP 69 K |
| Ex-protection level | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Type Rating by | 4 , 4X , 6 , UL 50E |
| Temperature range | -20°C to +95°C |
| Variant | PG.-long |
| External thread (AG) | PG 13,5 |
| Cable diameter | 6 - 12 mm |
| Thread length (GL) | 10 mm |
| Height (H) | 24 mm |
| Wrench size (SW1/SW2) | 22/22 mm |
| Tightening torque | 8 Nm |



HSK-M-Ex

Item number 1610130060

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 50 |
| EAN code | 4033878430361 |
| Weight | 0.03079 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-34 |
| Customs tariff number | 74198090 |

Note:

