# HSK-M-Ex

Item number 1610161151




Technical data

| | |
|---|---|
| **Material** | Nickel-plated brass |
| **Clamping insert** | Polyamide V0 according to UL94 |
| **Seal** | NBR |
| **Material o-ring** | NBR |
| **Protection class** | IP68 - 10bar/30min , IP 69 K |
| **Ex-protection level** | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| **Type Rating by** | 4 , 4X , 6 , UL 50E |
| **Variant** | Metric |
| **External thread (AG)** | M16 x 1,5 |
| **Cable diameter** | 3 - 7 mm |
| **Thread length (GL)** | 6 mm |
| **Height (H)** | 22 mm |
| **Wrench size (SW1/SW2)** | 20/20 mm |
| **Temperature range** | -20°C to +95°C |
| **Tightening torque** | 5 Nm |

# HSK-M-Ex

Item number 1610161151

Commercial data

| | |
|---|---|
| **Packaging Unit** | 50 |
| **EAN code** | 4033878430491 |
| **Weight** | 0.02325 kg |
| **ETIM 7** | EC000441 |
| **ETIM 8** | EC000441 |
| **ETIM 9** | EC000441 |
| **eCl@ss 10.1** | 27-14-44-34 |
| **Customs tariff number** | 74198090 |

Note: