

# HSK-M-Ex

Item number 1610420061



## Technical data

|                              |  |
|------------------------------|--|
| <b>Material</b>              | Nickel-plated brass                      |
| <b>Clamping insert</b>       | Polyamide VO according to UL94           |
| <b>Seal</b>                  | NBR                                      |
| <b>Material o-ring</b>       | NBR                                      |
| <b>Protection class</b>      | IP68 - 10bar/30min , IP 69 K             |
| <b>Ex-protection level</b>   | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| <b>Type Rating by</b>        | 4 , 4X , 6 , UL 50E                      |
| <b>Temperature range</b>     | -20°C to +95°C                           |
| <b>Variant</b>               | PG.-long                                 |
| <b>External thread (AG)</b>  | PG 42                                    |
| <b>Cable diameter</b>        | 25 - 31 mm                               |
| <b>Thread length (GL)</b>    | 15 mm                                    |
| <b>Height (H)</b>            | 37 mm                                    |
| <b>Wrench size (SW1/SW2)</b> | 57/57 mm                                 |
| <b>Tightening torque</b>     | 24 Nm                                    |

# HSK-M-Ex

Item number 1610420061

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 5             |
| EAN code              | 4033878430897 |
| Weight                | 0.23706 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 74198090      |

Note:

