


# HSK-MZ-EMC-Ex

Item number 1617630050



## Technical data

Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP68 - 10bar/30min , IP 69 K
Type Rating by	4 , 4X , 6 , UL 50E
Ex-protection level	II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb
Temperature range	-20°C to +95°C
Variant	Metric
External thread (AG)	M63 x 1,5
Cable diameter	37 - 44 mm
Thread length (GL)	10 mm
Height (H)	52 mm
Wrench size (SW1/SW2)	68/68 mm
Tightening torque	30 Nm



Dimensions and specifications may be changed without prior notice

[www.hummel.com](http://www.hummel.com)

# HSK-MZ-EMC-Ex

Item number 1617630050

## Commercial data

Packaging Unit	5
EAN code	4033878432198
Weight	0.28414 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-34
Customs tariff number	85369010

Note:



Dimensions and specifications may be changed without prior notice

[www.hummel.com](http://www.hummel.com)