


# HSK-M-Ex-d

Item number 1622540070



## Technical data

|                              |  |
|------------------------------|--|
| <b>Material</b>              | Nickel-plated brass                      |
| <b>Clamping insert</b>       | Polyamide V0 according to UL94           |
| <b>Protection class</b>      | IP68 - 10bar/30min , IP 69 K             |
| <b>Ex-protection level</b>   | II 1D Ex ta IIIC Da , II 2G Ex db IIC Gb |
| <b>Temperature range</b>     | -60°C to +105°C                          |
| <b>Variant</b>               | NPT                                      |
| <b>External thread (AG)</b>  | NPT 1 1/4"                               |
| <b>Cable diameter</b>        | 22 - 32 mm                               |
| <b>Thread length (GL)</b>    | 26 mm                                    |
| <b>Height (H)</b>            | 38.5 mm                                  |
| <b>Wrench size (SW1/SW2)</b> | 50/50 mm                                 |
| <b>Tightening torque</b>     | 24 Nm                                    |



# HSK-M-Ex-d

Item number 1622540070

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 4             |
| EAN code              | 4033878432730 |
| Weight                | 0.21297 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 74198090      |

Note:

