

HSK-M-Flex-EMC

Item number 1624210060



Technical data

| | |
|-----------------------|--------------------------------|
| Material | Nickel-plated brass |
| Steel spring | INOX 1.4310 |
| Clamping insert | Polyamide V0 according to UL94 |
| Seal | NBR |
| Material o-ring | NBR |
| Protection class | IP68 - 10bar/30min , IP 69 K |
| Type Rating by | 4 , 4X , 6 , UL 50E |
| Temperature range | -40 °C to +100 °C |
| Variant | PG.-long |
| External thread (AG) | PG 21 |
| Cable diameter | 13 - 18 mm |
| d | 18.4 mm |
| Thread length (GL) | 12 mm |
| Height (H) | 111 mm |
| Wrench size (SW1/SW2) | 30/30 mm |
| Tightening torque | 12 Nm |



HSK-M-Flex-EMC

Item number 1624210060

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 20 |
| EAN code | 4033878433676 |
| Weight | 0.05202 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-32 |
| Customs tariff number | 85369010 |

Note:

