


HSK-MZ-Ex-d

Item number 1628120050



Technical data

| | |
|-----------------------|------------------------------------------|
| Material | Nickel-plated brass |
| Clamping insert | Polyamide V0 according to UL94 |
| Seal | FKM |
| Material o-ring | FKM |
| Protection class | IP68 - 10bar/30min , IP 69 K |
| Ex-protection level | II 1D Ex ta IIIC Da , II 2G Ex db IIC Gb |
| Temperature range | -60°C to +105°C |
| Variant | Metric |
| External thread (AG) | M12 x 1,5 |
| Thread length (GL) | 16 mm |
| Cable diameter | 3 - 6,5 mm |
| Height (H) | 26 mm |
| Wrench size (SW1/SW2) | 14/14 mm |
| Tightening torque | 7.5 Nm |

HSK-MZ-Ex-d

Item number 1628120050

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 25 |
| EAN code | 4033878433782 |
| Weight | 0.01243 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-34 |
| Customs tariff number | 74198090 |

Note:

