

HSK-M-Ex

Item number 1640500051



Technical data

| | |
|------------------------------|--|
| Material | Nickel-plated brass |
| Clamping insert | Polyamide VO according to UL94 |
| Seal | NBR |
| Material o-ring | NBR |
| Protection class | IP68 - 10bar/30min , IP 69 K |
| Ex-protection level | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Type Rating by | 4 , 4X , 6 , UL 50E |
| Temperature range | -60°C to +95°C |
| Variant | Metric |
| External thread (AG) | M50 x 1,5 |
| Cable diameter | 25 - 31 mm |
| Thread length (GL) | 9 mm |
| Height (H) | 37 mm |
| Wrench size (SW1/SW2) | 57/57 mm |
| Tightening torque | 24 Nm |



HSK-M-Ex

Item number 1640500051

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 5 |
| EAN code | 4033878435915 |
| Weight | 0.22524 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-34 |
| Customs tariff number | 74198090 |

Note:

