

# HSK-MZ-Ex

Item number 1641250050



## Technical data

|                       |  |
|-----------------------|--|
| Material              | Nickel-plated brass                      |
| Clamping insert       | Polyamide V0 according to UL94           |
| Seal                  | NBR                                      |
| Material o-ring       | NBR                                      |
| Protection class      | IP68 - 10bar/30min , IP 69 K             |
| Type Rating by        | 4 , 4X , 6 , UL 50E                      |
| Ex-protection level   | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Temperature range     | -60°C to +95°C                           |
| Variant               | Metric                                   |
| External thread (AG)  | M25 x 1,5                                |
| Cable diameter        | 14 - 18 mm                               |
| Thread length (GL)    | 7 mm                                     |
| Height (H)            | 37 mm                                    |
| Wrench size (SW1/SW2) | 30/30 mm                                 |
| Tightening torque     | 12 Nm                                    |

# HSK-MZ-Ex

Item number 1641250050

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878436097 |
| Weight                | 0.09683 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-34   |
| Customs tariff number | 74198090      |

Note:

