

# HSK-M-EMC-PVDF-Ex

Item number 1666120070



## Technical data

Material	Nickel-plated brass
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP68 - 10bar/30min , IP 69 K
Ex-protection level	II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb
Type Rating by	4 , 4X , 6 , UL 50E
Temperature range	-20°C to +130°C
Variant	NPT
External thread (AG)	NPT 1/2"
Cable diameter	6 - 12 mm
Thread length (GL)	13 mm
Height (H)	24 mm
Wrench size (SW1/SW2)	22/24 mm
Tightening torque	8 Nm



Dimensions and specifications may be changed without prior notice

[www.hummel.com](http://www.hummel.com)

# HSK-M-EMC-PVDF-Ex

Item number 1666120070

## Commercial data

Packaging Unit	50
EAN code	4033878438480
Weight	0.018 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-34
Customs tariff number	85369010

Note:



Dimensions and specifications may be changed without prior notice

[www.hummel.com](http://www.hummel.com)