


# DIN 46320 SE

Item number 1680161401



## Technical data

|                              |  |
|------------------------------|--|
| <b>Material</b>              | Nickel-plated brass  |
| <b>Seal</b>                  | NBR  |
| <b>Protection class</b>      | IP 54 , IP 65 in case of additional flat seal at connection thread |
| <b>Temperature range</b>     | -20°C to +80°C   |
| <b>Variant</b>               | PG   |
| <b>External thread (AG)</b>  | PG 16  |
| <b>Cable diameter</b>        | 6,5 - 16 mm  |
| <b>Thread length (GL)</b>    | 8 mm   |
| <b>Height (H)</b>            | 24 mm  |
| <b>Wrench size (SW1/SW2)</b> | 22/24 mm   |
| <b>E</b>                     | 14 mm  |



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)

# DIN 46320 SE

Item number 1680161401

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 50            |
| EAN code              | 4033878440117 |
| Weight                | 0.03378 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 85369010      |

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)