


# HSK-M-MULTI-Ex

Item number 1687250050



## Technical data

<b>Material</b>	Nickel-plated brass
<b>Clamping insert</b>	Polyamide V0 according to UL94
<b>Seal</b>	Elastomer
<b>Material o-ring</b>	NBR
<b>Protection class</b>	IP 65 , IP68 - 10bar/30min , and optimum assignment of all holes
<b>Ex-protection level</b>	II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb
<b>Temperature range</b>	-20 °C to +95 °C
<b>Number of holes x d</b>	4 x 6
<b>Variant</b>	Metric
<b>External thread (AG)</b>	M25 x 1,5
<b>Thread length (GL)</b>	7 mm
<b>Height (H)</b>	26 mm
<b>Wrench size (SW1/SW2)</b>	30/30 mm
<b>Tightening torque</b>	12 Nm

# HSK-M-MULTI-Ex

Item number 1687250050

## Commercial data

Packaging Unit	25
EAN code	4033878007068
Weight	0.05112 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-34
Customs tariff number	74198090

Note:

