


HSK-M-MULTI-Ex

Item number 1687630250



Technical data

| | |
|------------------------------|--|
| Material | Nickel-plated brass |
| Clamping insert | Polyamide V0 according to UL94 |
| Seal | Elastomer |
| Material o-ring | NBR |
| Protection class | IP 65 , IP68 - 10bar/30min , and optimum assignment of all holes |
| Ex-protection level | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Temperature range | -20 °C to +95 °C |
| Number of holes x d | 3 x 18 |
| Variant | Metric |
| External thread (AG) | M63 x 1,5 |
| Thread length (GL) | 10 mm |
| Height (H) | 38 mm |
| Wrench size (SW1/SW2) | 64/68 mm |
| Tightening torque | 30 Nm |

HSK-M-MULTI-Ex

Item number 1687630250

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 5 |
| EAN code | 4033878006269 |
| Weight | 0.32496 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-34 |
| Customs tariff number | 74198090 |

Note:

