

HSK-MZ

Item number 1690500030



Technical data

| | |
|------------------------------|--------------------------------|
| Material | Nickel-plated brass |
| Clamping insert | Polyamide VO according to UL94 |
| Seal | NBR |
| Material o-ring | NBR |
| Protection class | IP68 - 10bar/30min , IP 69 K |
| Type Rating by | 4 , 4X , 6 , UL 50E |
| Temperature range | -40 °C to +100 °C |
| Variant | Metric-long |
| External thread (AG) | M50 x 1,5 |
| Cable diameter | 32 - 38 mm |
| Thread length (GL) | 15 mm |
| Height (H) | 51 mm |
| Wrench size (SW1/SW2) | 57/57 mm |
| Tightening torque | 24 Nm |



HSK-MZ

Item number 1690500030

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 5 |
| EAN code | 4033878441039 |
| Weight | 0.38751 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-32 |
| Customs tariff number | 74198090 |

Note:



Dimensions and specifications may be changed without prior notice



www.hummel.com