

# HSK-M-EMC

Item number 1691160060



## Technical data

|                              |                                |
|------------------------------|--------------------------------|
| <b>Material</b>              | Nickel-plated brass            |
| <b>Clamping insert</b>       | Polyamide VO according to UL94 |
| <b>Seal</b>                  | NBR                            |
| <b>Material o-ring</b>       | NBR                            |
| <b>Protection class</b>      | IP68 - 10bar/30min , IP 69 K   |
| <b>Type Rating by</b>        | 4 , 4X , 6 , UL 50E            |
| <b>Temperature range</b>     | -40 °C to +100 °C              |
| <b>Variant</b>               | PG-long                        |
| <b>External thread (AG)</b>  | PG 16                          |
| <b>Cable diameter</b>        | 10 - 14 mm                     |
| <b>Thread length (GL)</b>    | 10 mm                          |
| <b>Height (H)</b>            | 23 mm                          |
| <b>Wrench size (SW1/SW2)</b> | 24/24 mm                       |
| <b>Tightening torque</b>     | 10 Nm                          |



# HSK-M-EMC

Item number 1691160060

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 50            |
| EAN code              | 4033878441398 |
| Weight                | 0.03496 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 85369010      |

Note:

