


# HSK-M-EMC

Item number 1691160061



## Technical data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Nickel-plated brass            |
| Clamping insert       | Polyamide VO according to UL94 |
| Seal                  | NBR                            |
| Material o-ring       | NBR                            |
| Protection class      | IP68 - 10bar/30min , IP 69 K   |
| Type Rating by        | 4 , 4X , 6 , UL 50E            |
| Temperature range     | -40 °C to +100 °C              |
| Variant               | PG.-long                       |
| External thread (AG)  | PG 16                          |
| Cable diameter        | 7 - 12 mm                      |
| Thread length (GL)    | 10 mm                          |
| Height (H)            | 23 mm                          |
| Wrench size (SW1/SW2) | 24/24 mm                       |
| Tightening torque     | 10 Nm                          |



# HSK-M-EMC

Item number 1691160061

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 50            |
| EAN code              | 4033878441404 |
| Weight                | 0.0355 kg     |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 85369010      |

Note:

