

# HSK-M-EMC

Item number 1691340071



## Technical data

|                       |                                |
|-----------------------|--------------------------------|
| Material              | Nickel-plated brass            |
| Clamping insert       | Polyamide VO according to UL94 |
| Seal                  | NBR                            |
| Material o-ring       | NBR                            |
| Protection class      | IP68 - 10bar/30min , IP 69 K   |
| Type Rating by        | 4 , 4X , 6 , UL 50E            |
| Temperature range     | -40 °C to +100 °C              |
| Variant               | NPT                            |
| External thread (AG)  | NPT 3/4"                       |
| Cable diameter        | 9 - 16 mm                      |
| Thread length (GL)    | 13 mm                          |
| Height (H)            | 25 mm                          |
| Wrench size (SW1/SW2) | 30/30 mm                       |
| Tightening torque     | 12 Nm                          |



# HSK-M-EMC

Item number 1691340071

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 25            |
| EAN code              | 4033878441640 |
| Weight                | 0.06187 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 85369010      |

Note:

