


HSK-MZ-EMC

Item number 1692070060



Technical data

| | |
|-----------------------|--------------------------------|
| Material | Nickel-plated brass |
| Clamping insert | Polyamide VO according to UL94 |
| Seal | NBR |
| Material o-ring | NBR |
| Protection class | IP68 - 10bar/30min , IP 69 K |
| Type Rating by | 4 , 4X , 6 , UL 50E |
| Temperature range | -40 °C to +100 °C |
| Variant | PG.-long |
| External thread (AG) | PG 7* |
| Cable diameter | 3 - 6,5 mm |
| Thread length (GL) | 10 mm |
| Height (H) | 26 mm |
| Wrench size (SW1/SW2) | 14/14 mm |
| Tightening torque | 4 Nm |




HSK-MZ-EMC

Item number 1692070060

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 50 |
| EAN code | 4033878441947 |
| Weight | 0.01527 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-32 |
| Customs tariff number | 85369010 |

Note:



Dimensions and specifications may be changed without prior notice



www.hummel.com