

# HSK-M-PVDF

Item number 1699400050



## Technical data

|                       |                              |
|-----------------------|------------------------------|
| Material              | Nickel-plated brass          |
| Clamping insert       | PVDF                         |
| Seal                  | FKM                          |
| Material o-ring       | FKM                          |
| Protection class      | IP68 - 10bar/30min , IP 69 K |
| Type Rating by        | 4 , 4X , 6 , UL 50E          |
| Temperature range     | -35°C to +150°C              |
| Variant               | Metric                       |
| External thread (AG)  | M40 x 1,5                    |
| Cable diameter        | 22 - 32 mm                   |
| Thread length (GL)    | 8 mm                         |
| Height (H)            | 37 mm                        |
| Wrench size (SW1/SW2) | 50/50 mm                     |
| Tightening torque     | 15 Nm                        |



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)

# HSK-M-PVDF

Item number 1699400050

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging Unit        | 10            |
| EAN code              | 4033878444337 |
| Weight                | 0.18644 kg    |
| ETIM 7                | EC000441      |
| ETIM 8                | EC000441      |
| ETIM 9                | EC000441      |
| eCl@ss 10.1           | 27-14-44-32   |
| Customs tariff number | 74198090      |

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)