


# Diverter straight type lockable

Item number 2257000501



## Technical data

Connection size 1 (AG1)	G 3/4
Connection size 2 (AG2)	G 3/4
Axial dimension (AM)	50 mm
Connection type 1 (AT1)	Euro cone
Connection type 2 (AT2)	Internal thread
Length (L)	103 mm
Width (B)	33.5 mm
Height (H)	51 mm
Thread Length 1 (GL1)	10 mm
Wrench size 1 (SW1)	30 mm
Version	Nipple
Suitable for	Euro cone
Mounting form	Straight-type
Pipe system	Two pipe system
Type	absperibar
Kvs-value	1.04

# Diverter straight type lockable


Item number 2257000501

<b>Material</b>	Nickel-plated brass
<b>Material moulded seal</b>	EPDM / Teflon
<b>Material union nut</b>	Nickel-plated brass
<b>Material body/union nut</b>	Nickel-plated brass
<b>Material connection nipple</b>	Brass blank
<b>Material cone insert</b>	PA
<b>Max. operating pressure</b>	10 bar
<b>Max. operating temperature heating</b>	120 °C

## Commercial data

<b>Packaging Unit</b>	40
<b>EAN code</b>	4033878200292
<b>Weight</b>	0.45 kg
<b>ETIM 7</b>	EC010077
<b>ETIM 8</b>	EC010077
<b>ETIM 9</b>	EC010077
<b>eCl@ss 10.1</b>	22-39-04-90
<b>Customs tariff number</b>	84818039

Note:



# Diverter straight type lockable

Item number 2257000501