


# Flexible device connection

Item number 2823343401



## Technical data

Connection size 1 (AG1)	R 3/4
Connection size 2 (AG2)	G 3/4
Connection type 1 (AT1)	External thread
Connection type 2 (AT2)	Internal thread
Variable length (Lv)	95 – 200 mm
Width (B)	33.5 mm
Height (H)	33.5 mm
Mounting form	Straight-type
Thread Length 1 (GL1)	15 mm
Wrench size 1 (SW1)	27 mm
Wrench size 2 (SW2)	30 mm
Wrench size 3 (SW3)	21 mm
Material	Stainless steel
Material moulded seal	AFM
Material union nut	Nickel-plated brass

# Flexible device connection


Item number 2823343401

<b>Material corrugated tube</b>	Stainless steel
<b>Max. operating pressure</b>	6 bar
<b>Max. operating temperature heating</b>	95 °C
<b>max. bending radius</b>	50 mm
<b>Bursting pressure</b>	80 bar
<b>max. rate of flow</b>	2200 l/h

## Commercial data

<b>Packaging Unit</b>	20
<b>EAN code</b>	4033878008669
<b>Weight</b>	0.14 kg
<b>ETIM 7</b>	EC011399
<b>ETIM 8</b>	EC011399
<b>ETIM 9</b>	EC011399
<b>eCl@ss 10.1</b>	22-56-92-90
<b>Customs tariff number</b>	84818039

Note:



# Flexible device connection

Item number 2823343401