


Flexible radiator connection with reduction

Item number 28261238341



Technical data

Connection size 1 (AG1)	G 1/2
Connection size 2 (AG2)	G 3/4
Connection size 3 (AG3)	G 3/8
Connection size 4 (AG4)	G 3/4
Connection type 1 (AT1)	External thread
Connection type 2 (AT2)	Internal thread
Connection type 3 (AT3)	External thread
Connection type 4 (AT4)	External thread
Suitable for	Euro cone
Variable length (Lv)	65 – 95 mm
Width (B)	33.5 mm
Height (H)	33.5 mm
Mounting form	Straight-type
Thread Length 1 (GL1)	13.5 mm
Thread Length 2 (GL2)	12 mm

Flexible radiator connection with reduction

Item number 28261238341

Thread Length 3 (GL3)	11 mm
Wrench size 1 (SW1)	22 mm
Wrench size 2 (SW2)	30 mm
Wrench size 3 (SW3)	19 mm
Wrench size 4 (SW4)	24 mm
Wrench size 5 (SW5)	26 mm
Material	Stainless steel
Material moulded seal	EPDM
Material union nut	Nickel-plated brass
Material reduction	Nickel-plated brass
Material corrugated tube	Stainless steel
Max. operating pressure	10 bar
Max. operating temperature heating	120 °C
max. bending radius	40 mm
Bursting pressure	90 bar
max. rate of flow	1400 l/h

Commercial data

Packaging Unit	20
EAN code	4033878003046
Weight	0.19 kg
ETIM 7	EC011399

Flexible radiator connection with reduction

Item number 28261238341

ETIM 8	EC011399
ETIM 9	EC011399
eCl@ss 10.1	22-56-92-90
Customs tariff number	84818039

Note:

