


Flexible radiator connection with reduction

Item number 28291238341



Technical data

| | |
|-------------------------|-----------------|
| Connection size 1 (AG1) | G 1/2 |
| Connection size 2 (AG2) | G 3/4 |
| Connection size 3 (AG3) | G 3/8 |
| Connection size 4 (AG4) | G 3/4 |
| Connection type 1 (AT1) | External thread |
| Connection type 2 (AT2) | Internal thread |
| Connection type 3 (AT3) | External thread |
| Connection type 4 (AT4) | External thread |
| Suitable for | Euro cone |
| Variable length (Lv) | 190 – 410 mm |
| Width (B) | 33.5 mm |
| Height (H) | 33.5 mm |
| Mounting form | Straight-type |
| Thread Length 1 (GL1) | 13.5 mm |
| Thread Length 2 (GL2) | 12 mm |

Flexible radiator connection with reduction

Item number 28291238341

| | |
|------------------------------------|---------------------|
| Thread Length 3 (GL3) | 11 mm |
| Wrench size 1 (SW1) | 22 mm |
| Wrench size 2 (SW2) | 30 mm |
| Wrench size 3 (SW3) | 19 mm |
| Wrench size 4 (SW4) | 24 mm |
| Wrench size 5 (SW5) | 26 mm |
| Material | Stainless steel |
| Material moulded seal | EPDM |
| Material union nut | Nickel-plated brass |
| Material reduction | Nickel-plated brass |
| Material corrugated tube | Stainless steel |
| Max. operating pressure | 10 bar |
| Max. operating temperature heating | 120 °C |
| max. bending radius | 40 mm |
| Bursting pressure | 90 bar |
| max. rate of flow | 1400 l/h |

Commercial data

| | |
|----------------|---------------|
| Packaging Unit | 20 |
| EAN code | 4033878002292 |
| Weight | 0.24 kg |
| ETIM 7 | EC011399 |

Flexible radiator connection with reduction

Item number 28291238341

| | |
|-----------------------|-------------|
| ETIM 8 | EC011399 |
| ETIM 9 | EC011399 |
| eCl@ss 10.1 | 22-56-92-90 |
| Customs tariff number | 84818039 |

Note:

