


SpeedFIX compression fitting

Item number 2855001502



Technical data

Connection size 1 (AG1)	G 3/4
Connection size 2 (AG2)	15 mm
Connection type 1 (AT1)	Euro cone
Length (L)	33.2 mm
Width (B)	33.2 mm
Height (H)	20.5 mm
Wrench size 1 (SW1)	30 mm
Suitable for	Copper, precision steel or stainless steel tubes with a wall thickness ≥ 1 mm according to DIN EN 1057, DIN EN 10305-2 and DIN EN 10312 , Euro cone
Clamping range	15 mm
Colour	chrome
Material	Coated brass
Material moulded seal	EPDM
Material clamping ring	Brass blank



SpeedFIX compression fitting


Item number 2855001502

Material union nut	Coated brass
Max. operating pressure	10 bar
Max. operating temperature heating	120 °C
Max. operating temperature drinking water	95 °C
Compliance	UBA
Registration number ÜA	R-15.2.3-21-17214
DIN	EN ISO 228-1

Commercial data

Packaging Unit	100
EAN code	4033878104521
Weight	0.11 kg
ETIM 7	EC011042
ETIM 8	EC011042
ETIM 9	EC011042
eCl@ss 10.1	22-56-92-02
Customs tariff number	84818039

Note:



SpeedFIX compression fitting

Item number 2855001502

