



# Contact insert M16 - 8-pole (solder in)

## Item number 7001943137





### Technical data

Characteristic of connection	PCB assembly
Number of poles	8
Pole picture	4 + 3 + PE
Coding	PE
Dip solder contacts length	17 mm
Insert	Pin
Material insulating body	PA 6, PBT
Number of contacts signal	4
Number of contacts power	3
Number of contacts PE	1
Contact-Ø signal	0.8 mm
Contact-Ø power	1.6 mm
Nominal current signal	5 A
Nominal current power	16 A
Nominal voltage at degree of pollution 3 signal	160 V~



## Contact insert M16 - 8-pole (solder in)

Item number 7001943137	
Nominal voltage at degree of pollution 3 power	320 V~
Test voltage signal	1500 V~
Test voltage power	1500 V~
Insulation resistance signal	> 10^8
Insulation resistance power	> 10^8
max. contact resistance signal	3 mOhm
Temperature range	-40°C to +125°C
Degree of Protection	3
Flammability	V-0 (UL 94)



85366930

Con	tact	insert	MI	6 -	8-po	le	(sol	der	in)	
ltem num	nber 700	1943137								

#### Commercial data **Packaging Unit** 25 EAN code 4033878500859 Weight 0.05681 kg ETIM 7 EC003557 ETIM 8 EC003557 ETIM 9 EC003557 eCl@ss 10.1 27440223

Note:			

Customs tariff number