


Contact insert M16 - 8-pole

Item number 7011944127



Technical data

Characteristic of connection	Crimp
Pole picture	4 + 4
Dip solder contacts length	10 mm
Insert	Pin
Material insulating body	PA 6 , PBT
Number of contacts signal	4
Number of contacts power	4
Contact-Ø signal	0.8 mm
Contact-Ø power	1.6 mm
Nominal current signal	5 A
Nominal current power	25 A
Nominal voltage at degree of pollution 3 signal	160 V~
Nominal voltage at degree of pollution 3 power	160 V~
Test voltage signal	1500 V~



Contact insert M16 - 8-pole

Item number 7011944127	
Test voltage power	1500 V~
Insulation resistance signal	> 10^8
Insulation resistance power	10^8
max. contact resistance signal	3 mOhm
max. contact resistance power	3 mOhm
Degree of Protection	3
Flammability	V-0 (UL 94)



Contact insert M16 - 8-pole

Item number 7011944127						
Commercial data						
B I . II .	50					
Packaging Unit	50					
EAN code	4033878008409					
\ COGO	10000, 0000 10,					
Weight	0.00683 kg					
eCl@ss 10.1	27440223					
eciess 10.1	2/440223					
Customs tariff number	85366930					

Note:			