


Item number 7084942102



Ansicht: Steckseite
View: mating side

Technical data

Characteristic of connection	Crimp
Number of poles	10
Pole picture	2 + 4 + 3 + PE
Coding	PE
Insert	Socket
Color Ethernet insert	white
Color contact insert	blue
Material Ethernet insert	PBT
Material insulating body	PBT
Number of contacts data	2
Number of contacts signal	4
Number of contacts power	3
Number of contacts PE	1
Contact-Ø data	1 mm
Contact-Ø signal	1 mm
Contact-Ø power	2 mm



Item number 7084942102

Terminal cross section data	0,14 - 1 mm ²
Terminal cross section signal	0,14 - 1,5 mm ²
Terminal cross section power	0,75 - 4 mm ²
Nominal current data	1,2 A
Nominal current signal	8 A
Nominal current power	28 A
Nominal voltage at degree of pollution 3 data	30 V~
Nominal voltage at degree of pollution 3 signal	300 V~
Nominal voltage at degree of pollution 3 power	600 V~
Insulation resistance data	> 10 ⁸
Insulation resistance signal	> 10 ⁸
Insulation resistance power	> 10 ⁸
max. contact resistance data	3 mOhm
max. contact resistance signal	3 mOhm
max. contact resistance power	3 mOhm
Temperature range	-40°C to +125°C
Degree of Protection	3
Flammability	V-0 (UL 94)
Suitable data contacts	7015961002
Suitable Signal contacts	7010941002 , 7010941022
Suitable power contacts	7010942002 , 7010942012
Suitable PE-/FE-contacts	7010942002 , 7010942012



Item number 7084942102

Commercial data

Packaging Unit	25
Weight	0.0084 kg
ETIM 7	EC003557
ETIM 8	EC003557
ETIM 9	EC003557
eCl@ss 10.1	27440223
Customs tariff number	85469010

Note:



Dimensions and specifications may be changed without prior notice

www.hummel.com