


# Contact insert M23 Power - 8-pole

Item number 7084943122



## Technical data

Characteristic of connection	Crimp
Number of poles	8
Pole picture	4 + 3 + PE
Coding	PE
Insert	Socket
Color contact insert	blue
Material insulating body	PA 6 , PBT
Number of contacts data	2
Number of contacts signal	4
Number of contacts power	3
Number of contacts PE	1
Contact-Ø signal	1 mm
Contact-Ø power	2 mm
Terminal cross section signal	0,14 - 1,5 mm <sup>2</sup>
Terminal cross section power	0,75 - 4 mm <sup>2</sup>
Nominal current signal	8 A

# Contact insert M23 Power - 8-pole

Item number 7084943122

Nominal current power	28 A
Nominal voltage at degree of pollution 3 power	600 V~
Test voltage signal	2500 V~
Test voltage power	4000 V~
Insulation resistance signal	$> 10^{13}$
max. contact resistance signal	3 mOhm
max. contact resistance power	3 mOhm
Temperature range	-40°C to +125°C
Degree of Protection	3
Flammability	V-0 (UL 94)
Suitable Signal contacts	7010941002 , 7010941022
Suitable power contacts	7010942002 , 7010942012
Suitable PE-/FE-contacts	7010942002 , 7010942012

# Contact insert M23 Power - 8-pole

Item number 7084943122

## Commercial data

Packaging Unit	25
EAN code	4033878001653
Weight	0.0085 kg
ETIM 7	EC003557
ETIM 8	EC003557
ETIM 9	EC003557
eCl@ss 10.1	27440223
Customs tariff number	85472000

Note:

