


Item number 7084946101



Ansicht: Steckseite
View: mating side

Technical data

Characteristic of connection	Crimp
Number of poles	14
Pole picture	6 + 4 + 3 + PE
Coding	PE
Insert	Pin
Color Ethernet insert	white
Color contact insert	blue
Material Ethernet insert	PBT
Number of contacts data	6
Number of contacts signal	4
Number of contacts power	3
Number of contacts PE	1
Contact-Ø data	0.6 mm
Contact-Ø signal	1 mm
Contact-Ø power	2 mm
Nominal current data	1,2 A



Item number 7084946101

Nominal current signal	8 A
Nominal current power	28 A
Nominal voltage at degree of pollution 3 data	30 V~
Nominal voltage at degree of pollution 3 signal	300 V~
Nominal voltage at degree of pollution 3 power	600 V~
Test voltage power	4000 V~
Insulation resistance signal	$> 10^8$
Insulation resistance power	10^8
max. contact resistance data	3 mOhm
max. contact resistance signal	3 mOhm
max. contact resistance power	3 mOhm
Temperature range	-40°C to +125°C
Degree of Protection	3
Suitable data contacts	7010960611
Suitable Signal contacts	7010941001 , 7010941021
Suitable power contacts	7010942001 , 7010942011
Suitable PE-/FE-contacts	7010942001 , 7010942011



Item number 7084946101

Commercial data

Packaging Unit	25
Weight	0.0098 kg
ETIM 7	EC003557
ETIM 8	EC003557
ETIM 9	EC003557
Customs tariff number	85469010

Note:



Dimensions and specifications may be changed without prior notice

www.hummel.com