


Housing incl. insert cable connector M40

Power - 6+6+4+PE

Item number 7710666000



Technical data

Housing type	Cable
Material housing	Zinc Die Cast
Material housing surface	Nickel
Insert	Socket
Installation type	-
Version	Screw
External thread plug-in side	-
Internal thread plug-in side	M40 x 1,5
Knurled nut-Ø plug-in side	46 mm
TWILOCK thread	-
Locking type	Screw
Shield	shielded
Seal type	O-Ring
Material seals/o-rings	FKM (FPM) , NBR
Cable diameter	13 - 18 mm
Length (L)	111.2 mm



Housing incl. insert cable connector M40

Power - 6+6+4+PE

Item number 7710666000

Wrench size (SW1/SW2)	40/38 mm
Temperature range	-40°C to +125°C
Degree of Protection	3
Protection class	IP 67 , IP 69 K
Characteristic of connection	Crimp
Number of poles	17
Pole picture	6 + 6 + 4 + PE
Color Ethernet insert	white
Color contact insert	blue
Material insulating body	PBT
Material Ethernet insert	PA 6
Number of contacts data	6
Number of contacts signal	6
Number of contacts power	4
Number of contacts PE	1
Contact-Ø data	0.6 mm
Contact-Ø signal	1 mm
Contact-Ø power	3.6 mm
Terminal cross section data	0,05 - 0,34 mm ²
Terminal cross section signal	0,14 - 1,5 mm ²
Terminal cross section power	2,5 - 16 mm ²
Crimp range	0.05 - 16 mm ²
Nominal current data	1,2 A
Nominal current signal	7 A
Nominal current power	55 A



Housing incl. insert cable connector M40

Power - 6+6+4+PE

Item number 7710666000	
Nominal voltage at degree of pollution 3 data	30 V~
Nominal voltage at degree of pollution 3 signal	150 V~
Nominal voltage at degree of pollution 3 power	600 V~
Test voltage data	840 V~
Test voltage signal	840 V~
Test voltage power	4000 V~
Insulation resistance data	10 ⁸
Insulation resistance signal	10 ⁸
Insulation resistance power	10 ⁸
max. contact resistance data	0,003 mOhm
max. contact resistance signal	3 mOhm
max. contact resistance power	1 mOhm
Minimum mating cycles	> 500
Suitable data contacts	7010960612
Suitable Signal contacts	7015961002 , 7015961012
Suitable power contacts	7015963602 , 7015963612 , 7015963622 , 7015963632
Suitable PE-/FE-contacts	7015963602 , 7015963612 , 7015963622 , 7015963632



Housing incl. insert cable connector M40

Power - 6+6+4+PE

Item number 7710666000

Commercial data

Packaging Unit	5
EAN code	4033878012468
Weight	0.40515 kg
ETIM 7	EC002635
ETIM 8	EC002635
ETIM 9	EC002635
eCl@ss 10.1	27440102
Customs tariff number	85366990

Note:

