

## Fast and clean assembly



- // Ideal for renovation and rehabilitation of heating systems
- // Safe installation, also within a difficult work environment
- // Suitable for all common steel pipes installed in the building
- // No welding and reaming necessary

Steel pipe adapter case content

- // High temperature and pressure resistance
- // Flush-mounted usage according to DIN 18380

Туре	Case content	Item No.
with internal thread, $3/8" \times G 1/2$ , nickel-plated brass	2 pieces	2 356 3812 01
with internal thread, $1/2$ " x G $1/2$ , nickel-plated brass	2 pieces	2 356 1212 01
with external thread, $3/8" \times R 1/2$ external thread, nickel-plated brass	2 pieces	2 355 3812 01
with external thread, $1/2$ " x R $1/2$ external thread, nickel-plated brass	2 pieces	2 355 1212 01
with external thread, $3/4$ " x R $3/4$ external thread, nickel-plated brass	2 pieces	2 355 3434 01
with external thread, 1" $\times$ R1 external thread, nickel-plated brass	2 pieces	2 355 1010 01
with euro cone, $3/8$ " x G $3/4$ internal thread, nickel-plated brass	2 pieces	2 353 3834 01
with euro cone, $1/2$ " x G $3/4$ internal thread, nickel-plated brass	2 pieces	2 353 1234 01
with euro cone, $3/8$ " x G $3/4$ external thread, nickel-plated brass	2 pieces	2 354 3834 01
with euro cone, 1/2" x G 3/4 external thread, nickel-plated brass	2 pieces	2 354 1234 01

with euro cone, 3/4" x G 3/4 external thread, nickel-plated brass

2 354 3434 01

2 pieces