


CABLE GLANDS AND CABLE PROTECTION SYSTEMS







SMART & RELIABLE CONNECTIONS

HUMMEL AG

HUMMEL AG stands for reliability and soundness. That makes the medium-sized family-owned company in its third generation, future-proof and calculable for its business partners. Reliability and top quality also characterise the products. Customers value HUMMEL AG as an innovative producer of high-quality electromechanical components and customised products.

With in-house development, in-house production and in-house assembly, the company has an remarkable production depth. As a renowned manufacturer of cable glands, connectors, special customised parts and heating accessories, HUMMEL is equally specialised in plastic machining and metalworking.

Apart from its headquarters in Denzlingen in southern Baden, HUMMEL has production locations in Waldkirch, in France, China, Italy, Brazil and India. There are HUMMEL branches in Scandinavia, England, Russia, Poland and Korea. It also has a worldwide network with sales partners.

HUMMEL cable glands are premium segment products. The choice is enormous, the quality is outstanding. The cable glands made of plastic, brass or stainless steel have been put to the test for many years, function very reliably and have all relevant approvals.

HUMMEL is a certified manufacturer of components for which particular explosion protection is specified and which are used in particularly rough environments.

Table of contents

Legend	6		Accessories	65	
Legend and list of abbreviations	6		Locknuts		
			Plugs	71	
			Reducers	80	
			Adapter	89	
			Angles	92	
			Inserts	93	
			O-rings & seal rings	94	
			Others	97	
	Plastic cable glands	9		Ex cable glands	101
HSK-K	11		HSK-K-Ex-Active	102	
HSK-K-Multi	16		HSK-K-Multi-Ex-Active	105	
HSK-K-Flaka	17		HSK-K-MZ-Ex	106	
HSK-K-PVDF	18		HSK-M-Ex	107	
HSK-K-Flex	20		HSK-M-PVDF-Ex	111	
HSK-W	21		HSK-M-Multi-Ex	112	
HSK-W-Flex	22		HSK-M-Flaka-Ex	113	
	Metal cable glands	23	HSK-MZ-Ex	114	
HSK-M	25		HSK-INOX-Ex	115	
HSK-M-PVDF	28		HSK-INOX-PVDF-Ex	116	
HSK-M-Multi	30		HSK-M-Ex d	117	
HSK-M-Flex	31		HSK-M-PVDF-Ex d	118	
HSK-MZ	32		HSK-MZ-Ex d	119	
HSK-Mini	33		HSK-INOX-Ex d	120	
HSK-Mini-INOX	34		HSK-INOX-PVDF-Ex d	121	
HSK-XL	35				
HSK-INOX	36				
HSK-INOX-PVDF	38				
WADI-A-FKM	39				
	EMC cable glands	41		EMC-Ex e cable glands	123
HSK-M-EMC-D	43		HSK-M-EMC-D-Ex	124	
METRICA-M-EMC-E	45		HSK-M-EMC-Ex	125	
HSK-M-EMC	46		HSK-MZ-EMC-Ex	127	
HSK-M-PVDF-EMC	49		HSK-INOX-EMC-Ex	128	
HSK-M-Flex-EMC	50				
HSK-MZ-EMC	51				
HSK-Mini-EMC	52				
HSK-INOX-EMC	53				
	Cable glands for special applications	55		Ex Accessories	129
VariaPro Rail	57		Plugs Ex	130	
VariaPro Temp	58		Reducers Ex	140	
HSK-INOX-HD-Pro	59				
	DIN cable glands	61		EXIOS cable glands for "Hazardous Areas"	145
DIN 46320 metal	62		EXIOS Standard	146	
DIN 46320 Z	63		EXIOS MZ	149	
			EXIOS Barrier	150	
			EXIOS A2F	153	
			EXIOS Accessories	156	
				Cable protection systems	161
			Plastic conduits	162	
			Plastic fittings	163	

Index	170
alphabetical	170
numeric	172

Technical information	174
Thread dimensions	174

HUMMEL International	175
----------------------	-----

Installation instructions

Multiple seal insert: The cable diameter may be 20 % less than the drill diameter, however, maximum 1 mm less than the hole diameter.

Ribbon cable seal insert: The cable used may be less than the clamping range specified by the manufacturer by maximum 1 mm in length and maximum 1 mm in width. The geometries of the cable and the hole pattern must match (half-round or straight at the sides).

Fire protection classes according to UL94

V0: self-extinguishing after 10 seconds at the latest, burning droplets are not permitted, afterglow for maximum 30 seconds

V1: self-extinguishing after 30 seconds at the latest, burning droplets are not permitted, afterglow for maximum 60 seconds

V2: self-extinguishing after 30 seconds at the latest, burning droplets are permitted

Abbreviations used

CR	Chlorinated rubber
FKM	Fluorinated rubber
Ms	Brass
NBR	Acrylonitrile butadiene rubber
PA	Polyamide
PE	Polyethylene
PP	Polypropylene
PVC	Polyvinylchlorid
PVDF	Polyvinylidene fluoride
VMQ	Silicone

Note on the storage of items with elastomer components

// Storage protected from light

// Protection against ozone exposure

// Storage at room temperature

// Protection against moisture

For further information see DIN 7716

Norms



Railway Fire protection on railway vehicles according to EN 45545



Chemicals Resistant to acids and chemicals



EMC Cable glands with EMC protection (electromagnetic compatibility)



Ex d/ Ex e Explosion protection Ex d (flameproof enclosure) and Ex e (increased safety)



Leadfree Cable glands made of lead-free brass



RoHS Restrictions of Hazardous Substances: EU Directive on the use of hazardous substances



Temperature Temperature range from -60°C to $+200^{\circ}\text{C}$

Abbreviations and techn. features

A [mm]	Linear dimension A in mm
A1 [mm]	Clamping range 1
A2 [mm]	Clamping range 2
max. A2 [mm]	max. cable diameter, clamping range 2
max. A3 [mm]	max. cable diameter, clamping range 3
AG	External thread
B [mm]	Linear dimension B in mm
C [mm]	Linear dimension C in mm
d [mm]	Diameter in mm
D [mm]	Diameter in mm
DN	Nominal diameter in mm
E [mm]	Linear dimension E in mm
F [mm]	Linear dimension F in mm
GL [mm]	Thread length in mm
H [mm]	Height in mm
h [mm]	Height
H1 [mm]	Height 1 in mm
H2 [mm]	Height 2 in mm
IG	Internal thread
Item-No	Item number
K1 [mm]	Reinforcement, clamping ring 1 in mm
K2 [mm]	Reinforcement, clamping ring 2 in mm
K3 [mm]	Reinforcement, clamping ring 3 in mm
L [mm]	Length in mm
s [mm]	Thickness
SW [mm]	Width across flats in mm
Ø [mm]	Diameter in mm
⌀	Cable diameter in mm
	Tightening torque in Nm
	Allen key
	Minimum bending radius in mm

Certificates

	ABS	Approval for ship building and offshore applications
	ATEX	Certification for components in potentially explosive atmospheres (ATEX Directive 2014/34/EU)
	CE	EU Declaration of Conformity
	CSA	CSA approval for Canadian Standards
	CSA C/US	CSA approval for Canadian and US Standards
	DNV	Certificate for use in the maritime sector
	ECOLAB	Certified resistance to ECOLAB cleaning agent
	IECEx	Certification for components in potentially explosive atmospheres
	INMETRO	Certification for components in potentially explosive atmospheres in Brazil
	ktl	Certificate for the export of components to Korea
	UL	UL approval for US Standards
	UL f1	Certificate of outdoor resistance according to UL 746 C
	UL C	UL approval for Canadian and US Standards
	UR	UL approval recognized for US Standards
	UR C	UL approval recognized for Canadian and US Standards
	VDE	Seal of approval by the VDE, Association for Electrical Engineering, Electronics and Information Technology

HSK-M cable glands are also available lead-free

The cable glands of the premium HSK-M series are also available as lead-free versions. This means that users already have an alternative to conventional metal glands. The lead-free cable glands are an investment in future-proofing and sustainability. They already meet the RoHS and REACH requirements of tomorrow.

The metric versions M12 to M63 of the HSK-M cable gland series are available. Customised further options are offered on request.

Customers do not have to worry about functionality. All technical properties such as temperature range, leak-tightness, impact resistance and strain relief remain unchanged. The existing approvals also apply equally to the lead-free cable glands.

They are easy to handle. The lead-free cable glands retain the old article numbers and are simply supplemented with the suffix "LF" (Lead Free). The product itself is also marked with the suffix "LF" on the union nut. This prevents mix-ups.



PLASTIC CABLE GLANDS

HUMMEL HSK-K series cable glands lie in the premium segment and meet the highest demands for quality and safety. When it comes to fire protection, sealing ability and impact resistance, numerous certifications prove performance at the highest level. HUMMEL customers can rely on this.

- // HSK-K: Polyamide cable glands
- // HSK-K-PVDF: Cable glands for use at high temperatures
- // HSK-K-Multi: Glands for applications with several cables
- // HSK-K-Flaka: With fitting for flat cables
- // HSK-K-Flex: Offers bending protection for dynamic applications
- // HSK-W: Versions with a folding bracket for mounting with 90° cabling

In each case, HUMMEL offers different clamping areas, thread lengths, thread types and various sealing materials for different temperature ranges. The cable glands have all relevant approvals for international markets and a wide range of sectors.



HSK-K: The right solution for every application

HUMMEL has a huge range of cable glands for industrial applications on offer. The plastic cable glands of the HSK-K series meet all requirements for tough industrial environments indoors and outdoors. They have all the relevant certificates and can therefore be used worldwide, which is why customers have the choice between metric thread types, PG and NPT threads. There are also cable glands for flat cables, ones with multiple inserts and glands with a flexible cable outlet.


- // Protection class IP 54, IP 68 up to 10 bar / 30 min and IP 69K
- // RoHS and REACH/SVHC compliant
- // Free of conflict materials
- // Free of halogen and phosphorus
- // Fire protection class V0 according to UL94
- // Outdoor resistant polyamide according to UL 746C f1 (HSK-K black)


Overlapping clamping plates prevent the moulded seal from being torn out and thus increase the safety of the system

The chambered moulded seal results in protection class IP 68 up to 10 bar / 30 min

The trapezoidal thread guarantees a stable transfer of force

A chambered O-ring seals the gland on the housing optimally and guarantees a tight fit during assembly





Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Type Rating by	UL 50E / 4 / 4X / 6 (with additional O-ring) / 12
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS


- // Other sizes and colors on request
- // With additional premounted O-ring on request
- // Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No black	Item-No grey
M12 x 1,5	2 – 5	8	21	15/15	1,5	1.209.1201.51	1.209.1200.51
M12 x 1,5	3 – 6,5	8	21	15/15	1,5	1.209.1201.50	1.209.1200.50
M16 x 1,5	2 – 6	8	22	19/19	2	1.209.1601.51	1.209.1600.51
M16 x 1,5	4 – 8	8	22	19/19	2	1.209.1601.50	1.209.1600.50
M16 x 1,5	5 – 10	8	25	22/22	3	1.219.1601.50	1.219.1600.50
M20 x 1,5	5 – 9	9	27	24/24	3	1.209.2001.51	1.209.2000.51
M20 x 1,5	6 – 12	9	27	24/24	4,5	1.209.2001.50	1.209.2000.50
M20 x 1,5	10 – 14	9	28	27/27	4,5	1.219.2001.50	1.219.2000.50
M25 x 1,5	9 – 16	11	31	33/33	4	1.209.2501.51	1.209.2500.51
M25 x 1,5	13 – 18	11	31	30/30	5	1.219.2501.50	1.219.2500.50
M25 x 1,5	13 – 18	11	31	33/33	5	1.209.2501.50	1.209.2500.50
M32 x 1,5	13 – 20	11	39	42/42	6	1.209.3201.51	1.209.3200.51
M32 x 1,5	18 – 25	11	39	42/42	6,5	1.209.3201.50	1.209.3200.50
M40 x 1,5	20 – 26	13	48	53/53	9	1.209.4001.51	1.209.4000.51
M40 x 1,5	22 – 32	13	48	53/53	10	1.209.4001.50	1.209.4000.50
M50 x 1,5	25 – 31	13	49	60/60	11	1.209.5001.51	1.209.5000.51
M50 x 1,5	32 – 38	13	49	60/60	15	1.209.5001.50	1.209.5000.50
M63 x 1,5	29 – 35	14	49	65/68	12	1.209.6301.51	1.209.6300.51
M63 x 1,5	37 – 44	14	49	65/68	18	1.209.6301.50	1.209.6300.50



Plastic cable glands

HSK-K (metric-long)




Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Type Rating by	UL 50E / 4 / 4X / 6 (with additional O-ring) / 12
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS

- // Other sizes and colors on request
- // With additional premounted O-ring on request
- // Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No black	Item-No grey
M12 x 1,5	2 – 5	15	21	15/15	1,5	1.209.1201.31	1.209.1200.31
M12 x 1,5	3 – 6,5	15	21	15/15	1,5	1.209.1201.30	1.209.1200.30
M16 x 1,5	2 – 6	15	22	19/19	2	1.209.1601.31	1.209.1600.31
M16 x 1,5	4 – 8	15	22	19/19	2	1.209.1601.30	1.209.1600.30
M16 x 1,5	5 – 10	15	25	22/22	3	1.219.1601.30	1.219.1600.30
M20 x 1,5	5 – 9	15	27	24/24	3	1.209.2001.31	1.209.2000.31
M20 x 1,5	6 – 12	15	27	24/24	4,5	1.209.2001.30	1.209.2000.30
M20 x 1,5	10 – 14	15	28	27/27	4,5	1.219.2001.30	1.219.2000.30
M25 x 1,5	9 – 16	15	31	33/33	4	1.209.2501.31	1.209.2500.31
M25 x 1,5	13 – 18	15	31	33/33	5	1.209.2501.30	1.209.2500.30
M32 x 1,5	13 – 20	15	39	42/42	6	1.209.3201.31	1.209.3200.31
M32 x 1,5	18 – 25	15	39	42/42	6,5	1.209.3201.30	1.209.3200.30
M40 x 1,5	20 – 26	18	48	53/53	9	1.209.4001.31	
M40 x 1,5	22 – 32	18	48	53/53	10	1.209.4001.30	
M50 x 1,5	25 – 31	18	49	60/60	11	1.209.5001.31	
M50 x 1,5	32 – 38	18	49	60/60	15	1.209.5001.30	
M63 x 1,5	29 – 35	18	49	65/68	12	1.209.6301.31	
M63 x 1,5	37 – 44	18	49	65/68	18	1.209.6301.30	





Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Type Rating by	UL 50E / 4 / 4X / 6 (with additional O-ring) / 12
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS


- // Other sizes and colors on request
- // With additional premounted O-ring on request
- // Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No black	Item-No grey
PG 7	2 – 5	8	21	15/15	1,5	1.209.0701.15	1.209.0700.15
PG 7	3 – 6,5	8	21	15/15	1,5	1.209.0701.14	1.209.0700.14
PG 9	2 – 6	8	22	19/19	2	1.209.0901.15	1.209.0900.15
PG 9	4 – 8	8	22	19/19	2	1.209.0901.14	1.209.0900.14
PG 11	3 – 7	8	25	22/22	2,5	1.209.1101.15	1.209.1100.15
PG 11	5 – 10	8	25	22/22	3	1.209.1101.14	1.209.1100.14
PG 13,5	5 – 9	9	27	24/24	3	1.209.1301.15	1.209.1300.15
PG 13,5	6 – 12	9	27	24/24	4,5	1.209.1301.14	1.209.1300.14
PG 16	7 – 12	10	28	27/27	3,5	1.209.1601.15	1.209.1600.15
PG 16	10 – 14	10	28	27/27	4,5	1.209.1601.14	1.209.1600.14
PG 21	9 – 16	11	31	33/33	4	1.209.2101.15	1.209.2100.15
PG 21	13 – 18	11	31	33/33	5	1.209.2101.14	1.209.2100.14
PG 29	13 – 20	11	39	42/42	6	1.209.2901.15	1.209.2900.15
PG 29	18 – 25	11	39	42/42	6,5	1.209.2901.14	1.209.2900.14
PG 36	20 – 26	13	48	53/53	9	1.209.3601.15	
PG 36	22 – 32	13	48	53/53	10	1.209.3601.14	
PG 42	25 – 31	13	49	60/60	11	1.209.4201.15	
PG 42	32 – 38	13	49	60/60	15	1.209.4201.14	
PG 48	29 – 35	14	49	65/65	12	1.209.4801.15	
PG 48	37 – 44	14	49	65/65	18	1.209.4801.14	



Plastic cable glands

HSK-K (PG-long)




Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Type Rating by	UL 50E / 4 / 4X / 6 (with additional O-ring) / 12
Temperature range	-40°C to +100°C
Colour	black
RAL	9005

RoHS

- // Other sizes and colors on request
- // With additional premounted O-ring on request
- // Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
PG 7	2 – 5	15	21	15/15	1,5	1.209.0701.61
PG 7	3 – 6,5	15	21	15/15	1,5	1.209.0701.60
PG 9	4 – 8	15	22	19/19	2	1.209.0901.60
PG 11	3 – 7	15	25	22/22	2,5	1.209.1101.61
PG 11	5 – 10	15	25	22/22	3	1.209.1101.60
PG 13,5	5 – 9	15	27	24/24	3	1.209.1301.61
PG 13,5	6 – 12	15	27	24/24	4,5	1.209.1301.60
PG 16	7 – 12	15	28	27/27	3,5	1.209.1601.61
PG 16	10 – 14	15	28	27/27	4,5	1.209.1601.60
PG 21	9 – 16	15	31	33/33	4	1.209.2101.61
PG 21	13 – 18	15	31	33/33	5	1.209.2101.60
PG 29	13 – 20	15	39	42/42	6	1.209.2901.61
PG 29	18 – 25	15	39	42/42	6,5	1.209.2901.60
PG 36	20 – 26	18	48	53/53	9	1.209.3601.61
PG 36	22 – 32	18	48	53/53	10	1.209.3601.60





Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Type Rating by	UL 50E / 4 / 4X / 6 (with additional O-ring) / 12
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS


- // Other sizes and colors on request
- // With additional premounted O-ring on request
- // Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No black	Item-No grey
NPT 3/8"	2 – 6	15	22	19/22	2	1.209.3801.71	1.209.3800.71
NPT 3/8"	4 – 8	15	22	19/22	2	1.209.3801.70	1.209.3800.70
NPT 1/2"	5 – 9	13	27	24/24	3	1.209.1201.71	1.209.1200.71
NPT 1/2"	6 – 12	13	27	24/24	4,5	1.209.1201.70	1.209.1200.70
NPT 1/2"	10 – 14	13	28	27/27	4,5	1.209.1217.70	1.209.1216.70
NPT 3/4"	9 – 16	14	31	33/33	4	1.209.3401.71	1.209.3400.71
NPT 3/4"	13 – 18	14	31	33/33	5	1.209.3401.70	1.209.3400.70
NPT 1"	13 – 20	19	39	42/42	6	1.209.1001.71	1.209.1000.71
NPT 1"	18 – 25	19	39	42/42	6,5	1.209.1001.70	1.209.1000.70
NPT 1 1/4"	13 – 20	16	39	42/46	6	1.209.5401.71	
NPT 1 1/4"	18 – 25	16	39	42/46	6,5	1.209.5401.70	
NPT 1 1/2"	20 – 26	20	48	53/53	9	1.209.6401.71	
NPT 1 1/2"	22 – 32	20	48	53/53	10	1.209.6401.70	



Plastic cable glands

HSK-K-Multi (metric, PG, NPT)




Material	Polyamide V0 according to UL94
Seal	Elastomer
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS

- // With additional premounted O-ring on the connection thread on request
- // Elongated threads on request
- // Further seal inserts on request

AG	GL mm	H mm	SW1/SW2 mm	Nm	Number of holes x d	Item-No black	Item-No grey
M16 x 1,5	8	22	19/19	3	2 x 3	1.597.1601.51	
M20 x 1,5	9	27	24/24	4,5	2 x 5	1.597.2003.51	1.597.2003.50
M20 x 1,5	9	28	27/27	3	2 x 6	1.597.2005.51	
M25 x 1,5	11	31	33/33	5	3 x 7	1.597.2501.51	1.597.2501.50
M25 x 1,5	11	31	33/33	5	4 x 6	1.597.2500.51	1.597.2500.50
M32 x 1,5	11	39	42/42	6,5	4 x 9		1.597.3201.50
M32 x 1,5	11	39	42/42	6,5	6 x 6,5	1.597.3200.51	1.597.3200.50
M40 x 1,5	13	48	53/53	10	2 x 15	1.597.4003.51	
M40 x 1,5	13	48	53/53	10	7 x 9	1.597.4001.51	1.597.4001.50
M63 x 1,5	14	49	65/68	22	3 x 18	1.597.6302.51	
M63 x 1,5	14	49	65/68	22	6 x 12	1.597.6301.51	
PG 9	8	22	19/19	3	2 x 3	1.597.0901.01	
PG 11	8	25	22/22	3	2 x 4		1.597.1102.00
PG 11	8	25	22/22	3	3 x 3	1.597.1101.01	
PG 16	10	28	27/27	4,5	2 x 6	1.597.1605.01	1.597.1605.00
PG 16	10	28	27/27	4,5	6 x 4	1.597.1604.01	
PG 21	11	31	33/33	5	4 x 6	1.597.2100.01	
NPT 3/8"	15	22	19/22	3	2 x 3	1.597.3801.71	
NPT 1/2"	13	27	24/24	4,5	2 x 5	1.597.1203.71	
NPT 1/2"	13	27	24/24	4,5	3 x 4	1.597.1202.71	
NPT 1/2"	13	28	27/27	4,5	2 x 6	1.597.1221.71	1.597.1221.70
NPT 1/2"	13	28	27/27	4,5	6 x 4	1.597.1220.71	
NPT 3/4"	14	31	33/33	5	3 x 7	1.597.3401.71	1.597.3401.70
NPT 3/4"	14	31	33/33	5	4 x 6	1.597.3400.71	
NPT 1"	19	39	42/42	6,5	4 x 9	1.597.1001.71	
NPT 1"	19	39	42/42	6,5	6 x 6,5	1.597.1000.71	
NPT 1 1/2"	20	48	53/53	10	5 x 9	1.597.6400.71	1.597.6400.70
NPT 1 1/2"	20	48	53/53	10	7 x 9	1.597.6401.71	



Material	Polyamide V0 according to UL94
Seal	Elastomer
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS


- // With additional premounted O-ring on the connection thread on request
- // Elongated threads on request
- // Further seal inserts on request

AG	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No black	Item-No grey
M20 x 1,5	9	27	24/24			1.587.2011.50
M20 x 1,5	9	28	27/27	4,5	1.587.2018.51	1.587.2018.50
M25 x 1,5	11	31	33/33	5		1.587.2500.50
NPT 1/2"	13	28	27/27	4,5	1.587.1216.71	
NPT 3/4"	14	31	33/33	5	1.587.3400.71	
NPT 1"	19	39	42/42	6,5	1.587.1000.71	



Plastic cable glands

HSK-K-PVDF (metric, NPT)



Material	PVDF V0 according to UL94
Seal	FKM
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Type Rating by	UL 50E / 4 / 4X / 6 (with additional O-ring) / 12
Temperature range	-35°C to +150°C
Colour	natural


RoHS

// Other sizes on request

// With additional premounted O-ring on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	Nm	Item-No
M12 x 1,5	2 – 5	8	21	15/15	1,5	1.299.1200.51
M12 x 1,5	3 – 6,5	8	21	15/15	1,5	1.299.1200.50
M16 x 1,5	2 – 6	8	22	19/19	2	1.299.1600.51
M16 x 1,5	4 – 8	8	22	19/19	2	1.299.1600.50
M20 x 1,5	5 – 9	9	27	24/24	3	1.299.2000.51
M20 x 1,5	6 – 12	9	27	24/24	3	1.299.2000.50
M25 x 1,5	9 – 16	11	31	33/33	4	1.299.2500.51
M25 x 1,5	13 – 18	11	31	33/33	4	1.299.2500.50
M32 x 1,5	13 – 20	11	39	42/42	6	1.299.3200.51
M32 x 1,5	18 – 25	11	39	42/42	6	1.299.3200.50
NPT 3/8"	2 – 6	15	22	19/22	2	1.299.3800.71
NPT 3/8"	4 – 8	15	22	19/22	2	1.299.3800.70
NPT 1/2"	5 – 9	13	27	24/24	3	1.299.1200.71
NPT 1/2"	6 – 12	13	27	24/24	4,5	1.299.1200.70
NPT 1/2"	10 – 14	13	28	27/27	4,5	1.299.1216.70
NPT 3/4"	9 – 16	14	31	33/33	4	1.299.3400.71
NPT 3/4"	13 – 18	14	31	33/33	5	1.299.3400.70





Material	PVDF V0 according to UL94
Seal	FKM
Protection class	IP 54 / IP 68 with additional O-ring: IP68 - 10bar/30min / IP 69 K
Type Rating by	UL 50E / 4 / 4X / 6 (with additional O-ring) / 12
Temperature range	-35°C to +150°C
Colour	natural

RoHS

// Other sizes on request


// With additional premounted O-ring on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
PG 7	2 – 5	8	21	15/15	1,5	1.299.0700.15
PG 7	3 – 6,5	8	21	15/15	1,5	1.299.0700.14
PG 9	2 – 6	8	22	19/19	2	1.299.0900.15
PG 9	4 – 8	8	22	19/19	2	1.299.0900.14
PG 11	3 – 7	8	25	22/22	3	1.299.1100.15
PG 11	5 – 10	8	25	22/22	3	1.299.1100.14
PG 13,5	5 – 9	9	27	24/24	3	1.299.1300.15
PG 13,5	6 – 12	9	27	24/24	3	1.299.1300.14
PG 16	7 – 12	10	28	27/27	3,5	1.299.1600.15
PG 16	10 – 14	10	28	27/27	4,5	1.299.1600.14
PG 21	13 – 18	11	31	33/33	4	1.299.2100.14
PG 36	22 – 32	13	48	53/53	10	1.299.3600.14
PG 42	32 – 38	13	49	60/60	15	1.299.4200.14



Plastic cable glands

HSK-K-Flex (metric, PG, NPT)




Material	Polyamide
Seal	NBR
Protection class	IP 54 / IP 68 with additional O-ring: IP 68 - 10bar/30min / IP 69 K
Temperature range	-40°C to +100°C
Colour	black
RAL	9005

RoHS

- // Other sizes and colors on request
- // Elongated threads on request
- // With additional premounted O-ring on the connection thread on request
- // Other sealing material e.g. Silicone on request

AG	Øk mm	d mm	H mm	SW1/SW2 mm	⌀ Nm	GL mm	Item-No
M12 x 1,5	2 – 5	7,23	54	15/15	1,5	8	1.293.1201.51
M12 x 1,5	3 – 6,5	7,23	54	15/15	1,5	8	1.293.1201.50
M16 x 1,5	3 – 7	10,71	78	22/22	2,5	8	1.294.1601.51
M16 x 1,5	4 – 8	8,88	63	19/19	2	8	1.293.1601.50
M16 x 1,5	5 – 10	10,71	78	22/22	3	8	1.294.1601.50
M20 x 1,5	5 – 9	13,25	90	24/24	3	9	1.293.2001.51
M20 x 1,5	6 – 12	13,25	90	24/24	4,5	9	1.293.2001.50
M20 x 1,5	10 – 14	15,39	100	27/27	4,5	9	1.294.2001.50
M25 x 1,5	9 – 16	20,02	114	33/33	4	11	1.293.2501.51
M25 x 1,5	13 – 18	20,02	114	33/33	5	11	1.293.2501.50
PG 7	2 – 5	7,23	54	15/15	1,5	8	1.293.0701.15
PG 7	3 – 6,5	7,23	54	15/15	1,5	8	1.293.0701.14
PG 9	2 – 6	8,88	63	19/19	2	8	1.293.0901.15
PG 9	4 – 8	8,88	63	19/19	2	8	1.293.0901.14
PG 11	3 – 7	10,71	78	22/22	2,5	8	1.293.1101.15
PG 11	5 – 10	10,71	78	22/22	3	8	1.293.1101.14
PG 13,5	5 – 9	13,25	90	24/24	3	9	1.293.1301.15
PG 13,5	6 – 12	13,25	90	24/24	4,5	9	1.293.1301.14
PG 16	7 – 12	15,39	100	27/27	3,5	10	1.293.1601.15
PG 16	10 – 14	15,39	100	27/27	4,5	10	1.293.1601.14
PG 21	9 – 16	20,02	114	33/33	4	11	1.293.2101.15
PG 21	13 – 18	20,02	114	33/33	5	11	1.293.2101.14
NPT 3/8"	2 – 6	8,88	63	19/22	2	15	1.293.3801.71
NPT 3/8"	4 – 8	8,88	63	19/22	2	15	1.293.3801.70
NPT 1/2"	5 – 9	13,25	90	24/24	3	13	1.293.1201.71
NPT 1/2"	6 – 12	13,25	90	24/24	4,5	13	1.293.1201.70
NPT 1/2"	7 – 12	15,39	100	27/27	3,5	13	1.293.1217.71
NPT 1/2"	10 – 14	15,39	100	27/27	4,5	13	1.293.1217.70
NPT 3/4"	9 – 16	20,02	114	33/33	4	14	1.293.3401.71
NPT 3/4"	13 – 18	20,02	114	33/33	5	14	1.293.3401.70





Material	Polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 - 1bar/30min
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS

// Other sizes and colors on request


// Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	L mm	SW mm	Nm	Item-No black	Item-No grey
M16 x 1,5	2 – 6	8	23	45	19	2,5	1.313.1601.51	1.313.1600.51
M16 x 1,5	4 – 8	8	23	45	19	2,5	1.313.1601.50	1.313.1600.50
M20 x 1,5	5 – 9	9	30,5	57	24	4	1.313.2001.51	1.313.2000.51
M20 x 1,5	6 – 12	9	30,5	57	24	4	1.313.2001.50	1.313.2000.50
M25 x 1,5	9 – 16	11	40	73	33	6	1.313.2501.51	1.313.2500.51
M25 x 1,5	13 – 18	11	40	73	33	6	1.313.2501.50	1.313.2500.50
M32 x 1,5	13 – 20	11	51,5	91	42	9	1.313.3201.51	
M32 x 1,5	18 – 25	11	51,5	91	42	9	1.313.3201.50	1.313.3200.50
PG 9	2 – 6	8	23	45	19	2,5	1.313.0901.15	
PG 9	4 – 8	8	23	45	19	2,5	1.313.0901.14	
PG 11	3 – 7	8	27	50	22	2,5	1.313.1101.15	
PG 11	5 – 10	8	27	50	22	4	1.313.1101.14	
PG 13,5	5 – 9	9	30,5	57	24	4	1.313.1301.15	
PG 13,5	6 – 12	9	30,5	57	24	4	1.313.1301.14	
PG 16	7 – 12	10	32,5	59	27	4	1.313.1601.15	
PG 16	10 – 14	10	32,5	59	27	6	1.313.1601.14	
PG 21	9 – 16	11	40	73	33	6	1.313.2101.15	
PG 21	13 – 18	11	40	73	33	6	1.313.2101.14	
PG 29	13 – 20	11	51,5	91	42	9	1.313.2901.15	
PG 29	18 – 25	11	51,5	91	42	9	1.313.2901.14	
NPT 3/8"	2 – 6	15	23	45	19	2,5	1.313.3801.71	
NPT 3/8"	4 – 8	15	23	45	19	2,5	1.313.3801.70	
NPT 1/2"	5 – 9	13	32,5	57	24	4	1.313.1201.71	
NPT 1/2"	6 – 12	13	32,5	57	24	4	1.313.1201.70	
NPT 1/2"	7 – 12	13	32,5	59	27	4	1.313.1217.71	
NPT 1/2"	10 – 14	13	32,5	59	27	6	1.313.1217.70	
NPT 3/4"	9 – 16	13	40	73	33	6	1.313.3401.71	
NPT 3/4"	13 – 18	13	40	73	33	6	1.313.3401.70	
NPT 1"	13 – 20	19	51,5	91	42	9	1.313.1001.71	
NPT 1"	18 – 25	19	51,5	91	42	9	1.313.1001.70	



Plastic cable glands

HSK-W-Flex (metric, PG, NPT)



Material	Polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 - 1bar/30min
Temperature range	-40°C to +100°C
Colour	black
RAL	9005

RoHS

// Other sizes and colors on request

// Other sealing material e.g. Silicone on request

AG	Øk mm	d mm	GL mm	H mm	L mm	SW mm	⌀ Nm	Item-No
M16 x 1,5	4 – 8	8,88	8	23	85	19	2,5	1.314.1601.50
M20 x 1,5	6 – 12	13,25	9	30,5	119	24	4	1.314.2001.50
M25 x 1,5	9 – 16	20,02	11	40	156	33	6	1.314.2501.51
M25 x 1,5	13 – 18	20,02	11	40	156	33	6	1.314.2501.50
PG 11	3 – 7	10,71	8	27	103	22	2,5	1.314.1101.15
PG 11	5 – 10	10,71	8	27	103	22	4	1.314.1101.14
PG 13,5	6 – 12	13,25	9	30,5	119	24	4	1.314.1301.14
NPT 3/8"	4 – 8	8,88	15	23	85	19	2,5	1.314.3801.70
NPT 1/2"	5 – 9	13,25	13	30,5	119	24	4	1.314.1201.71
NPT 1/2"	6 – 12	13,25	13	30,5	119	24	4	1.314.1201.70
NPT 1/2"	10 – 14	15,39	13	31,5	130	27	6	1.314.1217.70
NPT 3/4"	9 – 16	20,02	13	40	156	33	6	1.314.3401.71
NPT 3/4"	13 – 18	20,02	13	40	156	33	6	1.314.3401.70



METAL CABLE GLANDS

Brass (nickel-plated) and stainless steel cable glands are very robust and generally suitable for industrial applications. The HSK series offers a huge range of solutions – for common, and also very unusual, applications. Uncompromising use of high-quality materials ensures the outstanding quality of HUMMEL products.

- // HSK-M: Nickel-plated brass cable glands
- // HSK-INOX: Stainless steel cable glands in a range of variants
- // HSK-M-Multi: Glands for applications with several cables
- // HSK-M-Flex: With bending protection
- // HSK-Mini: For threads smaller than M12
- // HSK-XL: Cable glands with threads from M63 to M90
- // HSK-MZ: Additional clamping for particularly high tension relief

In each case, HUMMEL offers different clamping areas, thread lengths, thread types and various sealing materials for different temperature ranges. The cable glands have all relevant approvals for international markets and a wide range of sectors.



HSK-M: Reliable, robust solutions for industry

Cable glands from the HSK-M premium series are available in brass and stainless steel. They are designed for industrial use and are characterised by a high degree of tightness, shock resistance and strain relief for the cables.


- // Protection class IP 66, IP 68 up to 10 bar / 30 min and IP 69K
- // RoHS and REACH/SVHC compliant
- // Free of conflict materials
- // Free of halogen and phosphorus
- // Fire protection class V0 according to UL94
- // Anti-twist protection for cables in the clamping insert


Overlapping clamping plates prevent the moulded seal from being torn out and thus increase the safety of the system

The internal sealing edge ensures optimum tightness between clamping insert and intermediate socket

The chambered moulded seal results in protection class IP 68 up to 10 bar / 30 min

The anti-twist protection prevents the clamp insert and cable from twisting during installation





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

LEAD
FREE


// Other sealing material e.g. Silicone on request

AG	Øk mm	H mm	SW1/SW2 mm	⌀ Nm	GL mm	Item-No short	GL mm	Item-No long
M12 x 1,5	2 – 5	19	14/14	4	6,5	1.609.1200.51	10	1.609.1200.31
M12 x 1,5	3 – 6,5	19	14/14	4	6,5	1.609.1200.50	10	1.609.1200.30
M16 x 1,5	2 – 6	21	17/19	6	6	1.609.1600.51	10	1.609.1600.31
M16 x 1,5	4 – 8	21	17/19	6	6	1.609.1600.50	10	1.609.1600.30
M16 x 1,5	5 – 10	22	20/20	5	6	1.609.1611.50	10	1.609.1611.30
M20 x 1,5	5 – 9	23	22/22	8	6	1.609.2000.51	10	1.609.2000.31
M20 x 1,5	6 – 12	23	22/22	8	6	1.609.2000.50	10	1.609.2000.30
M20 x 1,5	10 – 14	24	24/24	10	6	1.609.2016.50	10	1.609.2016.30
M25 x 1,5	9 – 16	26	30/30	12	7	1.609.2500.51	12	1.609.2500.31
M25 x 1,5	13 – 18	26	30/30	12	7	1.609.2500.50	12	1.609.2500.30
M32 x 1,5	13 – 20	31	40/40	15	8	1.609.3200.51	12	1.609.3200.31
M32 x 1,5	15 – 21	33	36/36	13	8	1.609.3200.52	12	1.609.3200.32
M32 x 1,5	18 – 25	31	40/40	15	8	1.609.3200.50	12	1.609.3200.30
M40 x 1,5	19 – 27	33	46/46	15	8	1.609.4000.52	15	1.609.4000.32
M40 x 1,5	20 – 26	37	50/50	15	8	1.609.4000.51	15	1.609.4000.31
M40 x 1,5	22 – 32	37	50/50	15	8	1.609.4000.50	15	1.609.4000.30
M50 x 1,5	25 – 31	37	57/57	24	9	1.609.5000.51	15	1.609.5000.31
M50 x 1,5	32 – 38	37	57/57	24	9	1.609.5000.50	15	1.609.5000.30
M63 x 1,5	29 – 35	38	64/68	30	10	1.609.6300.51	15	1.609.6300.31
M63 x 1,5	37 – 44	38	64/68	30	10	1.609.6300.50	15	1.609.6300.30



Metal cable glands

HSK-M (PG/-long)




Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

// Other sealing material e.g. Silicone on request

AG	Øk mm	H mm	SW1/SW2 mm	Nm	GL mm	Item-No short	GL mm	Item-No long
PG 7	2 – 5	19	14/14	4	5	1.609.0700.15		
PG 7	3 – 6,5	19	14/14	4	5	1.609.0700.01	10	1.609.0700.60
PG 9	2 – 6	21	17/17	6	6	1.609.0900.15		
PG 9	4 – 8	21	17/17	6	6	1.609.0900.01	10	1.609.0900.60
PG 11	3 – 7	22	20/20	5	6	1.609.1100.15		
PG 11	5 – 10	22	20/20	5	6	1.609.1100.01	10	1.609.1100.60
PG 13,5	5 – 9	24	22/22	8	6,5	1.609.1300.15		
PG 13,5	6 – 12	24	22/22	8	6,5	1.609.1300.01	10	1.609.1300.60
PG 16	7 – 12	23	24/24	10	6,5	1.609.1600.15		
PG 16	10 – 14	23	24/24	10	6,5	1.609.1600.01	10	1.609.1600.60
PG 21	9 – 16	24	30/30	12	7	1.609.2100.15		
PG 21	13 – 18	24	30/30	12	7	1.609.2100.01	12	1.609.2100.60
PG 29	13 – 20	29	40/40	15	8	1.609.2900.15		
PG 29	18 – 25	29	40/40	15	8	1.609.2900.01	12	1.609.2900.60
PG 36	22 – 32	35	50/50	15	8	1.609.3600.01	15	1.609.3600.60
PG 42	25 – 31	37	57/57	24	9	1.609.4200.15		
PG 42	32 – 38	37	57/57	24	9	1.609.4200.01	15	1.609.4200.60
PG 48	37 – 44	38	64/64	30	10	1.609.4800.01	15	1.609.4800.60





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS


// Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
NPT 3/8"	2 – 6	15	21	17/19	6	1.609.3800.71
NPT 3/8"	4 – 8	15	21	17/19	6	1.609.3800.70
NPT 1/2"	5 – 9	13	24	22/24	8	1.609.1200.71
NPT 1/2"	6 – 12	13	24	22/24	8	1.609.1200.70
NPT 3/4"	9 – 16	13	25	30/30	12	1.609.3400.71
NPT 3/4"	13 – 18	13	25	30/30	12	1.609.3400.70
NPT 1"	13 – 20	19	29	40/40	15	1.609.1000.71
NPT 1"	18 – 25	19	29	40/40	15	1.609.1000.70



Metal cable glands

HSK-M-PVDF (metric/-long)




Material	Nickel-plated brass
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-35°C to +150°C

RoHS

// Other sizes on request

AG	Ø mm	H mm	SW1/SW2 mm	Nm	GL mm	Item-No short	GL mm	Item-No long
M12 x 1,5	2 – 5	19	14/14	4	6,5	1.699.1200.51	10	1.699.1200.31
M12 x 1,5	3 – 6,5	19	14/14	4	6,5	1.699.1200.50	10	1.699.1200.30
M16 x 1,5	2 – 6	21	17/19	6	6	1.699.1600.51	10	1.699.1600.31
M16 x 1,5	4 – 8	21	17/19	6	6	1.699.1600.50	10	1.699.1600.30
M16 x 1,5	5 – 10	22	20/20	6	6	1.699.1611.50		
M20 x 1,5	5 – 9	23	22/22	8	6	1.699.2000.51	10	1.699.2000.31
M20 x 1,5	6 – 12	23	22/22	8	6	1.699.2000.50	10	1.699.2000.30
M20 x 1,5	10 – 14	24	24/24	10	6	1.699.2016.50	10	1.699.2016.30
M25 x 1,5	9 – 16	26	30/30	10	7	1.699.2500.51	12	1.699.2500.31
M25 x 1,5	13 – 18	26	30/30	10	7	1.699.2500.50	12	1.699.2500.30
M32 x 1,5	13 – 20	31	40/40	13	8	1.699.3200.51	12	1.699.3200.31
M32 x 1,5	18 – 25	31	40/40	13	8	1.699.3200.50	12	1.699.3200.30
M40 x 1,5	20 – 26	37	50/50	15	8	1.699.4000.51	15	1.699.4000.31
M40 x 1,5	22 – 32	37	50/50	15	8	1.699.4000.50	15	1.699.4000.30





Material	Nickel-plated brass
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-35°C to +150°C

RoHS


// Other sizes on request

AG	Øk mm	H mm	SW1/SW2 mm	 Nm	GL mm	Item-No
PG 7	2 – 5	19	14/14	4	5	1.699.0700.15
PG 7	3 – 6,5	19	14/14	4	5	1.699.0700.01
PG 9	2 – 6	21	17/17	6	6	1.699.0900.15
PG 9	4 – 8	21	17/17	6	6	1.699.0900.01
PG 11	3 – 7	22	20/20	6	6	1.699.1100.15
PG 11	5 – 10	22	20/20	6	6	1.699.1100.01
PG 16	10 – 13,5	23	24/24	10	10	1.699.1600.60
PG 21	13 – 18	24	30/30	10	12	1.699.2100.60
PG 29	13 – 20	29	40/40	13	12	1.699.2900.61
PG 29	18 – 25	29	40/40	13	12	1.699.2900.60
PG 36	22 – 32	35	50/50	15	15	1.699.3600.60
NPT 3/8"	2 – 6	21	17/19	6	15	1.699.3800.71
NPT 1/2"	5 – 9	24	22/24	8	13	1.699.1200.71
NPT 1/2"	6 – 12	24	22/24	8	13	1.699.1200.70
NPT 3/4"	9 – 16	25	30/30	10	13	1.699.3400.71



Metal cable glands

HSK-M-Multi (metric, PG, NPT)




Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	Elastomer
Material o-ring	NBR
Protection class	IP 68 – 10 bar and optimum assignment of all bores / IP 65
Temperature range	-40°C to +100°C

RoHS

- // AISI on request
- // Further seal inserts on request
- // Elongated threads on request
- // Type "Number of holes x d = -": without hole

AG	GL mm	H mm	SW1/SW2 mm	Nm	Number of holes x d	Item-No
M20 x 1,5	6	23	22/22	10	2 x 5	1.697.2003.50
M20 x 1,5	6	23	22/22	10	6 x 3	1.697.2001.50
M20 x 1,5	6	23	22/22	8	2 x 5	1.697.2024.50
M25 x 1,5	7	26	30/30	10	2 x 8	1.697.2502.50
M25 x 1,5	7	26	30/30	12	3 x 7	1.697.2501.50
M25 x 1,5	7	26	30/30	12	4 x 6	1.697.2500.50
M32 x 1,5	8	31	40/40	15	4 x 9	1.697.3201.50
M32 x 1,5	8	31	40/40	15	6 x 6,5	1.697.3200.50
M40 x 1,5	8	37	50/50	15	2 x 15	1.697.4003.50
M63 x 1,5	10	38	64/68	30	3 x 18	1.697.6302.50
PG 9	6	21	17/17	5	2 x 3	1.697.0901.01
PG 16	6,5	23	24/24	10	2 x 6	1.697.1605.01
NPT 3/8"	15	21	17/19	5	2 x 3	1.697.3801.70
NPT 1/2"	13	24	24/24	10	2 x 5	1.697.1203.70
NPT 1/2"	13	24	24/24	10	3 x 4	1.697.1202.70
NPT 3/4"	13	25	30/30	12	3 x 7	1.697.3401.70
NPT 3/4"	13	25	30/30	12	4 x 6	1.697.3400.70
NPT 1"	19	29	40/40	15	4 x 9	1.697.1001.70
NPT 1"	19	29	40/40	15	6 x 6,5	1.697.1000.70



Material	Nickel-plated brass
Steel spring	INOX 1.4310
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS


- // Other sizes on request
- // Elongated threads on request
- // Other sealing material e.g. Silicone on request

AG	Øk mm	d mm	H mm	SW1/SW2 mm	⌀ Nm	GL mm	Item-No
M12 x 1,5	2 – 5	6,8	55	14/14	4	6,5	1.623.1200.51
M12 x 1,5	3 – 6,5	6,8	55	14/14	4	6,5	1.623.1200.50
M16 x 1,5	4 – 8	8,2	66	19/19	6	6	1.623.1600.50
M16 x 1,5	5 – 10	10,3	77	20/20	5	6	1.623.1611.50
M20 x 1,5	5 – 9	12,3	88	22/22	8	6	1.623.2000.51
M20 x 1,5	6 – 12	12,3	88	22/22	8	6	1.623.2000.50
PG 7	2 – 5	6,8	55	14/14	4	5	1.623.0700.15
PG 7	3 – 6,5	6,8	55	14/14	4	5	1.623.0700.01
PG 9	4 – 8	8,2	66	17/17	6	6	1.623.0900.01
PG 11	3 – 7	10,3	77	20/20	5	6	1.623.1100.15
PG 11	5 – 10	10,3	77	20/20	5	6	1.623.1100.01
PG 13,5	6 – 12	12,3	88	22/22	8	6,5	1.623.1300.01
PG 16	7 – 12	14,3	98	24/24	10	6,5	1.623.1600.15
PG 16	10 – 14	14,3	98	24/24	10	6,5	1.623.1600.01
NPT 3/8"	2 – 6	8,2	66	17/19	6	15	1.623.3800.71
NPT 3/8"	4 – 8	8,2	66	17/19	6	15	1.623.3800.70
NPT 1/2"	5 – 9	12,3	88	22/24	8	13	1.623.1200.71
NPT 1/2"	6 – 12	12,3	88	22/24	8	13	1.623.1200.70
NPT 3/4"	9 – 16	18,4	111	33/33	12	13	1.623.3400.71
NPT 3/4"	13 – 18	18,4	111	33/33	12	13	1.623.3400.70



Metal cable glands

HSK-MZ (metric)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C


RoHS

// Elongated threads on request

// Other sealing material e.g. Silicone on request

AG	∅k mm	H mm	SW1/SW2 mm	Nm	Item-No
M12 x 1,5	3 – 6,5	26	14/14	4	1.690.1200.50
M16 x 1,5	4 – 8	28	19/19	6	1.690.1600.50
M16 x 1,5	5 – 10	30	20/20	5	1.690.1611.50
M20 x 1,5	6 – 12	33	22/22	8	1.690.2000.50
M20 x 1,5	10 – 14	33	24/24	10	1.690.2016.50
M25 x 1,5	13 – 18	37	30/30	12	1.690.2500.50
M32 x 1,5	18 – 25	43	40/40	15	1.690.3200.50
M40 x 1,5	22 – 32	50	50/50	15	1.690.4000.50
M50 x 1,5	25 – 31	51	57/57	24	1.690.5000.51
M50 x 1,5	32 – 38	51	57/57	24	1.690.5000.50
M63 x 1,5	29 – 35	52	64/68	30	1.690.6300.51
M63 x 1,5	37 – 44	52	64/68	30	1.690.6300.50





Material	Nickel-plated brass
Seal	TPE / FKM
Material o-ring	NBR / FKM
Protection class	IP 68 - 1bar/30min
Temperature range	-25°C to +200°C / -20°C to +100°C

RoHS


// Other thread pitches on request

// AISI on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⌚ Nm	Item-No -20°C to +100°C	Item-No -25°C to +200°C
M6 x 1	2 – 3,2	6	10	8/8	1	1.106.0601.50	1.106.0600.55
M8 x 0,75	2 – 4,5	3,5	14,3	11/11	2	1.112.0801.01	
M8 x 1,25	3 – 5	6	13	11/11	2	1.106.0801.50	1.106.0800.55
M8 x 1,25	3 – 5	10	13	11/11	2	1.106.0801.30	
M10 x 1,5	4 – 6	6	14	12/12	1	1.106.1001.50	1.106.1000.55

Metal cable glands

HSK-Mini-INOX (metric)




Material	INOX 1.4305
Seal	TPE / FKM
Material o-ring	NBR / FKM
Protection class	IP 68 - 1bar/30min
Temperature range	-25°C to +200°C / -20°C to +100°C

RoHS

- // Other thread pitches on request
- // Other sizes on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No -20°C to +100°C	Item-No -25°C to +200°C
M8 x 1,25	3 – 5	6	13	11/11	2	1.129.0800.50	1.129.0800.55
M10 x 1,5	4 – 6	6	14	12/12	1		1.129.1000.55





Material	Nickel-plated brass
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 - 1bar/30min
Temperature range	-20°C to +100°C


RoHS

// AISI on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M63 x 1,5	48 – 55	10	42	75/75	40	1.106.6375.50
M75 x 1,5	48 – 55	15	42	80/80	40	1.106.7500.50
M75 x 1,5	53 – 60	15	42	85/85	60	1.106.7500.51
M80 x 2	58 – 65	15	42	90/90	70	1.106.8000.50
M90 x 2	63 – 70	15	42	100/100	140	1.106.9000.50
M90 x 2	68 – 75	15	52	100/100	140	1.106.9000.51

Metal cable glands

HSK-INOX (metric)



Material	INOX 1.4305 / INOX 1.4404
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C


RoHS

// Other colors on request

// Other thread pitches on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No INOX 1.4305	Item-No INOX 1.4404
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.695.1200.51	
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.695.1200.50	1.675.1200.50
M16 x 1,5	3 – 7	6	22	22/22	5	1.695.1600.51	1.675.1600.51
M16 x 1,5	5 – 10	6	22	22/22	5	1.695.1600.50	1.675.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.695.2000.51	1.675.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.695.2000.50	1.675.2000.50
M25 x 1,5	9 – 16	7	24	30/30	12	1.695.2500.51	1.675.2500.51
M25 x 1,5	13 – 18	7	24	30/30	12	1.695.2500.50	1.675.2500.50
M32 x 1,5	13 – 20	8	31	41/41	15	1.695.3200.51	1.675.3200.51
M32 x 1,5	18 – 25	8	31	41/41	15	1.695.3200.50	1.675.3200.50
M40 x 1,5	20 – 26	8	37	50/50	15	1.695.4000.51	1.675.4000.51
M40 x 1,5	22 – 32	8	37	50/50	15	1.695.4000.50	1.675.4000.50
M50 x 1,5	25 – 31	9	37	60/60	24	1.695.5000.51	1.675.5000.51
M50 x 1,5	32 – 38	9	37	60/60	24	1.695.5000.50	1.675.5000.50
M63 x 1,5	29 – 35	10	38	64/68	30	1.695.6300.51	1.675.6300.51
M63 x 1,5	37 – 44	10	38	64/68	30	1.695.6300.50	1.675.6300.50





Material	INOX 1.4305 / INOX 1.4404
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C


// Other sizes on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No INOX 1.4305	Item-No INOX 1.4404
PG 7	2 – 5	5	19	14/14	4	1.695.0700.15	
PG 7	3 – 6,5	5	19	14/14	4	1.695.0700.01	
PG 9	4 – 8	6	21	17/17	6	1.695.0900.01	
PG 11	3 – 7	6	22	22/22	5	1.695.1100.15	
PG 11	5 – 10	6	22	22/22	5	1.695.1100.01	
PG 13,5	5 – 9	6,5	24	22/22	8	1.695.1300.15	
PG 13,5	6 – 12	6,5	24	22/22	8	1.695.1300.01	
PG 16	7 – 12	6,5	23	24/24	10	1.695.1600.15	
PG 16	10 – 14	6,5	23	24/24	10	1.695.1600.01	
PG 21	9 – 16	7	24	30/30	12	1.695.2100.15	
PG 21	13 – 18	7	24	30/30	12	1.695.2100.01	
NPT 3/8"	2 – 6	15	21	17/19	6		1.675.3800.71
NPT 3/8"	4 – 8	15	21	17/19	6		1.675.3800.70
NPT 1/2"	5 – 9	13	24	22/24	8		1.675.1200.71
NPT 1/2"	6 – 12	13	24	22/24	8		1.675.1200.70
NPT 3/4"	9 – 16	13	25	30/30	12		1.675.3400.71
NPT 3/4"	13 – 18	13	25	30/30	12		1.675.3400.70
NPT 1"	13 – 20	19	29	41/41	15		1.675.1000.71
NPT 1"	18 – 25	19	29	41/41	15		1.675.1000.70



Metal cable glands

HSK-INOX-PVDF (metric, PG)



Material	INOX 1.4404 / INOX 1.4305
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-35°C to +150°C


RoHS

// Other sizes on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	Nm	Item-No INOX 1.4305	Item-No INOX 1.4404
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.696.1200.51	1.676.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.696.1200.50	1.676.1200.50
M16 x 1,5	3 – 7	6	22	22/22	5	1.696.1600.51	1.676.1600.51
M16 x 1,5	5 – 10	6	22	22/22	5	1.696.1600.50	1.676.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.696.2000.51	1.676.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.696.2000.50	1.676.2000.50
M25 x 1,5	9 – 16	7	24	30/30	12	1.696.2500.51	1.676.2500.51
M25 x 1,5	13 – 18	7	24	30/30	12	1.696.2500.50	1.676.2500.50
M32 x 1,5	13 – 20	8	31	41/41	15	1.696.3200.51	1.676.3200.51
M32 x 1,5	18 – 25	8	31	41/41	15	1.696.3200.50	1.676.3200.50
PG 7	3 – 6,5	5	19	14/14	4	1.696.0700.01	1.676.0700.01
PG 9	4 – 8	6	21	17/17	6	1.696.0900.01	1.676.0900.01
PG 11	5 – 10	6	22	22/22	5	1.696.1100.01	1.676.1100.01



RoHS



Material	Nickel-plated brass
Seal	FKM
Material o-ring	FKM
Protection class	IP 68 - 1bar/30min
Temperature range	-25°C to +200°C

// Other sizes on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	4 – 6	5	18	14/14	4	1.106.1200.58
M16 x 1,5	7 – 9	5	19	18/18	6	1.106.1600.58
M20 x 1,5	10 – 13	6	21	22/22	8	1.106.2000.58
M25 x 1,5	15 – 18	7	23	28/28	12	1.106.2500.58

Even more information is available online: www.hummel.com

The HUMMEL AG website (www.hummel.com) is an enormous source for other product and company information. The complete HUMMEL assortment with all technical data, illustrations and downloads is presented in the cable glands product world. The technical centre contains lots of important background information. Special content pages address important topics such as EMC protection or applications in potentially explosive atmospheres. In addition, up-to-date information about product innovations, company news, trade fair participations and much more is also available there.

Cable glands product world

- // Complete assortment with all relevant technical data
- // Product illustrations and dimensioned line drawings
- // 3-D data to download
- // Filter functions as search help
- // Approvals and certificates

Technical centre

- // Product descriptions and assembly instruction
- // Downloading of approvals and certificates
- // Background information on EMC and Ex
- // Information about material, storage, thread types, etc.

EMC CABLE GLANDS

Protecting power units and electronic components from electromagnetic influences is becoming increasingly important. Cable management and connection solutions are of particularly high importance in this regard. Only a secure, long-lasting, 360° shield connection guarantees lasting protection for technical equipment.

- // HSK-M-EMC: The standard version with very good shield effectiveness
- // HSK-M-EMC-D: Simple, quick fitting with maximum EMC protection
- // PVDF-variants for applications in the particularly high temperature range
- // Flex variants with integrated bending protection
- // Glands with additional tension relief (HSK-M-EMC-MZ)
- // Stainless steel variants with outstanding shielding effectiveness

In each case, HUMMEL offers different clamping areas, thread lengths, thread types and various sealing materials for different temperature ranges. The cable glands have all relevant approvals for international markets and a wide range of sectors.



Full safety: 360 degree EMC connection

EMC cable glands protect electrical equipment from electromagnetic interference. As a premium manufacturer, HUMMEL relies here on innovative technology and high-quality materials. Therefore, users can rely on permanent protection, especially when it comes to a safe EMC connection.

HUMMEL cable glands with EMC protection are available in different versions:

HSK-M-EMC-D: This premium variant has a metallized clamping body, which ensures a continuous contact with the braided shield of the cable, even in dynamic applications.

Metrica-M-EMC-E: This cable gland also uses the clamping body principle. This ensures a significantly shorter installation time than with conventional EMC cable glands.


HSK-M-EMC: This cable gland also offers reliable protection against electromagnetic influences. It follows the classic mounting principle, in which the shield is separated and connected to the gland.

HSK-M-EMC-D

Overlapping clamping plates prevent the moulded seal from being torn out

The metallised clamp insert ensures optimum shielding values

Sturdy contact plates make reliable contact, even in dynamic applications




HSK-M-EMC

Overlapping clamping plates prevent the moulded seal from being torn out

The internal sealing edge ensures optimum tightness between clamping insert and intermediate socket

Secure 360° contact. Internal O-ring presses the braid against the intermediate socket





Material	Nickel-plated brass
Clamping insert	Metallized polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other sealing material e.g. Silicone on request

AG	Ø mm	H mm	SW1/SW2 mm	 Nm	GL mm	Item-No short	GL mm	Item-No long
M12 x 1,5	3 – 6,5	25	14/14	6	6,5	1.631.1200.50	10	1.631.1200.30
M16 x 1,5	4 – 8	29	17/19	9	6	1.631.1609.50	10	1.631.1609.30
M16 x 1,5	5 – 10	32	20/20	11	6	1.631.1600.50	10	1.631.1600.30
M20 x 1,5	6 – 12	32,5	22/22	12	6	1.631.2013.50	10	1.631.2013.30
M20 x 1,5	10 – 14	33	24/24	13	6	1.631.2000.50	10	1.631.2000.30
M25 x 1,5	13 – 18	39	30/30	13	7	1.631.2500.50	12	1.631.2500.30
M32 x 1,5	18 – 25	45	40/40	17,5	8	1.631.3200.50	12	1.631.3200.30
M40 x 1,5	24 – 32	51	50/50	25	8	1.631.4000.50	15	1.631.4000.30
M50 x 1,5	32 – 38	57,5	57/57	29	9	1.631.5000.50	15	1.631.5000.30
M63 x 1,5	37 – 44	52	64/68	38	10	1.631.6300.50	15	1.631.6300.30




to the product video

to the assembly
instruction

EMC cable glands

HSK-M-EMC-D (PG, NPT)



Material	Nickel-plated brass
Clamping insert	Metallized polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other sealing material e.g. Silicone on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
PG 7	3 – 6,5	5	24	14/14	6	1.631.0700.01
PG 9	4 – 8	6	28	17/17	9	1.631.0900.01
PG 11	5 – 10	6	29	20/20	11	1.631.1100.01
PG 13,5	6 – 12	6,5	31	22/22	12	1.631.1300.01
PG 16	10 – 14	6,5	32	24/24	13	1.631.1600.01
PG 21	13 – 18	7	38	30/30	13	1.631.2100.01
PG 29	18 – 25	8	43	40/40	17,5	1.631.2900.01
PG 36	24 – 32	8	48	50/50	25	1.631.3600.01
NPT 3/8"	4 – 8	15	29	17/19	9	1.631.3800.70
NPT 1/2"	6 – 12	13	32,5	22/24	12	1.631.1200.70
NPT 3/4"	13 – 18	13	39	30/30	13	1.631.3400.70




to the product video



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 68 - 5bar/30min
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other sizes on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M16 x 1,5	4,5 – 10	6	24,4	19/19	6,5	1.607.1600.50
M20 x 1,5	6 – 12	6	25,4	22/22	6	1.607.2013.50
M20 x 1,5	7,5 – 14	6	28,3	24/24	8	1.607.2000.50
M25 x 1,5	9 – 17	7	29,3	29/29	9,5	1.607.2500.50
M32 x 1,5	11 – 21	8	37,7	34/34	13,5	1.607.3200.50



to the product video




to the assembly
instruction



EMC cable glands

HSK-M-EMC (metric/-long)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other sealing material e.g. Silicone on request

AG	Øk mm	H mm	SW1/SW2 mm	⌚ Nm	GL mm	Item-No short	GL mm	Item-No long
M12 x 1,5	2 – 5	19	14/14	4	6,5	1.691.1200.51	10	1.691.1200.31
M12 x 1,5	3 – 6,5	19	14/14	4	6,5	1.691.1200.50	10	1.691.1200.30
M16 x 1,5	3 – 7	22	20/20	5	6	1.691.1600.51	10	1.691.1600.31
M16 x 1,5	5 – 10	22	20/20	5	6	1.691.1600.50	10	1.691.1600.30
M20 x 1,5	7 – 12	24	24/24	10	6	1.691.2000.51	10	1.691.2000.31
M20 x 1,5	10 – 14	24	24/24	10	6	1.691.2000.50	10	1.691.2000.30
M25 x 1,5	9 – 16	26	30/30	12	7	1.691.2500.51	12	1.691.2500.31
M25 x 1,5	13 – 18	26	30/30	12	7	1.691.2500.50	12	1.691.2500.30
M32 x 1,5	13 – 20	31	40/40	15	8	1.691.3200.51	12	1.691.3200.31
M32 x 1,5	15 – 21	33	36/36	15	8	1.691.3200.52	12	1.691.3200.32
M32 x 1,5	18 – 25	31	40/40	15	8	1.691.3200.50	12	1.691.3200.30
M40 x 1,5	19 – 27	33	46/46	15	8	1.691.4000.52	15	1.691.4000.32
M40 x 1,5	22 – 32	37	50/50	15	8	1.691.4000.50	15	1.691.4000.30
M50 x 1,5	25 – 31	37	57/57	24	9	1.691.5000.51	15	1.691.5000.31
M50 x 1,5	32 – 38	37	57/57	24	9	1.691.5000.50	15	1.691.5000.30
M63 x 1,5	29 – 35	38	64/68	30	10	1.691.6300.51		
M63 x 1,5	37 – 44	38	64/68	30	10	1.691.6300.50	15	1.691.6300.30




to the product video



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other sealing material e.g. Silicone on request

AG	Øk mm	H mm	SW1/SW2 mm	⌀ Nm	GL mm	Item-No short	GL mm	Item-No long
PG 7	3 – 6,5	19	14/14	4	5	1.691.0700.01	10	1.691.0700.60
PG 9	2 – 6	21	17/17	6	6	1.691.0900.15		
PG 9	4 – 8	21	17/17	6	6	1.691.0900.01	10	1.691.0900.60
PG 11	3 – 7	22	20/20	5	6	1.691.1100.15		
PG 11	5 – 10	22	20/20	5	6	1.691.1100.01	10	1.691.1100.60
PG 13,5	5 – 9	24	22/22	8	6,5	1.691.1300.15		
PG 13,5	6 – 12	24	22/22	8	6,5	1.691.1300.01	10	1.691.1300.60
PG 16	7 – 12	23	24/24	10	6,5	1.691.1600.15		
PG 16	10 – 14	23	24/24	10	6,5	1.691.1600.01	10	1.691.1600.60
PG 21	9 – 16	24	30/30	12	7	1.691.2100.15	12	1.691.2100.61
PG 21	13 – 18	24	30/30	12	7	1.691.2100.01	12	1.691.2100.60
PG 29	13 – 20	29	40/40	15	8	1.691.2900.15		
PG 29	18 – 25	29	40/40	15	8	1.691.2900.01	12	1.691.2900.60
PG 36	20 – 26	35	50/50	15	8	1.691.3600.15		
PG 36	22 – 32	35	50/50	15	8	1.691.3600.01		
PG 42	25 – 31	37	57/57	24	9	1.691.4200.15		
PG 42	32 – 38	37	57/57	24	9	1.691.4200.01		
PG 48	29 – 35	38	64/64	30	10	1.691.4800.15		
PG 48	37 – 44	38	64/64	30	10	1.691.4800.01		




to the product video

to the assembly
instruction

EMC cable glands

HSK-M-EMC (NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other sealing material e.g. Silicone on request
// Other sizes on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
NPT 3/8"	2 – 6	15	21	17/19	6	1.691.3800.71
NPT 3/8"	4 – 8	15	21	17/19	6	1.691.3800.70
NPT 1/2"	5 – 9	13	24	22/24	8	1.691.1200.71
NPT 1/2"	6 – 12	13	24	22/24	8	1.691.1200.70
NPT 3/4"	9 – 16	13	25	30/30	12	1.691.3400.71
NPT 3/4"	13 – 18	13	25	30/30	12	1.691.3400.70




to the product video



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP 68 – 10 bar / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-35°C to +150°C

RoHS

EMV
EMC

// Other sealing material e.g. Silicone on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.698.1200.50
M16 x 1,5	3 – 7	6	22	20/20	5	1.698.1611.51
M16 x 1,5	4 – 8	6	23	17/19	10	1.698.1600.50
M16 x 1,5	5 – 10	6	22	20/20	5	1.698.1611.50
M20 x 1,5	7 – 12	6	24	24/24	10	1.698.2000.51
M20 x 1,5	10 – 14	6	24	24/24	10	1.698.2000.50




to the product video

to the assembly
instruction

EMC cable glands

HSK-M-Flex-EMC (metric/-long)



Material	Nickel-plated brass
Steel spring	INOX 1.4310
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC


- // Also available in PVDF (-35°C to +150°C)
- // Other sealing material e.g. Silicone on request
- // Elongated threads on request

AG	∅ mm	d mm	H mm	SW1/SW2 mm	 Nm	GL mm	Item-No short	GL mm	Item-No long
M12 x 1,5	3 – 6,5	6,8	55	14/14	4	6,5	1.624.1200.50	10	1.624.1200.30
M16 x 1,5	5 – 10	10,3	77	20/20	5	6	1.624.1600.50	10	1.624.1600.30
M20 x 1,5	7 – 12	14,3	98	24/24	10	6	1.624.2000.51		
M20 x 1,5	10 – 14	14,3	98	24/24	10	6	1.624.2000.50	10	1.624.2000.30
M25 x 1,5	13 – 18	18,4	111	30/30	12	7	1.624.2500.50	12	1.624.2500.30



to the product video





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// *Also available in PVDF on request (-35°C to +150°C)

// Other sealing material e.g. Silicone on request

AG	∅k mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	3 – 6,5	26	14/14	4	1.692.1200.50
M16 x 1,5	5 – 10	29	20/20	5	1.692.1600.50
M20 x 1,5	10 – 14	32	24/24	10	1.692.2000.50
M25 x 1,5	13 – 18	35	30/30	12	1.692.2500.50
M32 x 1,5	18 – 25	41	40/40	15	1.692.3200.50
M40 x 1,5	22 – 32	48	50/50	15	1.692.4000.50
M50 x 1,5	32 – 38	51	57/57	24	1.692.5000.50
M63 x 1,5	37 – 44	52	64/68	30	1.692.6300.50




to the product video



EMC cable glands

HSK-Mini EMC (metric)



Material	Nickel-plated brass
Seal	TPE
Material o-ring	NBR
Protection class	IP 68 - 1bar/30min
Temperature range	-20°C to +100°C

RoHS


// Other thread pitches on request
// AISI on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M8 x 1,25	3 – 5	6	13	11/11	2	1.119.0800.50
M10 x 1,5	4 – 6	6	14	12/12	1	1.119.1000.50



to the product video





Material	INOX 1.4305
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

// Other types of stainless steels available on request

// Other sizes on request

// Other thread pitches on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.693.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.693.1200.50
M16 x 1,5	3 – 7	6	21	22/22	5	1.693.1600.51
M16 x 1,5	5 – 10	6	21	22/22	5	1.693.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.693.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.693.2000.50
M25 x 1,5	9 – 16	7	26	30/30	12	1.693.2500.51
M25 x 1,5	13 – 18	7	26	30/30	12	1.693.2500.50
M32 x 1,5	13 – 20	8	31	41/41	15	1.693.3200.51
M32 x 1,5	18 – 25	8	31	41/41	15	1.693.3200.50



to the product video



VariaPro: From M12 to M63

The cable glands of the VariaPro series are available in sizes from M12 to M63. These cable glands therefore cover a clamping range from 2 to 54 millimetre cable diameter for discerning markets. The reducer insert in the moulded seal is responsible for this. Users therefore gain maximum flexibility, simplified procurement processes and lean warehousing.


VariaPro is available with three characteristics. The VariaPro Temp version is designed for extreme temperatures. It covers a temperature range from -60 to +200° Celsius. On the other hand, the rail version meets the strictest fire protection standards and can therefore be used in all trains of the European rail network.

All versions have an integrated EMC link in the standard and fulfil protection class IP 68 up to 10 bar / 30min.

VariaPro
Rail




VariaPro
Temp



CABLE GLANDS FOR SPECIAL APPLICATIONS

With the VariaPro series, HUMMEL focusses on very special applications and the particular requirements of selected sectors. The VariaPro cable glands have been designed for very special sector requirements in each case. Their specific strengths with regard to temperature, fire protection or hygiene are certified which means they can be used without restriction in these extreme applications.

- // VariaPro Rail: The cable gland with railway approval EN 45545-3
- // VariaPro Temp: Suitable for particularly low and extremely high temperatures
- // HSK-INOX-HD-PRO: Developed for areas with a high level of hygienic requirements



VariaPro: Outstanding technical properties

Demanding markets with special challenges — these are ideal conditions for VariaPro. These cable glands impress with numerous technical features. The large clamping ranges of all variants are outstanding. For users this means high flexibility, easy procurement and lean warehousing. Simple assembly is also user-friendly. Two different wrench sizes on one gland facilitate tightening. The optimised ergonomics also ensure a better grip of the tool.

Technical features

- // Available sizes M12 to M63
- // Integrated EMC connection
- // Protection class IP 68 up to 10 bar / 30 min
- // Robust design and slimline construction
- // Large clamping range through a reduction insert


VariaPro


Compact union nut for easy installation even in confined spaces

Removable reduction sealing insert

Integrated EMC connection on the sealing insert

Anti-twist protection for the sealing insert and cable at the intermediate socket





Material	Nickel-plated brass
Seal	EPDM
Material o-ring	EPDM
Protection class	IP68 - 10bar/30min
Integrity	E20 / E30
Temperature range	-40°C to +100°C

RoHS

EMV
EMC

- // DIN EN 45545-2 and DIN EN 45545-3
- // Large clamping range through reduction insert
- // Integrated anti-twist protection during cable installation

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
M12 x 1,5	2 – 8	6,5	20	16/17	3	1.750.1200.50
M12 x 1,5	5 – 8	6,5	20	16/17	5	1.750.1200.51
M16 x 1,5	4 – 11	7	24,5	19/20	5	1.750.1600.50
M16 x 1,5	7 – 11	7	24,5	19/20	8	1.750.1600.51
M20 x 1,5	7 – 14	6	27	22/24	6	1.750.2000.50
M20 x 1,5	10 – 14	6	27	22/24	6	1.750.2000.51
M25 x 1,5	11 – 18	7	29	27/30	10	1.750.2500.50
M25 x 1,5	14,5 – 18	7	29	27/30	10	1.750.2500.51
M32 x 1,5	16 – 25	8	34	36/40	12	1.750.3200.50
M32 x 1,5	20,5 – 25	8	34	36/40	12	1.750.3200.51
M40 x 1,5	21 – 32	8	40	46/50	15	1.750.4000.50
M40 x 1,5	26,5 – 32	8	40	46/50	15	1.750.4000.51
M50 x 1,5	31 – 42	9	48	57/57	20	1.750.5000.50
M50 x 1,5	35 – 42	9	48	57/57	20	1.750.5000.51
M63 x 1,5	41 – 54	10	47,5	65/68	32	1.750.6300.50
M63 x 1,5	46,5 – 54	10	47,5	65/68	37	1.750.6300.51




to the product video



Cable glands for special applications

VariaPro Temp (metric)



Material	Nickel-plated brass
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Protection class	IP68 - 10bar/30min
Temperature range	-60°C to +200°C


RoHS

EMV
EMC

- // Suitable for absolute low and high temperature applications
- // Integrated possibility for EMC connection
- // Large clamping range through reduction insert
- // Integrated anti-twist protection during cable installation

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 8	6,5	20	16/17	3	1.751.1200.50
M12 x 1,5	5 – 8	6,5	20	16/17	5	1.751.1200.51
M16 x 1,5	4 – 11	7	24,5	19/20	5	1.751.1600.50
M16 x 1,5	7 – 11	7	22,8	19/20	8	1.751.1600.51
M20 x 1,5	7 – 14	6	27	22/24	6	1.751.2000.50
M20 x 1,5	10 – 14	6	27	22/24	6	1.751.2000.51
M25 x 1,5	11 – 18	7	29	27/30	18	1.751.2500.50
M25 x 1,5	14,5 – 18	7	29	27/30	10	1.751.2500.51
M32 x 1,5	16 – 25	8	34	36/40	24	1.751.3200.50
M32 x 1,5	20,5 – 25	8	34	36/40	20	1.751.3200.51
M40 x 1,5	21 – 32	8	40	46/50	20	1.751.4000.50
M40 x 1,5	26,5 – 32	8	40	46/50	20	1.751.4000.51
M50 x 1,5	31 – 42	9	48	57/57	20	1.751.5000.50
M50 x 1,5	35 – 42	9	48	57/57	20	1.751.5000.51
M63 x 1,5	41 – 54	10	47,5	65/68	32	1.751.6300.50
M63 x 1,5	46,5 – 54	10	47,5	65/68	37	1.751.6300.51





Material	INOX 1.4404
Seal	VMQ (silicone)
Protection class	IP 66 / IP 69 K / IP68 - 10bar/30min
Temperature range	-40°C to +120°C

**EMV
EMC**

- // EMC connection integrated
- // VDMA Riboflavin cleaning test passed
- // EHEDG O1 cleaning test passed

AG	Ø* mm	D mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
M12 x 1,5	5 – 6,5	21	6	19	14/14	8	1.740.1203.50
M16 x 1,5	6 – 7,5	27	6	20	19/21	15	1.740.1603.51
M16 x 1,5	7,5 – 10	27	6	20	19/21	15	1.740.1603.50
M20 x 1,5	9 – 12	33	6	22,5	24/27	30	1.740.2003.51
M20 x 1,5	11 – 13,5	33	6	22,5	24/27	30	1.740.2003.50
M25 x 1,5	14 – 16	38	7	23,5	30/30	35	1.740.2503.52
M25 x 1,5	15 – 18	38	7	23,5	30/30	35	1.740.2503.50
M32 x 1,5	18 – 21	45	8	26,5	36/36	40	1.740.3203.51
M32 x 1,5	21 – 25	45	8	26,5	36/36	40	1.740.3203.50



to the assembly
instruction




HUMMEL AG on social media

Apart from the HUMMEL website (www.hummel.com), information, news, videos and posts are available on different social media channels. The target group-specific topics to choose from range from training at HUMMEL, product innovations, information about events and reviews or even simply the light and amusing side of everyday working at HUMMEL AG.

YouTube

Youtube: On the HUMMEL Youtube channel there are many video clips of


- // Product presentations
- // Installation/Assembly videos
- // 3-D animations
- // Training videos



<https://www.youtube.com/user/HummelAGET>



Facebook: Here the topics primarily cover training at HUMMEL and everyday work in the company.



<https://www.facebook.com/Hummel.AG>

LinkedIn

LinkedIn: Following is worthwhile! All product innovations and news are published on LinkedIn promptly.



<https://www.linkedin.com/company/10651915>



DIN CABLE GLANDS

These cable glands have been designed to meet the requirements of very special norms and standards. This means they have a different construction and function compared to the premium cable glands in the HSK series. DIN cable glands offer very special clamping areas and feature a very low construction height.


- // DIN 46320: Brass cable glands
- // Z (DIN 46320): Cable glands with extra high tension relief

In each case, HUMMEL offers different clamping areas and thread types.



DIN cable glands

DIN 46320 (PG)




Material	Nickel-plated brass
Seal	NBR
Protection class	IP 54 / IP 65 in case of additional flat seal at connection thread
Temperature range	-20°C to +80°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Item-No
PG 7	6 – 8	5	15	13/14	1.101.0703.01
PG 9	4 – 10	6	15	15/17	1.101.0901.01
PG 11	6,5 – 12	6	17	18/20	1.101.1101.01
PG 13,5	6,5 – 13,5	6,5	20	20/22	1.101.1301.01
PG 16	6,5 – 16	6,5	22	22/24	1.101.1601.01





Material	Nickel-plated brass
Seal	NBR
Protection class	IP 54 / IP 65 in case of additional flat seal at connection thread
Temperature range	-20°C to +80°C


RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Version	Item-No
M20 x 1,5	7,5 – 12	6	26	22/22	with cut-out sealing ring	1.105.2000.52
M20 x 1,5	8,5 – 13,5	6	27,5	24/22	with cut-out sealing ring	1.105.2013.52
M20 x 1,5	10,5 – 15	6	28,5	26/24	with cut-out sealing ring	1.105.2016.52
M25 x 1,5	13 – 20	6	33	33/30	with cut-out sealing ring	1.105.2500.52
M32 x 1,5	19 – 28	6	36	42/39	with cut-out sealing ring	1.105.3200.52
M40 x 1,5	24 – 34	7	41	52/50	with cut-out sealing ring	1.105.4000.52
M50 x 1,5	34 – 40	8	45	59/57	with cut-out sealing ring	1.105.5000.52
M63 x 1,5	39 – 46	9	48	64/66	with cut-out sealing ring	1.105.6300.52
PG 13,5	8,5 – 13,5	6,5	27,5	24/22	with cut-out sealing ring	1.105.1301.01
PG 16	10,5 – 16	6,5	28,5	26/24	with cut-out sealing ring	1.105.1601.01
PG 21	13 – 20	7	33	33/30	with cut-out sealing ring	1.105.2101.01
PG 29	19 – 28	8	36	42/40	with cut-out sealing ring	1.105.2901.01

PRODUCTION DEPTH

Competence, know-how and decades of experience are guarantors of success. HUMMEL has now been involved in metal working and machining for more than 70 years. The machinery includes the latest generation of lathes, milling and zinc die casting machines. In the electroplating department the products are given professional surface treatment.

The in-house mould-making department supplies the moulds for the in-house injection casting and die casting facility. HUMMEL products are produced in-house in automatic and semi-automatic assembly.



IN-HOUSE DEVELOPMENT AND CAD DEPARTMENT



SURFACE TREATMENT, FINISHING



PROTOTYPE CONSTRUCTION



MODERN MACHINERY



EXPERIENCED PROJECT AND
PROCESS MANAGEMENT



ASSEMBLY



QUALITY MANAGEMENT WITH CERTIFICATIONS



IN-HOUSE TEST LABORATORY



METALWORKING



IN-HOUSE CABLE ASSEMBLY



PLASTICS PROCESSING



WAREHOUSE AND LOGISTICS MANAGEMENT




ACCESSORIES


That finishing touch for many applications: accessories. Seemingly insignificant, but actually extremely important. For the desired functionality is often only achieved with the right accessories. That's why HUMMEL offers a huge range of accessory components which are aligned perfectly with the cable glands and have been tried and tested over many years.

- // Accessories in plastic, brass and stainless steel
- // Plugs and locknuts
- // O-rings and connecting thread sealing rings
- // Various Multi inserts
- // Reduction and expansion parts

The accessories come in a range of materials, sizes and thread types. HUMMEL accessories also have all relevant approvals for international markets.



Locknut GM-FS (metric, PG, NPT)




Material	Polyamide, fiber reinforced / Polyamide V0 according to UL94
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS

IG	H mm	SW mm	Item-No black	Item-No grey
M12 x 1,5	5	17	1.262.1201.50	1.262.1200.50
M16 x 1,5	5	22	1.262.1601.50	1.262.1600.50
M20 x 1,5	6	27	1.262.2001.50	1.262.2000.50
M25 x 1,5	6,5	32	1.262.2501.50	1.262.2500.50
M32 x 1,5	7	41	1.262.3201.50	1.262.3200.50
M40 x 1,5	7	50	1.262.4001.50	1.262.4000.50
M50 x 1,5	8	60	1.262.5001.50	1.262.5000.50
M63 x 1,5	8	75	1.262.6301.50	1.262.6300.50
PG 7	5,8	19	1.262.0701.11	1.262.0700.11
PG 9	6,8	22	1.262.0901.11	1.262.0900.11
PG 11	6,8	24	1.262.1101.11	1.262.1100.11
PG 13,5	6	27	1.262.1301.11	1.262.1300.11
PG 16	6	30	1.262.1601.11	1.262.1600.11
PG 21	7	36	1.262.2101.11	1.262.2100.11
PG 29	7	46	1.262.2901.11	1.262.2900.11
PG 36	8	60	1.262.3601.11	1.262.3600.11
PG 42	8	65	1.262.4201.11	1.262.4200.11
PG 48	8	70	1.262.4801.11	1.262.4800.11
NPT 3/8"	6,8	24	1.262.3801.70	1.262.3800.70
NPT 1/2"	6,8	27	1.262.1201.70	1.262.1200.70
NPT 3/4"	6,75	32	1.262.3401.70	1.262.3400.70
NPT 1"	7,8	40	1.262.1001.70	1.262.1000.70

Locknut for breather drain **GM-KS** (metric)



Material	Polyamide
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035


IG	H mm	SW mm	Item-No black	Item-No grey
M25 x 1,5	9	30	1.263.2501.50	1.263.2500.50

Locknut GM-Ms (metric, PG)

Material

Nickel-plated brass

RoHS




IG	H mm	SW mm	Item-No
M12 x 1,5	2,8	15	1.161.1200.50
M16 x 1,5	2,8	19	1.161.1600.50
M20 x 1,5	3	23	1.161.2000.50
M25 x 1,5	3,5	29	1.161.2500.50
M32 x 1,5	4	36	1.161.3200.50
M40 x 1,5	4,5	41	1.161.4000.50
M50 x 1,5	5,5	55	1.161.5000.50
M63 x 1,5	6	70	1.161.6300.50
M75 x 1,5	8	85	1.161.7500.50
M80 x 2	8	90	1.161.8000.50
M90 x 2	8	100	1.161.9000.50
PG 7	2,8	15	1.161.0700.01
PG 9	2,8	18	1.161.0900.01
PG 11	3	21	1.161.1100.01
PG 13,5	3	23	1.161.1300.01
PG 16	3	26	1.161.1600.01
PG 21	3,5	32	1.161.2100.01
PG 29	4	41	1.161.2900.01
PG 36	5	51	1.161.3600.01
PG 42	5	60	1.161.4200.01
PG 48	5,5	64	1.161.4800.01

Material

Nickel-plated brass

RoHS




IG	H mm	s mm	SW mm	Item-No
M12 x 1,5	2,8	0,7	15	1.167.1200.50
M16 x 1,5	2,8	0,7	19	1.167.1600.50
M20 x 1,5	3	0,7	24	1.167.2000.50
M25 x 1,5	3,5	0,7	30	1.167.2500.50
M32 x 1,5	4,5	0,7	36	1.167.3200.50
M40 x 1,5	5	0,7	46	1.167.4000.50
M50 x 1,5	5	0,7	60	1.167.5000.50
M63 x 1,5	6	0,7	70	1.167.6300.50
PG 7	2,8	0,7	15	1.167.0700.01
PG 9	2,8	0,7	18	1.167.0900.01
PG 11	3	0,7	21	1.167.1100.01
PG 13,5	3	0,7	23	1.167.1300.01
PG 16	3	0,7	26	1.167.1600.01
PG 21	3,5	0,7	32	1.167.2100.01
PG 29	4	0,7	41	1.167.2900.01
PG 36	5	0,7	51	1.167.3600.01
PG 42	5	0,7	60	1.167.4200.01
PG 48	5,5	0,7	64	1.167.4800.01

Locknut GM-INOX (metric, PG)

MaterialINOX 1.4305RoHS



IG	H mm	SW mm	Item-No
M12 x 1,5	2,8	15	1.161.1200.58
M16 x 1,5	2,8	19	1.161.1600.58
M20 x 1,5	2,8	24	1.161.2000.58
M25 x 1,5	3,5	30	1.161.2500.58
M32 x 1,5	3,5	36	1.161.3200.58
M40 x 1,5	5	46	1.161.4000.58
M50 x 1,5	5	55	1.161.5000.58
M63 x 1,5	6	70	1.161.6300.58
PG 7	2,8	17	1.161.0700.08
PG 9	2,8	22	1.161.0900.08
PG 11	3	22	1.161.1100.08
PG 13,5	3	24	1.161.1300.08
PG 16	3	27	1.161.1600.08
PG 21	3,5	32	1.161.2100.08
PG 29	4	41	1.161.2900.08
PG 36	5	50	1.161.3600.08




Material	Polyamide
Protection class	IP 54
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

RoHS

AG	D mm	GL mm	H mm	Item-No black	Item-No grey
M12 x 1,5	15	6	10	1.251.1201.50	1.251.1200.50
M16 x 1,5	20	7	11	1.251.1601.50	1.251.1600.50
M20 x 1,5	25	6	9,5	1.251.2001.50	1.251.2000.50
M25 x 1,5	30	11	15,5	1.251.2501.50	1.251.2500.50
M32 x 1,5	38	11	16	1.251.3201.50	1.251.3200.50
M40 x 1,5	46	13	18	1.251.4001.50	1.251.4000.50
M50 x 1,5	56	13	18,5	1.251.5001.50	1.251.5000.50
M63 x 1,5	69	15	19	1.251.6301.50	1.251.6300.50
PG 7	15	6	8	1.251.0701.11	1.251.0700.11
PG 9	19	6	9	1.251.0901.11	1.251.0900.11
PG 11	22	6	9	1.251.1101.11	1.251.1100.11
PG 13,5	25	6	9,5	1.251.1301.11	1.251.1300.11
PG 16	27	6	9,5	1.251.1601.11	1.251.1600.11
PG 21	33	8	11	1.251.2101.11	1.251.2100.11
PG 29	44	8	12	1.251.2901.11	1.251.2900.11
PG 36	55	10	15	1.251.3601.11	1.251.3600.11
PG 42	62	10	16	1.251.4201.11	1.251.4200.11
PG 48	69	12	16	1.251.4801.11	1.251.4800.11

Plug V-NE (metric, PG)




Material	Polyamide, fiber reinforced
Protection class	IP 54
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS

AG	D mm	GL mm	H mm	SW mm	⊙	Item-No
M12 x 1,5	16,5	8,5	13	15	6	1.255.1201.50
M16 x 1,5	20,5	8,5	13	19	8	1.255.1601.50
M20 x 1,5	25,5	9	14,5	24	8	1.255.2001.50
M25 x 1,5	30,5	10,5	16	28	8	1.255.2501.50
M32 x 1,5	38	11,5	17,5	36	8	1.255.3201.50
M40 x 1,5	48	11,5	18	46	8	1.255.4001.50
M50 x 1,5	60	13,5	20	55	8	1.255.5001.50
M63 x 1,5	75	14,5	21	70	8	1.255.6301.50
PG 7	16,5	8,5	13	15	6	1.255.0701.11
PG 9	20,5	8,5	13	19	8	1.255.0901.11
PG 11	25,5	9	14,5	24	8	1.255.1101.11
PG 13,5	25,5	9	14,5	24	8	1.255.1301.11
PG 16	30,5	10,5	16	28	8	1.255.1601.11
PG 21	38	11,5	17,5	36	8	1.255.2101.11
PG 29	48	11,5	18	46	8	1.255.2901.11
PG 36	60	13,5	20	55	8	1.255.3601.11
PG 42	65	13,5	20	60	8	1.255.4201.11
PG 48	75	14,5	21	70	8	1.255.4801.11

Plug V-NE-SD (metric, PG)




Material	Polyamide, fiber reinforced
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS

AG	D mm	GL mm	H mm	SW mm	⊙	Item-No
M12 x 1,5	16,5	8,5	13	15	6	1.256.1201.50
M16 x 1,5	20,5	8,5	13	19	8	1.256.1601.50
M20 x 1,5	25,5	9	14,5	24	8	1.256.2001.50
M25 x 1,5	30,5	10,5	16	28	8	1.256.2501.50
M32 x 1,5	38	11,5	17,5	36	8	1.256.3201.50
M40 x 1,5	48	11,5	18	46	8	1.256.4001.50
M50 x 1,5	60	13,5	20	55	8	1.256.5001.50
M63 x 1,5	75	14,5	21	70	8	1.256.6301.50
PG 7	16,5	8,5	13	15	6	1.256.0701.11
PG 9	20,5	8,5	13	19	8	1.256.0901.11
PG 11	25,5	9	14,5	24	8	1.256.1101.11
PG 13,5	25,5	9	14,5	24	8	1.256.1301.11
PG 16	30,5	10,5	16	28	8	1.256.1601.11
PG 21	38	11,5	17,5	36	8	1.256.2101.11
PG 29	48	11,5	18	46	8	1.256.2901.11
PG 36	60	13,5	20	55	8	1.256.3601.11
PG 42	65	13,5	20	60	8	1.256.4201.11
PG 48	75	14,5	21	70	8	1.256.4801.11

Plug HSK-V



Material	Polyamide
Temperature range	-40°C to +100°C
Colour	black
RAL	9005


RoHS

// Dome plugs for cable glands

Suitable for AG	Suitable for AG2	Suitable for AG3	d mm	D mm	L mm	Item-No
PG 7	M12 x 1,5		4,5	6	15	1.280.0007.00
PG 9	M16 x 1,5	NPT 3/8"	5,5	7,5	17	1.280.0009.00
PG 11	M16 x 1,5 / 11		6,5	9,5	19	1.280.0011.00
PG 13,5	M20 x 1,5	NPT 1/2"	8,5	11,5	19	1.280.0013.00
PG 16	M20 x 1,5 / 16	NPT 1/2" / 16	11,5	13,5	19,5	1.280.0016.00
PG 21	M25 x 1,5	NPT 3/4"	15,5	17,5	23,5	1.280.0021.00
PG 29	M32 x 1,5	NPT 1" / NPT 1 1/4"	19	24	26	1.280.0029.00
PG 36	M40 x 1,5	NPT 1 1/2"	25	31	28	1.280.0036.00
PG 42	M50 x 1,5		30	37	28	1.280.0042.00
PG 48	M63 x 1,5		34	43	28	1.280.0048.00

Plug V-N-Ms (metric)


Material	Nickel-plated brass	RoHS
Protection class	IP 54	



AG	D mm	GL mm	H mm	Item-No
M12 x 1,5	14	5	7,5	1.052.1200.50
M16 x 1,5	18	5	8	1.052.1600.50
M20 x 1,5	22	6,5	9,5	1.052.2000.50
M25 x 1,5	28	7	11	1.052.2500.50
M32 x 1,5	35	8	12	1.052.3200.50
M40 x 1,5	45	8,5	13	1.052.4000.50
M50 x 1,5	54	9	15	1.052.5000.50
M63 x 1,5	67	10	16	1.052.6300.50

Accessories

Plug V-N-Ms-SD (metric, PG)




Material	Nickel-plated brass
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Temperature range	-40°C to +80°C

RoHS

// Other O-Ring materials on request

AG	D mm	GL mm	H mm	Item-No
M12 x 1,5	14	6,5	9,5	1.052.1201.50
M16 x 1,5	20	6	9	1.052.1601.50
M20 x 1,5	24	6,5	9,5	1.052.2001.50
M25 x 1,5	28	7	11	1.052.2501.50
M32 x 1,5	35	8	12,5	1.052.3201.50
M40 x 1,5	45	8	12	1.052.4001.50
M50 x 1,5	55	9	15	1.052.5001.50
M63 x 1,5	68	10	16	1.052.6301.50
PG 7	14	4,8	8	1.052.0701.01
PG 9	17	5,5	9	1.052.0901.01
PG 11	20	5,5	9	1.052.1101.01
PG 13,5	22	6	9,5	1.052.1301.01
PG 16	24	6	9,5	1.052.1601.01
PG 21	30	6,5	11	1.052.2101.01
PG 29	39	7,5	12	1.052.2901.01
PG 36	50	9	15	1.052.3601.01
PG 42	57	10	16	1.052.4201.01
PG 48	64	10	16	1.052.4801.01

Plug V-NE-Ms (metric, PG)



Material

Nickel-plated brass

RoHS

Protection class


IP 54

- // Without o-ring
- // NPT thread on request
- // Elongated threads on request

AG	GL mm	H mm	SW mm	Item-No
M12 x 1,5	6,5	9,5	14	1.155.1200.50
M16 x 1,5	6	9	19	1.155.1600.50
M20 x 1,5	6	9,5	22	1.155.2000.50
M25 x 1,5	7	10,5	30	1.155.2500.50
M32 x 1,5	8	12,5	41	1.155.3200.50
M40 x 1,5	8	13	46	1.155.4000.50
M50 x 1,5	9	15	55	1.155.5000.50
M63 x 1,5	10	16,5	70	1.155.6300.50
PG 9	6	9	17	1.155.0900.01
PG 11	6	9,5	20	1.155.1100.01
PG 13,5	6,5	10	22	1.155.1300.01
PG 16	6,5	10	24	1.155.1600.01
PG 21	7	10,5	30	1.155.2100.01
PG 29	8	12,5	41	1.155.2900.01

Accessories

Plug V-NE-Ms-SD (metric, PG)



Material	Nickel-plated brass
Material o-ring	NBR / FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Temperature range	-20°C to +180°C / -20°C to +95°C


RoHS

- // NPT thread on request
- // Elongated threads on request
- // Other O-Ring materials on request

AG	GL mm	H mm	SW mm	Item-No NBR -20°C to +95°C	Item-No FKM -20°C to +180°C
M12 x 1,5	6,5	9,5	14	1.156.1200.50	1.157.1200.50
M16 x 1,5	6	9	19	1.156.1600.50	1.157.1600.50
M20 x 1,5	6	9,5	22	1.156.2000.50	1.157.2000.50
M25 x 1,5	7	10,5	30	1.156.2500.50	1.157.2500.50
M32 x 1,5	8	12,5	41	1.156.3200.50	1.157.3200.50
M40 x 1,5	8	13	46	1.156.4000.50	1.157.4000.50
M50 x 1,5	9	15	55	1.156.5000.50	1.157.5000.50
M63 x 1,5	10	16,5	70	1.156.6300.50	1.157.6300.50
PG 7	5	8	14	1.156.0700.01	
PG 9	6	9	17	1.156.0900.01	
PG 11	6	9,5	20	1.156.1100.01	
PG 13,5	6,5	10	22	1.156.1300.01	
PG 16	6,5	10	24	1.156.1600.01	
PG 21	7	10,5	30	1.156.2100.01	
PG 29	8	12,5	41	1.156.2900.01	
PG 36	8	13	50	1.156.3600.01	
PG 42	9	15	58	1.156.4200.01	
PG 48	10	16,5	65	1.156.4800.01	



Plug V-INOX metric (metric, PG)



Material	INOX 1.4305
Material o-ring	VMQ (silicone) / FKM / NBR
Protection class	IP 69 K / IP 68 – 10 bar / IP68 - 10bar/30min
Temperature range	-20°C to +95°C / -60°C to +180°C / -20°C to +180°C

RoHS


// Elongated threads on request

// Other sizes on request

AG	GL mm	H mm	SW mm	Item-No NBR -20°C to +95°C	Item-No FKM -20°C to +180°C	Item-No VMQ (silicone) -60°C to +180°C
M12 x 1,5	6,5	9,5	14	1.152.1200.50	1.153.1200.50	1.154.1200.50
M16 x 1,5	6	9	19	1.152.1600.50	1.153.1600.50	1.154.1600.50
M20 x 1,5	6	9,5	22	1.152.2000.50	1.153.2000.50	1.154.2000.50
M25 x 1,5	7	10,5	30	1.152.2500.50	1.153.2500.50	1.154.2500.50
M32 x 1,5	8	12,5	41	1.152.3200.50	1.153.3200.50	1.154.3200.50
M40 x 1,5	8	13	46	1.152.4000.50	1.153.4000.50	1.154.4000.50
PG 7	5	8	14	1.152.0700.01		
PG 9	6	9	17	1.152.0900.01		
PG 11	6	9,5	20	1.152.1100.01		
PG 13,5	6,5	10	22	1.152.1300.01		
PG 16	6,5	10	24	1.152.1600.01		
PG 21	7	10,5	30	1.152.2100.01		
PG 29	8	12,5	41	1.152.2900.01		
PG 36	8	13	50	1.152.3600.01		

Accessories

Adapter R-FS type A (metric)




Material	Polyamide
Temperature range	-40°C to +80°C
Colour	grey
RAL	7035

RoHS

// For further sizes see type B or C

AG	IG	Type	D mm	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	A	24	9	16	22	1.272.1612.50
M20 x 1,5	M16 x 1,5	A	27	9	16	24	1.272.2016.50
M25 x 1,5	M20 x 1,5	A	32	10	17	29	1.272.2520.50
M32 x 1,5	M25 x 1,5	A	40	12	19	36	1.272.3225.50
M40 x 1,5	M32 x 1,5	A	51	12	19	46	1.272.4032.50
M50 x 1,5	M40 x 1,5	A	61	14	21	55	1.272.5040.50
M63 x 1,5	M50 x 1,5	A	75	15	22	65	1.272.6350.50

Reducer R-M-PA Type B (metric)




Material	Polyamide
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS

// For further sizes see type A or C

AG	IG	Type	d mm	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	B	10	8	6	20	1.273.1612.50
M20 x 1,5	M16 x 1,5	B	13,5	8	6	25	1.273.2016.50
M25 x 1,5	M20 x 1,5	B	18	8	6	29	1.273.2520.50
M32 x 1,5	M25 x 1,5	B	23	10	6	36	1.273.3225.50

Adapter R-M-PA type C (metric, PG)



Material	Polypropylene
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS


// For further sizes see type A or B

AG	IG	Type	d mm	GL mm	H mm	Item-No
M40 x 1,5	M32 x 1,5	C	30	15	5	1.273.4032.50
M50 x 1,5	M40 x 1,5	C	38	15	5	1.273.5040.50
M63 x 1,5	M50 x 1,5	C	48	15	5	1.273.6350.50
PG 9	M12 x 1,5	C	8,5	15	19	1.273.0912.11
PG 11	M16 x 1,5	C	11,5	15	19	1.273.1116.11
PG 21	M25 x 1,5	C	20,5	15	19	1.273.2125.11
PG 29	M32 x 1,5	C	28	15	19	1.273.2932.11
PG 36	M40 x 1,5	C	38	15	5	1.273.3640.11
PG 42	M40 x 1,5	C	38	15	5	1.273.4240.11
PG 48	M50 x 1,5	C	38	15	5	1.273.4850.11

Material


Nickel-plated brass

RoHS



AG	IG	D mm	GL mm	H mm	Item-No
M16 x 1,5	M12 x 1,5	20	6	8,5	1.076.1612.50
M20 x 1,5	M12 x 1,5	24	6,5	9	1.076.2012.50
M20 x 1,5	M16 x 1,5	24	6,5	9	1.076.2016.50
M25 x 1,5	M16 x 1,5	30	7	10	1.076.2516.50
M25 x 1,5	M20 x 1,5	30	7	10	1.076.2520.50
M32 x 1,5	M20 x 1,5	37	8	11,5	1.076.3220.50
M32 x 1,5	M25 x 1,5	37	8	11,5	1.076.3225.50
M40 x 1,5	M25 x 1,5	43	8	11,5	1.076.4025.50
M40 x 1,5	M32 x 1,5	43	9	12,5	1.076.4032.50
M50 x 1,5	M32 x 1,5	56	10	14	1.076.5032.50
M50 x 1,5	M40 x 1,5	56	10	14	1.076.5040.50
M63 x 1,5	M40 x 1,5	66	10	14	1.076.6340.50
M63 x 1,5	M50 x 1,5	66	10	14	1.076.6350.50
PG 9	PG 7	17	6	8,5	1.071.0907.01
PG 11	PG 9	20	6	8,5	1.071.1109.01
PG 13,5	PG 11	22	6,5	9	1.071.1311.01
PG 16	PG 9	24	6,5	9,5	1.071.1609.01
PG 16	PG 11	24	6,5	9,5	1.071.1611.01
PG 16	PG 13,5	24	6,5	9,5	1.071.1613.01
PG 21	PG 16	30	7	10	1.071.2116.01
PG 29	PG 21	39	8	11,5	1.071.2921.01
PG 36	PG 29	50	9	12,5	1.071.3629.01
PG 42	PG 36	57	10	14	1.071.4236.01
PG 48	PG 36	64	10	14	1.071.4836.01
PG 48	PG 42	64	10	14	1.071.4842.01

Adapter RSD-Ms (metric, PG)




Material	Nickel-plated brass
Material o-ring	NBR
Temperature range	-40°C to +100°C

RoHS

// O-ring made of FKM / VMQ on request

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	6	8,5	18	1.077.1612.50
M20 x 1,5	M12 x 1,5	6	9	22	1.077.2012.50
M20 x 1,5	M16 x 1,5	6	9	22	1.077.2016.50
M25 x 1,5	M16 x 1,5	7	10	27	1.077.2516.50
M25 x 1,5	M20 x 1,5	7	10	27	1.077.2520.50
M32 x 1,5	M16 x 1,5	8	11	34	1.077.3216.50
M32 x 1,5	M20 x 1,5	8	11,5	35	1.077.3220.50
M32 x 1,5	M25 x 1,5	8	11	34	1.077.3225.50
M40 x 1,5	M20 x 1,5	8	12	43	1.077.4020.50
M40 x 1,5	M25 x 1,5	9	13,5	43	1.077.4025.50
M40 x 1,5	M32 x 1,5	9	13,5	43	1.077.4032.50
M50 x 1,5	M25 x 1,5	9	13	55	1.077.5025.50
M50 x 1,5	M32 x 1,5	10	14	54	1.077.5032.50
M50 x 1,5	M40 x 1,5	9	13	55	1.077.5040.50
M63 x 1,5	M32 x 1,5	10	14	65	1.077.6332.50
M63 x 1,5	M40 x 1,5	10	14	65	1.077.6340.50
M63 x 1,5	M50 x 1,5	10	14	68	1.077.6350.50
PG 9	PG 7	6	8,8	17	1.077.0907.01
PG 11	PG 9	6	9	20	1.077.1109.01
PG 13,5	PG 9	6,5	9,5	22	1.077.1309.01
PG 13,5	PG 11	6,5	9,5	22	1.077.1311.01
PG 16	PG 9	6,5	9,5	24	1.077.1609.01
PG 16	PG 11	6,5	9,5	24	1.077.1611.01
PG 16	PG 13,5	6,5	9,5	24	1.077.1613.01
PG 21	PG 13,5	7	10,3	30	1.077.2113.01
PG 21	PG 16	7	10,3	30	1.077.2116.01
PG 29	PG 21	8	11,5	40	1.077.2921.01
PG 36	PG 21	9	12,5	50	1.077.3621.01
PG 36	PG 29	9	12,5	50	1.077.3629.01




Material

Nickel-plated brass

RoHS

AG	IG	D mm	GL mm	H mm	Item-No
M16 x 1,5	PG 9	20	6	10,5	1.039.1609.01
M20 x 1,5	PG 16	24	6,5	12,5	1.039.2016.01
M25 x 1,5	PG 16	28	6,5	12,5	1.039.2516.01
M25 x 1,5	PG 21	30	6,5	14,5	1.039.2521.01
M32 x 1,5	PG 29	39	7	16	1.039.3229.01
PG 9	M16 x 1,5	20	6	10,5	1.039.0916.01
PG 11	M20 x 1,5	22	6,5	12,5	1.039.1120.01
PG 13,5	M20 x 1,5	22	6,5	12,5	1.039.1320.01
PG 16	M25 x 1,5	27	6,5	14,5	1.039.1625.01

Adapter RE-Ms (metric, PG, NPT)




Material	Nickel-plated brass
Material o-ring	NBR
Temperature range	-40°C to +100°C

RoHS

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1,5	NPT 1/2"	6	17	24	1.171.1612.50
M20 x 1,5	NPT 1/2"	6	17	24	1.171.2012.50
M25 x 1,5	NPT 1/2"	7	8	30	1.171.2512.50
M25 x 1,5	NPT 3/4"	7	19	30	1.171.2534.50
M32 x 1,5	NPT 1"	8	25	40	1.171.3210.50
M32 x 1,5	NPT 1 1/4"	8	25	46	1.171.3254.50
PG 11	NPT 1/2"	6	16,7	24	1.171.1112.01
PG 13,5	NPT 1/2"	6,5	17	24	1.171.1312.01
PG 16	NPT 1/2"	6,5	16,5	24	1.171.1612.01
PG 21	NPT 1/2"	7	8	30	1.171.2112.01
PG 21	NPT 3/4"	7	17	30	1.171.2134.01
PG 29	NPT 1"	8	12	40	1.171.2910.01

Adapter RS-INOX (metric, PG)


Material	INOX 1.4305	RoHS
Temperature range	-20°C to +95°C	



AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	6	9	19	1.094.1612.50
M20 x 1,5	M12 x 1,5	6	9,5	22	1.094.2012.50
M20 x 1,5	M16 x 1,5	6	9,5	22	1.094.2016.50
M25 x 1,5	M16 x 1,5	7	10,5	30	1.094.2516.50
M25 x 1,5	M20 x 1,5	7	10,5	30	1.094.2520.50
M32 x 1,5	M20 x 1,5	8	12,5	41	1.094.3220.50
M32 x 1,5	M25 x 1,5	8	12,5	41	1.094.3225.50
M40 x 1,5	M32 x 1,5	8	13	46	1.094.4032.50
M50 x 1,5	M40 x 1,5	9	15	55	1.094.5040.50
M63 x 1,5	M50 x 1,5	10	16,5	65	1.094.6350.50



Adapter RSD-INOX (metric, PG)



Material	INOX 1.4305
Material o-ring	NBR
Protection class	IP68 - 10bar/30min / IP 69 K
Temperature range	-20°C to +95°C


RoHS

// Other O-Ring materials on request

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	6	9	19	1.097.1612.50
M20 x 1,5	M12 x 1,5	6	9,5	22	1.097.2012.50
M20 x 1,5	M16 x 1,5	6	9,5	22	1.097.2016.50
M25 x 1,5	M16 x 1,5	7	10,5	30	1.097.2516.50
M25 x 1,5	M20 x 1,5	7	10,5	30	1.097.2520.50
M32 x 1,5	M20 x 1,5	8	12,5	41	1.097.3220.50
M32 x 1,5	M25 x 1,5	8	12,5	41	1.097.3225.50
M40 x 1,5	M32 x 1,5	8	13	46	1.097.4032.50
M50 x 1,5	M25 x 1,5	9	15	55	1.097.5025.50
M50 x 1,5	M40 x 1,5	9	15	55	1.097.5040.50
M63 x 1,5	M50 x 1,5	10	16,5	65	1.097.6350.50



Adapter E-M-PA type A (metric, PG)




Material	Polyamide
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS

// For further sizes see type C

AG	IG	Type	d mm	GL mm	H mm	SW mm	Item-No
M12 x 1,5	M16 x 1,5	A	6,5	8	12	21	1.239.1216.50
M16 x 1,5	M20 x 1,5	A	9	8	13	25	1.239.1620.50
M20 x 1,5	M25 x 1,5	A	14	8	15	30	1.239.2025.50
PG 9	M16 x 1,5	A	9	8	12	21	1.239.0916.11
PG 13,5	M20 x 1,5	A	14	8	13	25	1.239.1320.11
PG 16	M25 x 1,5	A	16	8	15	30	1.239.1625.11
PG 21	M32 x 1,5	A	21	8	15	37	1.239.2132.11
PG 29	M40 x 1,5	A	30	10	17	45	1.239.2940.11

Adapter E-M-PA type C (metric, PG)



Material	Polypropylene
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS


// For further sizes see type A

AG	IG	Type	d mm	GL mm	H mm	Item-No
M25 x 1,5	M32 x 1,5	C	16,5	15	15	1.239.2532.50
M32 x 1,5	M40 x 1,5	C	23	15	19,5	1.239.3240.50
M40 x 1,5	M50 x 1,5	C	30	15	19,5	1.239.4050.50
M50 x 1,5	M63 x 1,5	C	39	15	20	1.239.5063.50
PG 7	M12 x 1,5	C	6	15	19	1.239.0712.11
PG 11	M20 x 1,5	C	11,5	15	19	1.239.1120.11
PG 36	M50 x 1,5	C	37	15	19,5	1.239.3650.11
PG 42	M50 x 1,5	C	43	15	19,5	1.239.4250.11
PG 48	M63 x 1,5	C	48	15	20	1.239.4863.11

Material


Nickel-plated brass

RoHS



AG	IG	D mm	GL mm	H mm	Item-No
M12 x 1,5	M16 x 1,5	18	5	15	1.033.1216.50
M16 x 1,5	M20 x 1,5	22	6	17,5	1.033.1620.50
M20 x 1,5	M25 x 1,5	27	6,5	19	1.033.2025.50
M25 x 1,5	M32 x 1,5	34	6,5	21	1.033.2532.50
M32 x 1,5	M40 x 1,5	42	7	23	1.033.3240.50
M40 x 1,5	M50 x 1,5	53	9	31	1.033.4050.50
M50 x 1,5	M63 x 1,5	66	9	31	1.033.5063.50
PG 7	PG 9	17	5	15	1.033.0709.01
PG 9	PG 11	20	6	16,5	1.033.0911.01
PG 9	PG 13,5	22	6	17,5	1.033.0913.01
PG 11	PG 13,5	22	6	17,5	1.033.1113.01
PG 11	PG 16	24	6	18,5	1.033.1116.01
PG 13,5	PG 16	24	6,5	19	1.033.1316.01
PG 16	PG 21	30	6,5	21	1.033.1621.01
PG 21	PG 29	39	7	23	1.033.2129.01
PG 29	PG 36	50	8	27,5	1.033.2936.01
PG 36	PG 42	57	9	31	1.033.3642.01
PG 42	PG 48	64	10	33	1.033.4248.01

Rightangle snap elbow (metric)




Material	Polyamide
Material o-ring	NBR
Protection class	IP 68
Temperature range	-20°C to +80°C
Colour	black / grey
RAL	9005 / 7035

// Other sizes on request

RoHS

AG	IG	GL mm	H mm	L mm	Item-No black	Item-No grey
M16 x 1,5	M16 x 1,5	8	23	28,5	1.316.1601.50	1.316.1600.50
M20 x 1,5	M20 x 1,5	9	30,5	35	1.316.2001.50	1.316.2000.50
M25 x 1,5	M25 x 1,5	11	40	49	1.316.2501.50	1.316.2500.50

Multiple cable insertion HSK-ME



Material

Elastomer

RoHS


Temperature range

-40°C to +100°C

- // Further seal inserts on request
- // The inserts are exclusively capable for the glands of the HSK series
- // *Slotted variant for inserting pre-assembled cables and lines

Suitable for AG	Suitable for AG2	Suitable for AG3	Number of holes x d	Item-No	Number of holes x d	Item-No	Number of holes x d	Item-No
PG 7	M12 x 1,5		1 x 1,5*	1.089.0712.19	-	1.089.0799.19		
PG 9 / KR PG 11	M16 x 1,5	NPT 3/8"	2 x 3	1.089.0901.19	4 x 2,3	1.089.0908.19	6 x 1,4	1.089.0905.19
PG 9 / KR PG 11	M16 x 1,5	NPT 3/8"	-	1.089.0999.19	2 x 1,7	1.089.0903.19	3 x 1,7	1.089.0906.19
PG 11 / KR PG 13,5	M16 x 1,5 / 11		2 x 4	1.089.1102.19	3 x 3	1.089.1101.19		
PG 13,5 / KE PG 11 / KR PG 16	M20 x 1,5	NPT 1/2"	1 x 5*	1.089.1312.19	1 x 4,6	1.089.1310.19	2 x 5,2	1.089.1305.19
PG 13,5 / KE PG 11 / KR PG 16	M20 x 1,5	NPT 1/2"	2 x 2,5	1.089.1308.19	2 x 5	1.089.1303.19	3 x 2	1.089.1300.19
PG 16 / KE PG 13,5 / KR PG 21	M20 x 1,5 / 16	NPT 1/2" / 16	2 x 6	1.089.1605.19	-	1.089.1699.19	2 x 4,5	1.089.1614.19
PG 16 / KE PG 13,5 / KR PG 21	M20 x 1,5 / 16	NPT 1/2" / 16	3 x 5,6	1.089.1606.19	3 x 4	1.089.1601.19	4 x 4	1.089.1602.19
PG 16 / KE PG 13,5 / KR PG 21	M20 x 1,5 / 16	NPT 1/2" / 16	6 x 4	1.089.1604.19				
PG 21 / KE PG 16	M25 x 1,5	NPT 3/4"	1 x 5,8*	1.089.2113.19	1 x 8	1.089.2104.19	-	1.089.2199.19
PG 21 / KE PG 16	M25 x 1,5	NPT 3/4"	1 x 7*	1.089.2117.19	2 x 8	1.089.2102.19	2 x 7,4	1.089.2108.19
PG 21 / KE PG 16	M25 x 1,5	NPT 3/4"	4 x 5	1.089.2103.19	4 x 6	1.089.2100.19		
PG 29	M32 x 1,5	NPT 1 1/4"	2 x 11	1.089.2908.19	6 x 6,5	1.089.2900.19	-	1.089.2999.19
PG 29	M32 x 1,5	NPT 1 1/4"	4 x 9	1.089.2901.19	4 x 9,5	1.089.2902.19		
PG 36	M40 x 1,5	NPT 1 1/2"	2 x 15	1.089.3603.19	7 x 9	1.089.3601.19	-	1.089.3699.19
PG 36	M40 x 1,5	NPT 1 1/2"	6 x 8	1.089.3602.19	10 x 5	1.089.3621.19		
PG 48	M63 x 1,5		-	1.089.4899.19				

O-Rings



Material	VMQ (silicone) / FKM / NBR
Temperature range	-40°C to +100°C / -20°C to +200°C / -60°C to +200°C

RoHS



// Temperature limit

Suitable for AG	d mm	s mm	Item-No NBR	Item-No FKM	Item-No VMQ (silicone)
M12 x 1,5 / PG 7	10	1,5	1.321.1200.57	1.321.1200.58	1.321.1200.59
M16 x 1,5 / PG 9	12	1,5	1.321.1600.57	1.321.1600.58	1.321.1600.59
M20 x 1,5 / PG 13,5	17	1,8	1.321.2000.57	1.321.2000.58	1.321.2000.59
M25 x 1,5	22	2	1.321.2500.57	1.321.2500.58	1.321.2500.59
M32 x 1,5	29	2	1.321.3200.57	1.321.3200.58	1.321.3200.59
M40 x 1,5	35	2	1.321.4000.57	1.321.4000.58	1.321.4000.59
M50 x 1,5 / PG 36	43	2	1.321.5000.57	1.321.5000.58	1.321.5000.59
M63 x 1,5 / PG 48	55	2	1.321.6300.57	1.321.6300.58	1.321.6300.59
PG 11	16	1,5	1.321.1100.17	1.321.1100.21	1.321.1100.22
PG 16	18	1,5	1.321.1600.17	1.321.1600.21	1.321.1600.22
PG 21	26	2	1.321.2100.17	1.321.2100.21	1.321.2100.22
PG 29	33	2	1.321.2900.17	1.321.2900.21	1.321.2900.22
PG 42	50	2	1.321.4200.17	1.321.4200.21	1.321.4200.22
NPT 3/8"	13	2	1.321.3800.77	1.321.3800.78	1.321.3800.79
NPT 1/2"	19	1,8	1.321.1200.77	1.321.1200.78	1.321.1200.79
NPT 3/4"	25	2			1.321.3400.79
NPT 3/4"	25	2,5	1.321.3400.77	1.321.3400.78	
NPT 1"	29	2			1.321.1000.79
NPT 1"	30	2,5	1.321.1000.77	1.321.1000.78	
NPT 1 1/4"	38	2,5	1.321.5400.77	1.321.5400.78	1.321.5400.79
NPT 1 1/2"	45	2,5	1.321.6400.77	1.321.6400.78	1.321.6400.79

Thread seal ring made of polyethylene


Material	Polyethylene
Temperature range	-30°C to +70°C

RoHS



Suitable for AG	d mm	D mm	s mm	Item-No
M12 x 1,5	12	16	2	1.325.1200.59
M16 x 1,5	16	20	2	1.325.1600.59
M20 x 1,5	20	24	2	1.325.2000.59
M25 x 1,5	25	31	2	1.325.2500.59
M32 x 1,5	32	38	2	1.325.3200.59
M40 x 1,5	40	52,7	2	1.325.4000.59
M50 x 1,5	50	58	2	1.325.5000.59
M63 x 1,5	63	72	2	1.325.6300.59
PG 7	12,5	16,5	2	1.325.0700.19
PG 9	15,2	19	2	1.325.0900.19
PG 11	18,6	22,5	2	1.325.1100.19
PG 13,5	20,4	25	2	1.325.1300.19
PG 16	22,5	27	2	1.325.1600.19
PG 21	28,3	33,5	2	1.325.2100.19
PG 29	37	43,5	2	1.325.2900.19
PG 36	47	55	2	1.325.3600.19
PG 42	54	63	2	1.325.4200.19
PG 48	59,3	69	2	1.325.4800.19

Thread seal ring made of fibre composite material



Material

Fiber composite


RoHS

Temperature range

-50°C to +250°C

Suitable for AG	d mm	D mm	s mm	Item-No
M12 x 1,5	12	16	2	1.325.1200.50
M16 x 1,5	16	20	2	1.325.1600.50
M20 x 1,5	20	25	2	1.325.2000.50
M25 x 1,5	25	31	2	1.325.2500.50
M32 x 1,5	32	38	2	1.325.3200.50
M40 x 1,5	40	48	2	1.325.4000.50
M50 x 1,5	50	58	2	1.325.5000.50
M63 x 1,5	63	72	2	1.325.6300.50
PG 7	12,5	16,5	1,5	1.325.0700.20
PG 9	15,2	19	1,5	1.325.0900.20
PG 11	18,6	22,5	1,5	1.325.1100.20
PG 13,5	20,4	25	1,5	1.325.1300.20
PG 16	22,5	27	1,5	1.325.1600.20
PG 21	28,3	33,5	2	1.325.2100.20
PG 29	37	43,5	2	1.325.2900.20
PG 48	59,3	69	2	1.325.4800.20


Breather drain KS (metric)



Material	Polyamide
Protection class	IP 54
Temperature range	-40°C to +100°C
Colour	black / grey
RAL	9005 / 7035

AG	GL mm	H mm	SW mm	Item-No black	Item-No grey
M25 x 1,5	15	21,5	30	1.213.2501.50	1.213.2500.50

Compression clamp KLE (metric, PG)



Material Nickel-plated brass

RoHS

// Other sizes on request

AG	∅k mm	GL mm	H mm	SW mm	Item-No
M12 x 1,5	5 – 7,5	5,5	15	16	1.143.1200.50
M16 x 1,5	7 – 10	6	16	19	1.143.1600.50
M20 x 1,5	10 – 14	6,5	18	24	1.143.2000.50
M25 x 1,5	12 – 21,5	8	21	34	1.143.2500.50
M32 x 1,5	16 – 27	8	22	42	1.143.3200.50
M40 x 1,5	22 – 33	9,5	25,5	52	1.143.4000.50
PG 7	5,5 – 8	5,5	14,8	16	1.143.0700.01
PG 9	6,5 – 10	6	16,6	19	1.143.0900.01
PG 11	7,5 – 12	6	17,3	22	1.143.1100.01
PG 13,5	8,5 – 14	6,5	17,8	24	1.143.1300.01
PG 16	9,5 – 16	6,5	18,3	26	1.143.1600.01
PG 21	12 – 21	7,5	20,8	33	1.143.2100.01
PG 29	19 – 30	8	21,8	42	1.143.2900.01
PG 36	25 – 37	9,5	25,3	52	1.143.3600.01
PG 42	31 – 43	10	26,3	59	1.143.4200.01
PG 48	35 – 48	11	27,3	64	1.143.4800.01

Ex CABLE GLANDS

HUMMEL offers a wide range of cable glands for explosion protection areas. This includes cable glands for ignition protection types Ex d, Ex e and Ex t. For areas where "Increased Safety" (Ex e) is prescribed, HUMMEL offers plastic and metal cable glands, also with multi or flat cable inserts. Cable glands for ignition type Ex d meet the requirements for "Pressure-tight Encapsulation". This prevents transfer of an explosion in the housing interior to the exterior.

- // HSK-K-Ex-Active, the plastic cable gland for ex-areas
- // Ex e metal cable glands with various inserts
- // Ex d metal cable glands for pressure-tight encapsulation
- // Ex t metal cable glands for dust explosion protection through encapsulation

HUMMEL has many years of experience in handling components for explosion-protection areas. This is why we have a sophisticated range of explosion area products in a range of materials and designs.



Polyamide cable glands for areas at risk of explosion

The cable gland made of specially formulated, fibreglass reinforced polyamide is designed for use on electrical equipment with protection types Ex e and Ex t. It has been developed in accordance with current international and national standards in accordance with the respective standards:

- ATEX / IECEx
- HazLoc according to cSAus standard
- CCC certification for China

- // Free of halogen
- // Protection class IP 68 up to 10 bar / 30 min
- // Union nut vibration protection
- // Wear-resistant labelling
- // Suitable for use in Class II Division 1; Class I Zone 1; Class II Zone 1

HSK-K-Ex-Active

Overlapping clamping plates guarantee high cable strain relief

The chambered moulded seal securely seals the cable off

The HUMMEL trapezoidal thread guarantees a stable transfer of force

A chambered O-ring reliably seals the cable gland off from the housing



Reliable explosion protection


Not all forms of explosion protection are equal. There are different scenarios and areas of application which require different types of explosion protection. Ex cable glands from HUMMEL offer protection in a wide range of environments.

Ex e Increased safety: The cable gland prevents the occurrence of sparks and arcs inside or on external parts of electrical equipment, which do not occur during normal operation in according to DIN EN IEC 60079-7.

Ex d Flameproof enclosure: Parts which can ignite an explosive atmosphere are firmly set in an enclosure. The housing withstands the explosion pressure and prevents transmission to the outside according to DIN EN IEC 60079-1.


Ex t Equipment dust explosion protection by enclosure: The cable gland protects the enclosure in accordance with DIN EN IEC 60079-31.

HSK-M-Ex d



Ex cable glands

HSK-K-Ex-Active (metric)



Material	Polyamide, fiber reinforced
Seal	NBR
Material o-ring	NBR
Protection class	IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-20°C to +85°C
Colour	black / blue-black
RAL	9005 / 5012


RoHS

AG	Øk mm	H mm	SW1/SW2 mm	Nm	Item-No black	Item-No blue-black
M12 x 1,5	2 – 5	21	15/15	2	1.292.1201.51	
M12 x 1,5	3 – 6,5	21	15/15	1,5	1.292.1201.50	
M16 x 1,5	3 – 6	22	19/19	2	1.292.1601.51	1.292.1602.51
M16 x 1,5	4 – 8	22	19/19	2	1.292.1601.50	1.292.1602.50
M16 x 1,5	5 – 10	25	22/22	3	1.292.1611.50	1.292.1612.50
M20 x 1,5	5 – 9	27	24/24	4,5	1.292.2001.51	1.292.2002.51
M20 x 1,5	6 – 12	27	24/24	4,5	1.292.2001.50	1.292.2002.50
M20 x 1,5	10 – 14	28	27/27	4,5	1.292.2016.50	1.292.2017.50
M25 x 1,5	9 – 16	31	33/33	5	1.292.2501.51	1.292.2502.51
M25 x 1,5	13 – 18	31	33/33	5	1.292.2501.50	1.292.2502.50
M32 x 1,5	13 – 20	39	42/42	6,5	1.292.3201.51	1.292.3202.51
M32 x 1,5	18 – 25	39	42/42	6,5	1.292.3201.50	1.292.3202.50
M40 x 1,5	20 – 26	48	53/53	10	1.292.4001.51	
M40 x 1,5	22 – 32	48	53/53	10	1.292.4001.50	
M50 x 1,5	25 – 31	49	60/60	15	1.292.5001.51	
M50 x 1,5	32 – 38	49	60/60	15	1.292.5001.50	
M63 x 1,5	29 – 35	49	65/68	22	1.292.6301.51	
M63 x 1,5	37 – 44	49	65/68	22	1.292.6301.50	



to the assembly
instruction





Material	Polyamide, fiber reinforced
Seal	NBR
Material o-ring	NBR
Protection class	IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-20°C to +85°C
Colour	black
RAL	9005

RoHS

AG	∅k mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	21	15/15	2	1.292.1201.31
M12 x 1,5	3 – 6,5	21	15/15	1,5	1.292.1201.30
M16 x 1,5	3 – 6	22	19/19	2	1.292.1601.31
M16 x 1,5	4 – 8	22	19/19	2	1.292.1601.30
M16 x 1,5	5 – 10	25	22/22	3	1.292.1611.30
M20 x 1,5	5 – 9	27	24/24	4,5	1.292.2001.31
M20 x 1,5	6 – 12	27	24/24	4,5	1.292.2001.30
M20 x 1,5	7 – 12	28	27/27	4,5	1.292.2016.31
M20 x 1,5	10 – 14	28	27/27	4,5	1.292.2016.30
M25 x 1,5	9 – 16	31	33/33	5	1.292.2501.31
M25 x 1,5	13 – 18	31	33/33	5	1.292.2501.30
M32 x 1,5	13 – 20	39	42/42	6,5	1.292.3201.31
M32 x 1,5	18 – 25	39	42/42	6,5	1.292.3201.30
M40 x 1,5	20 – 26	48	53/53	10	1.292.4001.31
M40 x 1,5	22 – 32	48	53/53	10	1.292.4001.30
M50 x 1,5	25 – 31	49	60/60	15	1.292.5001.31
M50 x 1,5	32 – 38	49	60/60	15	1.292.5001.30
M63 x 1,5	29 – 35	49	65/68	22	1.292.6301.31
M63 x 1,5	37 – 44	49	65/68	22	1.292.6301.30




to the assembly
instruction



Ex cable glands

HSK-K-Ex-Active (NPT)



Material	Polyamide, fiber reinforced
Seal	NBR
Material o-ring	NBR
Protection class	IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-20°C to +85°C
Colour	black
RAL	9005

RoHS


// with blue union nut on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⚙ Nm	Item-No
NPT 3/8"	3 – 6	15	22	19/22	2	1.292.3801.71
NPT 3/8"	4 – 8	15	22	19/22	2	1.292.3801.70
NPT 1/2"	5 – 9	13	27	24/24	4,5	1.292.1201.71
NPT 1/2"	6 – 12	13	27	24/24	4,5	1.292.1201.70
NPT 1/2"	7 – 12	13	28	27/27	4,5	1.292.1216.71
NPT 1/2"	10 – 14	13	28	27/27	4,5	1.292.1216.70
NPT 3/4"	9 – 16	14	31	33/33	5	1.292.3401.71
NPT 3/4"	13 – 18	14	31	33/33	5	1.292.3401.70
NPT 1"	13 – 20	19	39	42/42	6,5	1.292.1001.71
NPT 1"	18 – 25	19	39	42/42	6,5	1.292.1001.70
NPT 1 1/4"	18 – 25	16	39	42/46	6,5	1.292.5401.70
NPT 1 1/2"	22 – 32	20	48	53/53	10	1.292.6401.70



to the assembly
instruction





Material	Polyamide, fiber reinforced
Seal	Elastomer
Material o-ring	NBR
Protection class	IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-20°C to +85°C
Colour	black / blue-black
RAL	9005 / 5012

RoHS

// Further seal inserts on request


// Installation note: The cable diameter may be less than the drill diameter by 20%, but not more than 1 mm

AG	GL mm	H mm	SW1/SW2 mm	 Nm	Number of holes x d	Item-No black	Item-No blue-black
M16 x 1,5	8	22	19/19	2	2 x 3	1.581.1601.51	
M20 x 1,5	9	27	24/24	4,5	2 x 5	1.581.2003.51	
M25 x 1,5	11	31	33/33	5	3 x 7	1.581.2501.51	
M25 x 1,5	11	31	33/33	5	4 x 6	1.581.2500.51	
M32 x 1,5	11	39	42/42	6,5	4 x 9		1.581.3201.52
M32 x 1,5	11	39	42/42	6,5	6 x 6,5	1.581.3200.51	
NPT 3/8"	15	22	19/22	2	2 x 3		1.581.3801.72

to the assembly
instruction

Ex cable glands

HSK-K-MZ-Ex (metric, PG)



Material	Polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Temperature range	-20°C to +70°C
Colour	black
RAL	9005


RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M16 x 1,5	4 – 8	15	29	19/19	3	1.215.1601.50
M20 x 1,5	7 – 12	15	35,5	24/24	3,5	1.215.2001.50
M25 x 1,5	13 – 18	11	41	33/33	5	1.215.2501.50
M32 x 1,5	18 – 25	11	49	42/42	6,5	1.215.3201.50
M40 x 1,5	22 – 32	13	58	53/53	10	1.215.4001.50
M50 x 1,5	32 – 38	13	61,5	60/60	15	1.215.5001.50
M63 x 1,5	37 – 44	14	62	65/68	18	1.215.6301.50



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C / -60°C to +95°C


RoHS

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌚ Nm	Item-No -20°C to +95°C	Item-No -60°C to +95°C
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.610.1200.51	1.640.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.610.1200.50	1.640.1200.50
M16 x 1,5	2 – 6	6	21	17/19	6	1.610.1600.51	1.640.1600.51
M16 x 1,5	3 – 7	6	22	20/20	5	1.610.1611.51	
M16 x 1,5	4 – 8	6	21	17/19	6	1.610.1600.50	1.640.1600.50
M16 x 1,5	5 – 10	6	22	20/20	5	1.610.1611.50	1.640.1611.50
M20 x 1,5	5 – 9	6	23	22/22	8	1.610.2000.51	1.640.2000.51
M20 x 1,5	6 – 12	6	23	22/22	8	1.610.2000.50	1.640.2000.50
M20 x 1,5	7 – 12	6	24	24/24	10	1.610.2016.51	1.640.2016.51
M20 x 1,5	10 – 14	6	24	24/24	10	1.610.2016.50	1.640.2016.50
M25 x 1,5	10 – 16	7	26	30/30	12	1.610.2500.51	1.640.2500.51
M25 x 1,5	14 – 18	7	26	30/30	12	1.610.2500.50	1.640.2500.50
M32 x 1,5	13 – 20	8	31	40/40	15	1.610.3200.51	
M32 x 1,5	20 – 25	8	31	40/40	15	1.610.3200.50	
M40 x 1,5	20 – 26	8	37	50/50	15	1.610.4000.51	
M40 x 1,5	22 – 32	8	37	50/50	15	1.610.4000.50	
M50 x 1,5	25 – 31	9	37	57/57	24	1.610.5000.51	
M50 x 1,5	32 – 38	9	37	57/57	24	1.610.5000.50	
M63 x 1,5	29 – 35	10	38	64/68	30	1.610.6300.51	
M63 x 1,5	37 – 44	10	38	64/68	30	1.610.6300.50	

to the assembly
instruction

Ex cable glands

HSK-M Ex (metric-long)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C

RoHS


// Other sizes on request
// extended temperature range on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M16 x 1,5	4 – 8	10	21	17/19	6	1.610.1600.30
M16 x 1,5	5 – 10	10	22	20/20	5	1.610.1611.30
M20 x 1,5	5 – 9	10	23	22/22	8	1.610.2000.31
M20 x 1,5	6 – 12	10	23	22/22	8	1.610.2000.30
M20 x 1,5	7 – 12	10	24	24/24	10	1.610.2016.31
M20 x 1,5	10 – 14	10	24	24/24	10	1.610.2016.30
M25 x 1,5	14 – 18	12	26	30/30	12	1.610.2500.30



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C

RoHS

// Other sizes on request

// extended temperature range on request


// Elongated threads on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
PG 7	3 – 6,5	5	19	14/14	4	1.610.0700.01
PG 9	4 – 8	6	21	17/17	6	1.610.0900.01
PG 11	3 – 7	6	22	20/20	5	1.610.1100.15
PG 11	5 – 10	6	22	20/20	5	1.610.1100.01
PG 13,5	6 – 12	6,5	24	22/22	8	1.610.1300.01
PG 16	10 – 14	6,5	23	24/24	10	1.610.1600.01
PG 21	14 – 18	7	24	30/30	12	1.610.2100.01

to the assembly
instruction

Ex cable glands

HSK-M-Ex (NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C

RoHS


// extended temperature range on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
NPT 3/8"	2 – 6	15	21	17/19	6	1.610.3800.71
NPT 3/8"	4 – 8	15	21	17/19	6	1.610.3800.70
NPT 1/2"	5 – 9	13	24	22/24	8	1.610.1200.71
NPT 1/2"	6 – 12	13	24	22/24	8	1.610.1200.70
NPT 3/4"	10 – 16	13	25	30/30	12	1.610.3400.71
NPT 3/4"	14 – 18	13	25	30/30	12	1.610.3400.70
NPT 1"	13 – 20	19	29	40/40	15	1.610.1000.71
NPT 1"	20 – 25	19	29	40/40	15	1.610.1000.70



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +130°C

RoHS

// extended temperature range on request


// Other thread pitches on request

AG	$\varnothing k$ mm	H mm	SW1/SW2 mm	 Nm	Item-No
M16 x 1,5	5 – 10	22	20/20	5	1.660.1611.50
M20 x 1,5	7 – 12	23	22/22	8	1.660.2000.50
M20 x 1,5	10 – 14	24	24/24	10	1.660.2016.50
M25 x 1,5	10 – 16	26	30/30	12	1.660.2500.51
M32 x 1,5	13 – 20	31	40/40	15	1.660.3200.51

to the assembly
instruction

Ex cable glands

HSK-M-Multi-Ex (metric, NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	Elastomer
Material o-ring	NBR
Protection class	and optimum assignment of all holes / IP 65 / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Temperature range	-20°C to +95°C

RoHS


// Further seal inserts on request

AG	GL mm	H mm	SW1/SW2 mm	Nm	Number of holes x d	Item-No
M20 x 1,5	6	23	22/22	8	6 x 3	1.687.2001.50
M32 x 1,5	8	31	40/40	15	4 x 9	1.687.3201.50
M32 x 1,5	8	31	40/40	15	6 x 6,5	1.687.3200.50
NPT 1"	19	29	40/40	15	4 x 9	1.687.1001.70



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	Elastomer
Material o-ring	NBR
Protection class	IP 68 – 10 bar and optimum assignment of all bores / IP 65
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Temperature range	-20°C to +95°C

RoHS

// Further seal inserts on request

AG	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M20 x 1,5	6	24	24/24	10	1.689.2017.50
M40 x 1,5	8	37	50/50	15	1.689.4003.50
M63 x 1,5	10	38	64/68	30	1.689.6300.50




to the assembly
instruction



Ex cable glands

HSK-MZ-Ex (metric)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-60°C to +95°C

RoHS


// extended temperature range on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	3 – 6,5	6,5	26	14/14	4	1.641.1200.50
M16 x 1,5	5 – 10	6	30	20/20	5	1.641.1611.50
M20 x 1,5	7 – 12	6	33	22/22	10	1.641.2000.50
M20 x 1,5	10 – 14	6	33	24/24	10	1.641.2016.50
M25 x 1,5	14 – 18	7	37	30/30	12	1.641.2500.50
M32 x 1,5	20 – 25	8	43	40/40	15	1.641.3200.50



to the assembly
instruction





Material	INOX 1.4305
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C

RoHS

// extended temperature range on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.612.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.612.1200.50
M16 x 1,5	3 – 7	6	22	22/22	5	1.612.1600.51
M16 x 1,5	5 – 10	6	22	22/22	5	1.612.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.612.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.612.2000.50
M25 x 1,5	9 – 16	7	24	30/30	12	1.612.2500.51
M25 x 1,5	13 – 18	7	24	30/30	12	1.612.2500.50
M32 x 1,5	13 – 20	8	29	41/41	15	1.612.3200.51
M32 x 1,5	20 – 25	8	29	41/41	15	1.612.3200.50


to the assembly
instruction

ATEX



Ex cable glands

HSK-INOX-PVDF-Ex (metric)



Material	INOX 1.4305
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +130°C

RoHS


// Other sizes on request
// Other thread pitches on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M16 x 1,5	3 – 7	6	22	22/22	5	1.662.1600.51
M16 x 1,5	5 – 10	6	22	22/22	5	1.662.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.662.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.662.2000.50
M25 x 1,5	9 – 16	7	24	30/30	12	1.662.2500.51



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperature range	-60°C to +105°C

RoHS


// Other sizes on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	16	18,7	14/14	7,5	1.622.1200.51
M12 x 1,5	3 – 6,5	16	18,7	14/14	7,5	1.622.1200.50
M16 x 1,5	3 – 7	16	22	20/20	9	1.622.1600.51
M16 x 1,5	5 – 10	16	22	20/20	9	1.622.1600.50
M20 x 1,5	7 – 12	16	25	24/24	10	1.622.2000.51
M20 x 1,5	10 – 14	16	25	24/24	10	1.622.2000.50
M25 x 1,5	9 – 16	16	26,5	30/30	12	1.622.2500.51
M25 x 1,5	13 – 18	16	26,5	30/30	12	1.622.2500.50
M32 x 1,5	14 – 20	16	32	40/40	15	1.622.3200.51
M32 x 1,5	18 – 25	16	32	40/40	15	1.622.3200.50
M40 x 1,5	22 – 32	16	38,5	50/50	24	1.622.4000.50
NPT 1/2"	7 – 12	20	25	24/24	10	1.622.1200.71
NPT 1/2"	10 – 14	20	25	24/24	10	1.622.1200.70
NPT 3/4"	9 – 16	20,5	26,5	30/30	12	1.622.3400.71
NPT 3/4"	13 – 18	20,5	26,5	30/30	12	1.622.3400.70

to the assembly
instruction

Ex cable glands

HSK-M-PVDF-Ex d (metric, NPT)



Material	Nickel-plated brass
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperature range	-20°C to +130°C

RoHS


// Other sizes on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	16	18,7	14/14	7,5	1.634.1200.51
M16 x 1,5	5 – 10	16	22	20/20	9	1.634.1600.50
M20 x 1,5	7 – 12	16	25	24/24	10	1.634.2000.51
M25 x 1,5	9 – 16	16	26,5	30/30	12	1.634.2500.51
NPT 1/2"	7 – 12	20	25	24/24	10	1.634.1200.71
NPT 3/4"	13 – 18	20,5	26,5	30/30	12	1.634.3400.70



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperature range	-60°C to +105°C

RoHS


// Other sizes on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	3 – 6,5	16	26	14/14	7,5	1.628.1200.50
M16 x 1,5	5 – 10	16	30,2	20/20	9	1.628.1600.50
M20 x 1,5	10 – 14	16	34	24/24	10	1.628.2000.50
M25 x 1,5	13 – 18	16	37,8	30/30	12	1.628.2500.50

to the assembly
instruction

Ex cable glands

HSK-INOX-Ex d (metric, NPT)



Material	INOX 1.4404
Clamping insert	Polyamide V0 according to UL94
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperature range	-60°C to +105°C

RoHS


// Other sizes on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	16	19	14/14	7,5	1.632.1200.51
M12 x 1,5	3 – 6,5	16	19	14/14	7,5	1.632.1200.50
M16 x 1,5	3 – 7	16	22	22/22	9	1.632.1600.51
M16 x 1,5	5 – 10	16	22	22/22	9	1.632.1600.50
M20 x 1,5	7 – 12	16	25	24/24	10	1.632.2000.51
M20 x 1,5	10 – 14	16	25	24/24	10	1.632.2000.50
M25 x 1,5	9 – 16	14	26,5	30/30	12	1.632.2500.51
M25 x 1,5	13 – 18	16	26,5	30/30	12	1.632.2500.50
M32 x 1,5	14 – 20	16	32	41/41	15	1.632.3200.51
M32 x 1,5	18 – 25	16	32	41/41	15	1.632.3200.50
M40 x 1,5	20 – 26	16	38,5	50/50	24	1.632.4000.51
M40 x 1,5	22 – 32	16	38,5	50/50	24	1.632.4000.50
NPT 1/2"	7 – 12	20	25	24/24	10	1.632.1200.71
NPT 1/2"	10 – 14	20	25	24/24	10	1.632.1200.70
NPT 3/4"	9 – 16	20,5	26,5	30/30	12	1.632.3400.71
NPT 3/4"	13 – 18	20,5	26,5	30/30	12	1.632.3400.70



to the assembly
instruction





Material	INOX 1.4404
Clamping insert	PVDF
Seal	FKM
Material o-ring	FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperature range	-20°C to +130°C

RoHS

// Other sizes on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	16	19	14/14	7,5	1.633.1200.51
M12 x 1,5	3 – 6,5	16	19	14/14	7,5	1.633.1200.50
M16 x 1,5	3 – 7	16	22	22/22	9	1.633.1600.51
M16 x 1,5	5 – 10	16	22	22/22	9	1.633.1600.50
M20 x 1,5	7 – 12	16	25	24/24	10	1.633.2000.51
M20 x 1,5	10 – 14	16	25	24/24	10	1.633.2000.50
M25 x 1,5	9 – 16	16	26,5	30/30	12	1.633.2500.51
M25 x 1,5	13 – 18	16	26,5	30/30	12	1.633.2500.50
M32 x 1,5	18 – 25	16	32	41/41	15	1.633.3200.50
NPT 3/8"	3 – 7	16	22	22/22	9	1.633.3800.71
NPT 3/8"	5 – 10	16	22	22/22	9	1.633.3800.70
NPT 1/2"	7 – 12	20	25	24/24	10	1.633.1200.71
NPT 1/2"	10 – 14	20	25	24/24	10	1.633.1200.70
NPT 3/4"	9 – 16	20,5	26,5	30/30	12	1.633.3400.71
NPT 3/4"	13 – 18	20,5	26,5	30/30	12	1.633.3400.70

to the assembly
instruction

HISTORY

70 years of HUMMEL: This is the story of the development of a small workshop of the post-war years into an internationally successful family-run company with technologies and products for the industry of today and tomorrow.

1948

Anton Hummel establishes the Anton Hummel metalworking factory in Altsimonswald in the Black Forest. Turned metal parts for everyday products are produced.

1951

Start of cable gland production. Experience acquired from the production of nuts and bolts is the basis for the development of cable glands – and it remains one of the most successful product segments of HUMMEL to this day.

1952

Move from Altsimonswald to Waldkirch. HUMMEL builds a hall-type building there to accommodate the production, warehouse and administration. At the same time, production of vent valves for radiators starts

1970

Start of plastics production in Waldkirch. Beforehand, parts of the metalworking were moved to Kenzingen-Nordweil. The rotatable vent valve is patented and millions are sold in the ensuing years.

1972

Helmut Hummel becomes managing director of Anton Hummel Metallwarenfabrik GmbH. The second generation takes on responsibility for the up-and-coming family business.

1994

HUMMEL builds a logistics centre for its electrical engineering division in Denzlingen. That is the starting signal for numerous other construction phases in the new location. At the same time, cable glands for the explosion-proof segment are launched on the market.

1999

Internationalisation begins with the formation of HUMMEL China. Branches in Italy, Brazil and Russia follow as well as sales offices in Sweden and England. Meanwhile the development of circular connectors begins at the headquarters.

2008

The company's headquarters is moved from Waldkirch to Denzlingen. Beforehand, a new administration building was erected, a fully-automatic high-bay storage was built and the production buildings were extended by house mouldmaking and injection casting.

2013

The company's headquarter is moved from Waldkirch to Denzlingen. Beforehand, a new administration building was erected, a fully-automatic high-bay storage was built and the production buildings were extended by house mouldmaking and injection casting.

2018

HUMMEL celebrates its 70-year company anniversary, records a new sales record of 71.5 million euros, has around 600 employees and is present worldwide with its branches, sales offices and a large partner network.

2023

HUMMEL celebrates its 75-year company anniversary, with a strategic realignment, the challenges of the future are being addressed

EMC-Ex e CABLE GLANDS

Safe EMC protection plus explosion area approval: This is what EMC Ex e cable glands deliver. HUMMEL also offers a range of designs for particular requirements here, too. These include cable glands for high-temperature applications, designs for very easy fitting and also stainless steel versions.


- // HSK-M-EMC-D-Ex: Fast, easy fitting, combined with maximum EMC protection and explosion protection
- // HSK-M-EMC-Ex: Cable glands with excellent shielding properties and explosion protection
- // HSK-MZ-EMC-Ex: Glands with a high level of tension-relief, EMC and explosion protection
- // HSK-INOX-EMC-Ex: Stainless steel cable glands, EMC and explosion protection

HUMMEL has many years of experience in handling components for explosion-protection areas. This is why we have a sophisticated range of explosion area products in a range of materials and designs.



EMC-Ex e cable glands

HSK-M-EMC-D-Ex (metric)



Material	Nickel-plated brass
Clamping insert	Metallized polyamide
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Temperature range	-20°C to +95°C / -60°C to +95°C

RoHS

EMV
EMC

- // Elongated threads on request
- // Other sizes on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No -20°C to +95°C	Item-No -60°C to +95°C
M16 x 1,5	5 – 10	6	29	20/20	11	1.636.1600.50	1.637.1600.50
M16 x 1,5	5 – 10	10	29	20/20	11	1.636.1600.30	1.637.1600.30
M20 x 1,5	10 – 14	6	31	24/24	13	1.636.2000.50	1.637.2000.50
M20 x 1,5	10 – 14	10	31	24/24	13	1.636.2000.30	1.637.2000.30
M25 x 1,5	13 – 18	7	38	30/30	15	1.636.2500.50	1.637.2500.50
M25 x 1,5	13 – 18	12	38	30/30	15	1.636.2500.30	1.637.2500.30
M32 x 1,5	18 – 25	8	43	40/40	17,5	1.636.3200.50	
M32 x 1,5	18 – 25	12	43	40/40	17,5	1.636.3200.30	
M40 x 1,5	24 – 32	8	51	50/50	25	1.636.4000.50	




to the product video



to the assembly
instruction





Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C / -60°C to +95°C

RoHS

EMV
EMC

// Other thread pitches on request

// extended temperature range on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌚ Nm	Item-No -20°C to +95°C	Item-No -60°C to +95°C
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.616.1200.51	
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.616.1200.50	1.646.1200.50
M16 x 1,5	3 – 7	6	22	20/20	5	1.616.1600.51	1.646.1600.51
M16 x 1,5	5 – 10	6	22	20/20	5	1.616.1600.50	1.646.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.616.2000.51	1.646.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.616.2000.50	1.646.2000.50
M25 x 1,5	10 – 16	7	24	30/30	12	1.616.2500.51	1.646.2500.51
M25 x 1,5	14 – 18	7	24	30/30	12	1.616.2500.50	1.646.2500.50
M32 x 1,5	13 – 20	8	31	40/40	15	1.616.3200.51	1.646.3200.51
M32 x 1,5	20 – 25	8	31	40/40	15	1.616.3200.50	1.646.3200.50
M40 x 1,5	20 – 26	8	37	50/50	15	1.616.4000.51	1.646.4000.51
M40 x 1,5	22 – 32	8	37	50/50	15	1.616.4000.50	1.646.4000.50
M50 x 1,5	25 – 31	9	37	57/57	24	1.616.5000.51	
M50 x 1,5	32 – 38	9	37	57/57	24	1.616.5000.50	
M63 x 1,5	37 – 44	10	38	64/68	30	1.616.6300.50	



to the product video




to the assembly
instruction



EMC-Ex e cable glands

HSK-M-EMC-Ex (NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C

RoHS



// Other thread pitches on request

// extended temperature range on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
NPT 1/2"	5 – 9	13	24	22/24	8	1.616.1200.71
NPT 1/2"	6 – 12	13	24	22/24	8	1.616.1200.70
NPT 3/4"	10 – 16	13	25	30/30	12	1.616.3400.71




to the product video



to the assembly
instruction

**ATEX** 



Material	Nickel-plated brass
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-20°C to +95°C / -60°C to +95°C

RoHS

EMV
EMC

// Elongated threads on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌚ Nm	Item-No -20°C to +95°C	Item-No -60°C to +95°C
M12 x 1,5	3 – 6,5	6,5	26	14/14	4	1.617.1200.50	1.647.1200.50
M16 x 1,5	5 – 10	6	29	20/20	5	1.617.1600.50	1.647.1600.50
M20 x 1,5	10 – 14	6	32	24/24	10	1.617.2000.50	1.647.2000.50
M25 x 1,5	13 – 17	7	35	30/30	12	1.617.2500.50	
M32 x 1,5	20 – 25	8	41	40/40	15		1.647.3200.50



to the product video




to the assembly
instruction



EMC-Ex e cable glands

HSK-INOX-EMC-Ex (metric)



Material	INOX 1.4305
Clamping insert	Polyamide V0 according to UL94
Seal	NBR
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Type Rating by	UL 50E / 4X / 6 / 4
Temperature range	-60°C to +95°C

RoHS

EMV
EMC

// Elongated threads on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Item-No
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.673.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.673.1200.50
M16 x 1,5	3 – 7	6	21	22/22	5	1.673.1600.51
M16 x 1,5	5 – 10	6	21	22/22	5	1.673.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.673.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.673.2000.50
M25 x 1,5	9 – 16	7	26	30/30	12	1.673.2500.51
M25 x 1,5	13 – 18	7	26	30/30	12	1.673.2500.50
M32 x 1,5	13 – 20	8	31	41/41	15	1.673.3200.51
M32 x 1,5	18 – 25	8	31	41/41	15	1.673.3200.50
M40 x 1,5	20 – 26	8	37	50/50	15	1.673.4000.51
M40 x 1,5	22 – 32	8	37	50/50	15	1.673.4000.50



to the product video



to the assembly
instruction



ATEX_{Ex}

UK
CA



Ex ACCESSORIES


Cable glands for explosion protection areas also demand accessories specifically designed for those areas. HUMMEL has a wide range of accessories specially developed for this sector. These accessories meet all the requirements for Ex-areas and are backed up by all the necessary certification and approvals.

- // Accessories in plastic, brass and stainless steel
- // Plugs with explosion area approval
- // Reduction fittings in a wide range of different sizes

The accessories come in a range of materials, sizes and thread types.



Plug V-Ex (metric, PG)



Material	Polyamide, fiber reinforced
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-20°C to +90°C
Colour	black
RAL	9005


RoHS

AG	D mm	GL mm	H mm	SW mm	⊙	Item-No
M12 x 1,5	16,5	8,5	13	15	6	1.297.1201.50
M16 x 1,5	20,5	8,5	13	19	8	1.297.1601.50
M20 x 1,5	25,5	9	14,5	24	8	1.297.2001.50
M25 x 1,5	30,5	10,5	16	28	8	1.297.2501.50
M32 x 1,5	38	11,5	17,5	36	8	1.297.3201.50
M40 x 1,5	48	11,5	18	46	8	1.297.4001.50
M50 x 1,5	60	13,5	20	55	8	1.297.5001.50
M63 x 1,5	75	14,5	21	70	8	1.297.6301.50
PG 7	16,5	8,5	13	15	6	1.297.0701.11
PG 9	20,5	8,5	13	19	8	1.297.0901.11
PG 11	25,5	9	14,5	24	8	1.297.1101.11
PG 13,5	25,5	9	14,5	24	8	1.297.1301.11
PG 16	30,5	10,5	16	28	8	1.297.1601.11
PG 21	38	11,5	17,5	36	8	1.297.2101.11
PG 29	48	11,5	18	46	8	1.297.2901.11
PG 36	60	13,5	20	55	8	1.297.3601.11
PG 42	65	13,5	20	60	8	1.297.4201.11
PG 48	75	14,5	21	70	8	1.297.4801.11



to the assembly
instruction





Material	Elastomer
Ex-protection level	II 1D Ex ta IIC Da / II 2G Ex e IIC Gb
Temperature range	-40°C to +95°C
Colour	black
RAL	9005

RoHS


Suitable for AG	Suitable for AG2	Suitable for AG3	D mm	d mm	H mm	h mm	Item-No
PG 7	M12 x 1,5		8,5	6,3	11,5	4,5	1.296.0701.11
PG 9	M16 x 1,5	NPT 3/8"	11	7,8	13,5	5,5	1.296.0901.11
PG 11	M16 x 1,5		13,5	9,8	14,5	5,5	1.296.1101.11
PG 13,5	M20 x 1,5	NPT 1/2"	16	11,8	18	8	1.296.1301.11
PG 16	M20 x 1,5	NPT 1/2" / 16	18,5	13,8	19	9	1.296.1601.11
PG 21	M25 x 1,5	NPT 3/4"	22	17,8	22	11	1.296.2101.11
PG 29	M32 x 1,5	NPT 1" / NPT 1 1/4"	29	25	25	10	1.296.2901.11
PG 36	M40 x 1,5	NPT 1 1/2"	38	32	28	11	1.296.3601.11
PG 42	M50 x 1,5		43	38	30	12	1.296.4201.11
PG 48	M63 x 1,5		49	44	30	12	1.296.4801.11



to the assembly
instruction



Plug HSK-V-Ex (MZ version)



Material	Elastomer
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-40°C to +95°C
Colour	black
RAL	9005

RoHS


// This closure fits on all HSK screw fittings with additional strain relief (double bracket)

Suitable for AG	Suitable for AG2	Suitable for AG3	D mm	d mm	H mm	h mm	Item-No
PG 7	M12 x 1,5		8,5	6,3	18	4,5	1.296.0701.61
PG 9	M16 x 1,5	NPT 3/8"	11	7,8	20,5	5,5	1.296.0901.61
PG 11	M16 x 1,5		13,5	9,8	22	5,5	1.296.1101.61
PG 13,5	M20 x 1,5	NPT 1/2"	16	11,8	26,5	8	1.296.1301.61
PG 16	M20 x 1,5	NPT 1/2" / 16	18,5	13,8	28,8	9	1.296.1601.61
PG 21	M25 x 1,5	NPT 3/4"	22	17,8	32	11	1.296.2101.61
PG 29	M32 x 1,5	NPT 1" / NPT 1 1/4"	29	25	35,5	10	1.296.2901.61
PG 36	M40 x 1,5	NPT 1 1/2"	38	32	39	11	1.296.3601.61



to the assembly
instruction





Material	Nickel-plated brass
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIC Da / II 2G Ex e IIC Gb
Temperature range	-20°C to +95°C

RoHS


AG	GL mm	H mm	SW mm	Item-No
M12 x 1,5	6,5	9,5	14	1.197.1200.50
M16 x 1,5	6	9	19	1.197.1600.50
M20 x 1,5	6	9,5	22	1.197.2000.50
M25 x 1,5	7	10,5	30	1.197.2500.50
M32 x 1,5	8	12,5	41	1.197.3200.50
M40 x 1,5	8	13	46	1.197.4000.50
M50 x 1,5	9	15	55	1.197.5000.50
M63 x 1,5	10	16,5	70	1.197.6300.50
PG 7	5	8	14	1.197.0700.01
PG 9	6	9	17	1.197.0900.01
PG 11	6	9,5	20	1.197.1100.01
PG 13,5	6,5	10	22	1.197.1300.01
PG 16	6,5	10	24	1.197.1600.01
PG 21	7	10,5	30	1.197.2100.01
PG 29	8	12,5	41	1.197.2900.01
PG 36	8	13	50	1.197.3600.01
PG 42	9	15	58	1.197.4200.01
PG 48	10	16,5	65	1.197.4800.01



to the assembly
instruction



Plug V-Ms-FKM-Ex (metric)



Material	Nickel-plated brass
Material o-ring	VMQ (silicone) / FKM
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-20°C to +180°C / -60°C to +180°C


RoHS

AG	GL mm	H mm	SW mm	Item-No -20°C to +180°C FKM	Item-No -60°C to +180°C VMQ (silicone)
M12 x 1,5	6,5	9,5	14	1.198.1200.50	1.199.1200.50
M16 x 1,5	6	9	19	1.198.1600.50	1.199.1600.50
M20 x 1,5	6	9,5	22	1.198.2000.50	1.199.2000.50
M25 x 1,5	7	10,5	30	1.198.2500.50	1.199.2500.50
M32 x 1,5	8	12,5	41	1.198.3200.50	1.199.3200.50
M40 x 1,5	8	13	46	1.198.4000.50	1.199.4000.50
M50 x 1,5	9	15	55	1.198.5000.50	1.199.5000.50
M63 x 1,5	10	16,5	70	1.198.6300.50	1.199.6300.50



to the assembly
instruction





Material	Nickel-plated brass
Material o-ring	VMQ (silicone) / FKM / NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db eb IIC Gb
Temperature range	-20°C to +95°C / -60°C to +180°C / -20°C to +180°C

RoHS


AG	GL mm	H mm	SW mm	Item-No NBR -20°C to +95°C	Item-No FKM -20°C to +180°C	Item-No VMQ (silicone) -60°C to +180°C
M12 x 1,5	16	21	14	1.875.1200.50	1.876.1200.50	1.877.1200.50
M16 x 1,5	16	20	19	1.875.1600.50	1.876.1600.50	1.877.1600.50
M20 x 1,5	16	19,5	22	1.875.2000.50	1.876.2000.50	1.877.2000.50
M25 x 1,5	16	19,5	30	1.875.2500.50	1.876.2500.50	1.877.2500.50
M32 x 1,5	16	20,5	41	1.875.3200.50	1.876.3200.50	1.877.3200.50
M40 x 1,5	16	21	46	1.875.4000.50	1.876.4000.50	1.877.4000.50
M50 x 1,5	16	22	55	1.875.5000.50	1.876.5000.50	1.877.5000.50
M63 x 1,5	16	22,5	70	1.875.6300.50	1.876.6300.50	1.877.6300.50



to the assembly
instruction



Plug V-Ms-Ex d (NPT)



Material	Nickel-plated brass
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db eb IIC Gb

RoHS


AG	GL mm	H mm	SW mm	Item-No
NPT 3/8"	16	20	16	1.877.3800.70
NPT 1/2"	20	23,5	24	1.877.1200.70
NPT 3/4"	20,5	24	30	1.877.3400.70
NPT 1"	25	29,5	41	1.877.1000.70
NPT 1 1/4"	26	31	46	1.877.5400.70
NPT 1 1/2"	26,5	32,5	55	1.877.6400.70



to the assembly
instruction



Plug V-INOX-Ex (metric)



Material	INOX 1.4305
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-20°C to +95°C

RoHS


AG	GL mm	H mm	SW mm	Item-No
M12 x 1,5	6,5	9,5	14	1.192.1200.50
M16 x 1,5	6	9	19	1.192.1600.50
M20 x 1,5	6	9,5	22	1.192.2000.50
M25 x 1,5	7	10,5	30	1.192.2500.50
M32 x 1,5	8	12,5	41	1.192.3200.50
M40 x 1,5	8	13	46	1.192.4000.50
M50 x 1,5	9	15	55	1.192.5000.50
M63 x 1,5	10	16,5	70	1.192.6300.50



to the assembly
instruction



Plug V-INOX-Ex d (metric)



Material	INOX 1.4404
Material o-ring	VMQ (silicone) / NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db eb IIC Gb
Temperature range	-20°C to +95°C / -60°C to +180°C

RoHS


AG	GL mm	H mm	SW mm	Item-No	Item-No
				-20°C to +95°C	-60°C to +180°C VMQ (silicone)
M12 x 1,5	16	19	14		1.897.1200.50
M16 x 1,5	16	19	19	1.895.1600.50	1.897.1600.50
M20 x 1,5	16	19,5	22	1.895.2000.50	1.897.2000.50
M25 x 1,5	16	19,5	30	1.895.2500.50	1.897.2500.50
M32 x 1,5	16	20,5	41	1.895.3200.50	1.897.3200.50
M40 x 1,5	16	21	46	1.895.4000.50	1.897.4000.50
M50 x 1,5	16	22	55		1.897.5000.50
M63 x 1,5	16	22,5	70		1.897.6300.50



to the assembly
instruction



Plug V-INOX-Ex d (NPT)



Material	INOX 1.4404
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db eb IIC Gb

RoHS


AG	GL mm	H mm	SW mm	Item-No
NPT 3/8"	16	20	16	1.897.3800.70
NPT 1/2"	20	23,5	24	1.897.1200.70
NPT 3/4"	20,5	24	30	1.897.3400.70



to the assembly
instruction



Adapter RSD-MS-Ex (metric, PG)



Material	Nickel-plated brass
Material o-ring	NBR
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Temperature range	-20°C to +95°C

RoHS


AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	6	8,5	18	1.078.1612.50
M20 x 1,5	M12 x 1,5	6	9	22	1.078.2012.50
M20 x 1,5	M16 x 1,5	6	9	22	1.078.2016.50
M25 x 1,5	M16 x 1,5	7	10	29	1.078.2516.50
M25 x 1,5	M20 x 1,5	7	10	29	1.078.2520.50
M32 x 1,5	M16 x 1,5	8	11	34	1.078.3216.50
M32 x 1,5	M20 x 1,5	8	11,5	35	1.078.3220.50
M32 x 1,5	M25 x 1,5	8	11	34	1.078.3225.50
M40 x 1,5	M20 x 1,5	8	12	43	1.078.4020.50
M40 x 1,5	M25 x 1,5	9	13,5	43	1.078.4025.50
M40 x 1,5	M32 x 1,5	9	13,5	43	1.078.4032.50
M50 x 1,5	M25 x 1,5	9	13	55	1.078.5025.50
M50 x 1,5	M32 x 1,5	10	14	54	1.078.5032.50
M50 x 1,5	M40 x 1,5	9	13	55	1.078.5040.50
M63 x 1,5	M32 x 1,5	10	14	65	1.078.6332.50
M63 x 1,5	M40 x 1,5	10	14	65	1.078.6340.50
M63 x 1,5	M50 x 1,5	10	14	68	1.078.6350.50
PG 9	PG 7	6	8,8	17	1.078.0907.01
PG 11	PG 9	6	9	20	1.078.1109.01
PG 16	PG 9	6,5	9,5	24	1.078.1609.01
PG 16	PG 11	6,5	9,5	24	1.078.1611.01
PG 16	PG 13,5	6,5	9,5	24	1.078.1613.01
PG 21	PG 13,5	7	10,3	30	1.078.2113.01
PG 21	PG 16	7	10,3	30	1.078.2116.01
PG 29	PG 21	8	11,5	40	1.078.2921.01
PG 36	PG 29	9	12,5	50	1.078.3629.01



to the assembly
instruction



Adapter RSD-MS-VMQ-Ex (metric, PG)



Material	Nickel-plated brass
Material o-ring	VMQ (silicone)
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Temperature range	-60°C to +180°C

RoHS


AG	IG	GL mm	H mm	SW mm	Item-No
M20 x 1,5	M16 x 1,5	6	9	22	1.079.2016.50
M25 x 1,5	M16 x 1,5	7	10	29	1.079.2516.50
M25 x 1,5	M20 x 1,5	7	10	29	1.079.2520.50
M32 x 1,5	M20 x 1,5	8	11	34	1.079.3220.50
M32 x 1,5	M25 x 1,5	8	11	34	1.079.3225.50
M40 x 1,5	M32 x 1,5	9	13,5	43	1.079.4032.50
M50 x 1,5	M40 x 1,5	9	13	55	1.079.5040.50
M63 x 1,5	M50 x 1,5	10	14	68	1.079.6350.50



to the assembly
instruction



Adapter RSD-MS-Ex d (metric)



Material	Nickel-plated brass
Material o-ring	VMQ (silicone) / NBR
Protection class	IP 68 – 10 bar / IP 69 K
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db eb IIC Gb
Temperature range	-20°C to +95°C / -60°C to +180°C

RoHS


AG	IG	GL mm	H mm	SW mm	Item-No -20°C to +95°C NBR	Item-No -60°C to +180°C VMQ (silicone)
M16 x 1,5	M12 x 1,5	16	19	19	1.878.1612.50	1.879.1612.50
M20 x 1,5	M16 x 1,5	16	19,5	22	1.878.2016.50	1.879.2016.50
M25 x 1,5	M16 x 1,5	16	19,5	30	1.878.2516.50	1.879.2516.50
M25 x 1,5	M20 x 1,5	16	19,5	30	1.878.2520.50	1.879.2520.50
M32 x 1,5	M16 x 1,5	16	20,5	41	1.878.3216.50	1.879.3216.50
M32 x 1,5	M20 x 1,5	16	20,5	41	1.878.3220.50	1.879.3220.50
M32 x 1,5	M25 x 1,5	16	20,5	41	1.878.3225.50	1.879.3225.50
M40 x 1,5	M20 x 1,5	16	21	46	1.878.4020.50	1.879.4020.50
M40 x 1,5	M25 x 1,5	16	21	46	1.878.4025.50	1.879.4025.50
M40 x 1,5	M32 x 1,5	16	21	46	1.878.4032.50	1.879.4032.50
M50 x 1,5	M32 x 1,5	16	21	55	1.878.5032.50	1.879.5032.50



to the assembly
instruction



Reducer RSD-INOX-Ex (metric)



Material	INOX 1.4305
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperature range	-20°C to +95°C

RoHS


AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	5	15	19	1.098.1612.50
M20 x 1,5	M12 x 1,5	6	15,5	22	1.098.2012.50
M20 x 1,5	M16 x 1,5	6	15,5	22	1.098.2016.50
M25 x 1,5	M20 x 1,5	7	15,5	30	1.098.2520.50
M32 x 1,5	M25 x 1,5	8	12,5	41	1.098.3225.50
M40 x 1,5	M32 x 1,5	8	17	46	1.098.4032.50
M50 x 1,5	M40 x 1,5	9	13,5	55	1.098.5040.50
M63 x 1,5	M50 x 1,5	10	16,5	65	1.098.6350.50



to the assembly
instruction



Adapter RSD-INOX-Ex d (metric)



Material	INOX 1.4404
Material o-ring	NBR
Protection class	IP 69 K / IP68 - 10bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / II 2G Ex db eb IIC Gb
Temperature range	-20°C to +95°C

RoHS

AG	IG	GL mm	H mm	SW mm	Item-No
M16 x 1,5	M12 x 1,5	16	19	19	1.898.1612.50
M20 x 1,5	M12 x 1,5	16	19,5	22	1.898.2012.50
M20 x 1,5	M16 x 1,5	16	19,5	22	1.898.2016.50
M25 x 1,5	M20 x 1,5	16	19,5	30	1.898.2520.50
M32 x 1,5	M20 x 1,5	16	20,5	41	1.898.3220.50
M32 x 1,5	M25 x 1,5	16	20,5	41	1.898.3225.50
M40 x 1,5	M32 x 1,5	16	21	46	1.898.4032.50




to the assembly
instruction



EXIOS CABLE GLANDS FOR „HAZARDOUS AREAS“


Cable glands for all popular threads, used in electrical equipment and hazardous areas in Group I, II and III applications. The Ex d, Ex e and / or Ex t certified cable glands have been designed for all explosion proof areas which are in need of high standards, reliability, strain relief and water proof requirements, e.g. marine, offshore, gas conveying machinery, refineries and chemical industry.

- // EXIOS MZ: high-end cable gland with extra strain relief and zero torsion or armour and wires. For armoured cables in hazardous areas including the latest IECEx and ATEX certifications, for the use in Ex e, Ex d and Ex t areas
- // EXIOS BARRIER: high-end cable gland for armoured cables in hazardous areas uses a barrier compound sealing including the latest IECEx and ATEX certifications, for the use in Ex e, Ex d and Ex t areas
- // EXIOS A2F: or non-armoured cables for the use in Ex e, Ex d and Ex t areas



EXIOS cable glands for "Hazardous Areas"

EXIOS Standard brass (metric, NPT)



Material	Brass
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Armour	Metallic armour or screen
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / Class I Div 2 Groups A,B,C,D / II 2G Ex db eb IIC Gb / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +105°C

RoHS

AG	Size	D mm	A1 mm	A2 mm	H mm	GL mm	SW1/SW2 mm	⌀ Nm	K1 mm	K2 mm	K3 mm	Item-No
M16 x 1,5	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.1600.50
M20 x 1,5	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.2000.50
M20 x 1,5	20-2	29	9 - 16	6 - 12	74,3	16	24/24	8	0 - 0,7	0,7 - 1,25		1.605.2000.51
M20 x 1,5	20-3	35	12,5 - 20,5	9 - 14	80,5	16	30/30	12	0 - 0,7	0,7 - 1,4		1.605.2000.52
M25 x 1,5	20-3	35	12,5 - 20,5	9 - 14	80,5	16	30/30	12	0 - 0,7	0,7 - 1,4		1.605.2500.51
M25 x 1,5	25	42	16,9 - 26	12,5 - 20,5	91	16	36/36	18	0 - 0,7	0,9 - 1,6	0,7 - 1,4	1.605.2500.50
M32 x 1,5	32	52	22 - 33	16,9 - 26	96	16	46/46	30	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.3200.50
M40 x 1,5	40	64	28 - 41	22 - 33	107	16	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.4000.50
M50 x 1,5	50	73	36 - 52,6	28,9 - 44,4	131,5	16	65/65	60	0 - 1	1,5 - 2,5	1 - 2	1.605.5000.50
M63 x 1,5	63	90	46 - 65,3	39,9 - 56,3	144,5	16	80/80	65	0 - 1	1,5 - 2,5	1 - 2	1.605.6300.50
M75 x 1,5	75	107	57 - 78	50,5 - 68,2	154	16	95/95	135	0 - 1	1,5 - 2,5	1 - 2	1.605.7500.50
NPT 3/8"	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.3800.70
NPT 1/2"	20-2	29	9 - 16	6 - 12	74,3	20	24/24	8	0 - 0,7	0,7 - 1,25		1.605.1200.70
NPT 1/2"	20-3	35	12,5 - 20,5	9 - 14	80,5	20	30/30	12	0 - 0,7	0,7 - 1,4		1.605.1200.71
NPT 3/4"	25	42	16,9 - 26	12,5 - 20,5	91	20,5	36/36	18	0 - 0,7	0,9 - 1,6	0,7 - 1,4	1.605.3400.70
NPT 1"	32	52	22 - 33	16,9 - 26	96	25	46/46	30	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.1000.70
NPT 1 1/4"	40	64	28 - 41	22 - 33	107	26	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.5400.70
NPT 1 1/2"	40	64	28 - 41	22 - 33	107	26,5	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.6400.70
NPT 2"	50	73	36 - 52,6	28,9 - 44,4	131,5	27	65/65	60	0 - 1	1,5 - 2,5	1 - 2	1.605.2000.70
NPT 2 1/2"	63	90	46 - 65,3	39,9 - 56,3	144,5	40	80/80	65	0 - 1	1,5 - 2,5	1 - 2	1.605.5200.70
NPT 3"	75	107	57 - 78	50,5 - 68,2	154	41,5	95/95	135	0 - 1	1,5 - 2,5	1 - 2	1.605.3000.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS Standard nickel-plated brass (metric, NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Armour	Metallic armour or screen
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / Class I Div 2 Groups A,B,C,D / II 2G Ex db eb IIC Gb / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +105°C

RoHS

AG	Size	D mm	A1 mm	A2 mm	H mm	GL mm	SW1/SW2 mm	⌀ Nm	K1 mm	K2 mm	K3 mm	Item-No
M16 x 1,5	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.1603.50
M20 x 1,5	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.2003.50
M20 x 1,5	20-2	29	9 - 16	6 - 12	74,3	16	24/24	8	0 - 0,7	0,7 - 1,25		1.605.2003.51
M20 x 1,5	20-3	35	12,5 - 20,5	9 - 14	80,5	16	30/30	12	0 - 0,7	0,9 - 1,6	0,7 - 1,4	1.605.2003.52
M25 x 1,5	20-3	35	12,5 - 20,5	9 - 14	80,5	16	30/30	12	0 - 0,7	0,9 - 1,6	0,7 - 1,4	1.605.2503.51
M25 x 1,5	25	42	16,9 - 26	12,5 - 20,5	91	16	36/36	18	0 - 1	1,5 - 2,5	1 - 2	1.605.2503.50
M32 x 1,5	32	52	22 - 33	16,9 - 26	96	16	46/46	30	0 - 1	1,5 - 2,5	1 - 2	1.605.3203.50
M40 x 1,5	40	64	28 - 41	22 - 33	107	16	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.4003.50
M50 x 1,5	50	73	36 - 52,6	28,9 - 44,4	131,5	16	65/65	60	0 - 1	1,5 - 2,5	1 - 2	1.605.5003.50
M63 x 1,5	63	90	46 - 65,3	39,9 - 56,3	144,5	16	80/80	65	0 - 1	1,5 - 2,5	1 - 2	1.605.6303.50
M75 x 1,5	75	107	57 - 78	50,5 - 68,2	154	16	95/95	135	0 - 1	1,5 - 2,5	1 - 2	1.605.7503.50
NPT 3/8"	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.3803.70
NPT 1/2"	20-2	29	9 - 16	6 - 12	74,3	20	24/24	8	0 - 0,7	0,7 - 1,25		1.605.1203.70
NPT 1/2"	20-3	35	12,5 - 20,5	9 - 14	80,5	20	30/30	12	0 - 0,7	0,7 - 1,4		1.605.1203.71
NPT 3/4"	25	42	16,9 - 26	12,5 - 20,5	91	20,5	36/36	18	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.3403.70
NPT 1"	32	52	22 - 33	16,9 - 26	96	25	46/46	30	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.1003.70
NPT 1 1/4"	40	64	28 - 41	22 - 33	107	26	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.5403.70
NPT 1 1/2"	40	64	28 - 41	22 - 33	107	26,5	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.6403.70
NPT 2"	50	73	36 - 52,6	28,9 - 44,4	131,5	27	65/65	60	0 - 0,7	0,7 - 1,4		1.605.2003.70
NPT 2 1/2"	63	90	46 - 65,3	39,9 - 56,3	144,5	40	80/80	65	0 - 1	1,5 - 2,5	1 - 2	1.605.5203.70
NPT 3"	75	107	57 - 78	50,5 - 68,2	154	41,5	95/95	135	0 - 0,7	0,7 - 1,4		1.605.3003.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS Standard INOX (metric, NPT)



Material	INOX 1.4404
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Armour	Metallic armour or screen
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / Class I Div 2 Groups A,B,C,D / II 2G Ex db eb IIC Gb / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +105°C

RoHS

AG	Size	D mm	A1 mm	A2 mm	H mm	GL mm	SW1/SW2 mm	⌀ Nm	K1 mm	K2 mm	K3 mm	Item-No
M16 x 1,5	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.1602.50
M20 x 1,5	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.2002.50
M20 x 1,5	20-2	29	9 - 16	6 - 12	74,3	16	24/24	8	0 - 0,7	0,7 - 1,25		1.605.2002.51
M20 x 1,5	20-3	35	12,5 - 20,5	9 - 14	80,5	16	30/30	12	0 - 0,7	0,9 - 1,6	0,7 - 1,4	1.605.2002.52
M25 x 1,5	20-3	35	12,5 - 20,5	9 - 14	80,5	16	30/30	12	0 - 0,7	0,9 - 1,6	0,7 - 1,4	1.605.2502.51
M25 x 1,5	25	42	16,9 - 26	12,5 - 20,5	91	16	36/36	18	0 - 1	1,5 - 2,5	1 - 2	1.605.2502.50
M32 x 1,5	32	52	22 - 33	16,9 - 26	96	16	46/46	30	0 - 1	1,5 - 2,5	1 - 2	1.605.3202.50
M40 x 1,5	40	64	28 - 41	22 - 33	107	16	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.4002.50
M50 x 1,5	50	73	36 - 52,6	28,9 - 44,4	131,5	16	65/65	60	0 - 1	1,5 - 2,5	1 - 2	1.605.5002.50
M63 x 1,5	63	90	46 - 65,3	39,9 - 56,3	144,5	16	80/80	65	0 - 1	1,5 - 2,5	1 - 2	1.605.6302.50
M75 x 1,5	75	107	57 - 78	50,5 - 68,2	154	16	95/95	135	0 - 1	1,5 - 2,5	1 - 2	1.605.7502.50
NPT 3/8"	20-1	27	6 - 12	3 - 8,1	69,5	16	22/22	8	0 - 0,7	0,7 - 1,25		1.605.3802.70
NPT 1/2"	20-2	29	9 - 16	6 - 12	74,3	20	24/24	8	0 - 0,7	0,7 - 1,25		1.605.1202.70
NPT 1/2"	20-3	35	12,5 - 20,5	9 - 14	80,5	20	30/30	12	0 - 0,7	0,7 - 1,4		1.605.1202.71
NPT 3/4"	25	42	16,9 - 26	12,5 - 20,5	91	20,5	36/36	18	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.3402.70
NPT 1"	32	52	22 - 33	16,9 - 26	96	25	46/46	30	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.1002.70
NPT 1 1/4"	40	64	28 - 41	22 - 33	107	26	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.5402.70
NPT 1 1/2"	40	64	28 - 41	22 - 33	107	26,5	55/55	50	0 - 0,7	1,3 - 2	0,7 - 1,4	1.605.6402.70
NPT 2"	50	73	36 - 52,6	28,9 - 44,4	131,5	27	65/65	60	0 - 0,7	0,7 - 1,4		1.605.2002.70
NPT 2 1/2"	63	90	46 - 65,3	39,9 - 56,3	144,5	40	80/80	65	0 - 1	1,5 - 2,5	1 - 2	1.605.5202.70
NPT 3"	75	107	57 - 78	50,5 - 68,2	154	41,5	95/95	135	0 - 0,7	0,7 - 1,4		1.605.3002.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS MZ nickel plated brass (metric)



Material	Nickel-plated brass
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Armour	Metallic armour or screen
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	II 1D Ex ta IIIC Da / Class I Div 2 Groups A,B,C,D / II 2G Ex db eb IIC Gb / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +105°C

RoHS

// brass blank on request

// NPT connection thread on request

AG	Size	D mm	A1 mm	A2 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	K1 mm	K2 mm	K3 mm	Item-No
M16 x 1,5	20-1	27	6 – 11	3 – 8,1	16	79	22/22	8	0 – 0,7	0,7 – 1,25		1.675.1603.50
M20 x 1,5	20-1	27	6 – 11	3 – 8,1	16	79	22/22	8	0 – 0,7	0,7 – 1,25		1.675.2003.50
M20 x 1,5	20-2	29	9 – 13	9 – 12	16	83,8	24/24	8	0 – 0,7	0,7 – 1,25		1.675.2003.51
M20 x 1,5	20-3	35	12,5 – 17,5	9 – 14	16	91,5	30/30	12	0 – 0,7	0,7 – 1,4		1.675.2003.52
M25 x 1,5	20-3	35	12,5 – 17,5	9 – 14	16	91,5	30/30	12	0 – 0,7	0,7 – 1,4		1.675.2503.51
M25 x 1,5	25	42	16,9 – 24	12,5 – 20,5	16	105,7	36/36	18	0 – 0,7	0,9 – 1,6	0,7 – 1,4	1.675.2503.50
M32 x 1,5	32	52	22 – 32,5	16,9 – 26	16	107	46/46	30	0 – 0,7	1,3 – 2	0,7 – 1,4	1.675.3203.50
M40 x 1,5	40	64	28 – 39,5	22 – 33	16	120	55/55	50	0 – 0,7	1,3 – 2	0,7 – 1,4	1.675.4003.50
M50 x 1,5	50	73	36 – 49	28,9 – 44,4	16	144,5	65/65	60	0 – 1	1,5 – 2,5	1 – 2	1.675.5003.50
M63 x 1,5	63	90	46 – 64	39,9 – 56,3	16	157,5	80/80	65	0 – 1	1,5 – 2,5	1 – 2	1.675.6303.50
M75 x 1,5	75	107	57 – 78	50,5 – 68,2	16	167	95/95	135	0 – 1	1,5 – 2,5	1 – 2	1.675.7503.50




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS Barrier brass (metric, NPT)



Material	Brass
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Armour	Metallic armour or screen
Compound	Two-component epoxy compound
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	Class I Div 2 Groups A,B,C,D / I M2 Ex de / I Mb IIC Gb / I M2 Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +85°C

RoHS

AG	Size	D mm	A1 mm	max. A2 mm	max. A3 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	max. No. cores	K1 mm	K2 mm	Item-No
NPT 3/8"	20-1	27	6 – 12	8,2	7,9	16	64	22/22	8	8	0 – 0,7	0,7 – 1,25	1.606.3800.70
NPT 1/2"	20-2	29	9 – 16	12	8,8	20	68	24/24	12	10	0 – 0,7	0,7 – 1,25	1.606.1200.70
NPT 1/2"	20-3	35	12,5 – 20,5	14	11,5	20	73	30/30	12	15	0 – 0,7	0,7 – 1,4	1.606.1200.71
NPT 3/4"	25	42	16,9 – 26	20	16,4	20,5	81,3	36/36	18	25	0 – 0,7	0,9 – 1,6	1.606.3400.70
NPT 1"	32	52	22 – 32,5	26	21,4	25	85,5	46/46	30	45	0 – 0,7	1,3 – 2	1.606.1000.70
NPT 1 1/4"	40	64	28 – 41	33,2	27,6	26	94,4	55/55	50	70	0 – 0,7	1,3 – 2	1.606.5400.70
NPT 1 1/2"	40	64	28 – 41	33,2	27,6	26,5	94,4	55/55	50	70	0 – 0,7	1,3 – 2	1.606.6400.70
NPT 2"	50	73	36 – 52,6	44,2	37,5	27	116,3	65/65	60	85	0 – 1	1,5 – 2,5	1.606.2000.70
NPT 2 1/2"	63	90	46 – 65,3	56,2	47,3	40	127,6	80/80	65	120	0 – 1	1,5 – 2,5	1.606.5200.70
NPT 3"	75	107	57 – 78	68,2	58,0	41,5	136,5	95/95	135	150	0 – 1	1,5 – 2,5	1.606.3000.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS Barrier nickel-plated brass (metric, NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Armour	Metallic armour or screen
Compound	Two-component epoxy compound
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	Class I Div 2 Groups A,B,C,D / I M2 Ex de / I Mb IIC Gb / I M2 Ex ta IIC Da / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +85°C

RoHS

AG	Size	D mm	A1 mm	max. A2 mm	max. A3 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	max. No. cores	K1 mm	K2 mm	Item-No
M16 x 1,5	20-1	27	6 – 12	8,2	7,9	16	64	22/22	8	8	0 – 0,7	0,7 – 1,25	1.606.1603.50
M20 x 1,5	20-1	27	6 – 12	8,2	7,9	16	64	22/22	8	8	0 – 0,7	0,7 – 1,25	1.606.2003.50
M20 x 1,5	20-2	29	9 – 16	12	8,8	16	68	24/24	12	10	0 – 0,7	0,7 – 1,25	1.606.2003.51
M20 x 1,5	20-3	35	12,5 – 20,5	14	11,5	16	73	30/30	12	15	0 – 0,7	0,7 – 1,4	1.606.2003.52
M25 x 1,5	20-3	35	12,5 – 20,5	14	11,5	16	73	30/30	12	15	0 – 0,7	0,7 – 1,4	1.606.2503.51
M25 x 1,5	25	42	16,9 – 26	20	16,4	16	81,3	36/36	18	25	0 – 0,7	0,9 – 1,6	1.606.2503.50
M32 x 1,5	32	52	22 – 33	26	21,4	16	85,5	46/46	30	45	0 – 0,7	1,3 – 2	1.606.3203.50
M40 x 1,5	40	64	28 – 41	33,2	27,6	16	94,4	55/55	50	70	0 – 0,7	1,3 – 2	1.606.4003.50
M50 x 1,5	50	73	36 – 52,6	44,2	37,5	16	116,3	65/65	60	85	0 – 1	1,5 – 2,5	1.606.5003.50
M63 x 1,5	63	90	46 – 65,3	56,2	47,3	16	127,6	80/80	65	120	0 – 1	1,5 – 2,5	1.606.6303.50
M75 x 1,5	75	107	57 – 78	68,2	58,0	16	136,5	95/95	135	150	0 – 1	1,5 – 2,5	1.606.7503.50
NPT 3/8"	20-1	27	6 – 12	8,2	7,9	16	64	22/22	8	8	0 – 0,7	0,7 – 1,25	1.606.3803.70
NPT 1/2"	20-2	29	9 – 16	12	8,8	20	68	24/24	12	10	0 – 0,7	0,7 – 1,25	1.606.1203.70
NPT 1/2"	20-3	35	12,5 – 20,5	14	11,5	20	73	30/30	12	15	0 – 0,7	0,7 – 1,4	1.606.1203.71
NPT 3/4"	25	42	16,9 – 26	20	16,4	20,5	81,3	36/36	18	25	0 – 0,7	0,9 – 1,6	1.606.3403.70
NPT 1"	32	52	22 – 32,5	26	21,4	25	85,5	46/46	30	45	0 – 0,7	1,3 – 2	1.606.1003.70
NPT 1 1/4"	40	64	28 – 41	33,2	27,6	26	94,4	55/55	50	70	0 – 0,7	1,3 – 2	1.606.5403.70
NPT 1 1/2"	40	64	28 – 41	33,2	27,6	26,5	94,4	55/55	50	70	0 – 0,7	1,3 – 2	1.606.6403.70
NPT 2"	50	73	36 – 52,6	44,2	37,5	27	116,3	65/65	60	85	0 – 1	1,5 – 2,5	1.606.2003.70
NPT 2 1/2"	63	90	46 – 65,3	56,2	47,3	40	127,6	80/80	65	120	0 – 1	1,5 – 2,5	1.606.5203.70
NPT 3"	75	107	57 – 78	68,2	58,0	41,5	136,5	95/95	135	150	0 – 1	1,5 – 2,5	1.606.3003.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS Barrier INOX (metric, NPT)



Material	INOX 1.4404
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Armour	Metallic armour or screen
Compound	Two-component epoxy compound
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	Class I Div 2 Groups A,B,C,D / I M2 Ex de / I Mb IIC Gb / I M2 Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +85°C

RoHS

AG	Size	D mm	A1 mm	max. A2 mm	max. A3 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	max. No. cores	K1 mm	K2 mm	Item-No
M16 x 1,5	20-1	27	6 – 12	8,2	7,9	16	68,5	22/22	8	8	0 – 0,7	0,7 – 1,25	1.606.1602.50
M20 x 1,5	20-1	27	6 – 12	8,2	7,9	16	68,5	22/22	8	8	0 – 0,7	0,7 – 1,25	1.606.2002.50
M20 x 1,5	20-2	29	9 – 16	12	8,8	16	74,3	24/24	12	10	0 – 0,7	0,7 – 1,25	1.606.2002.51
M20 x 1,5	20-3	35	12,5 – 20,5	14	11,5	16	80,5	30/30	12	15	0 – 0,7	0,7 – 1,4	1.606.2002.52
M25 x 1,5	20-3	35	12,5 – 20,5	14	11,5	16	80,5	30/30	12	15	0 – 0,7	0,7 – 1,4	1.606.2502.51
M25 x 1,5	25	42	17 – 26	20	16,4	16	91	36/36	18	25	0 – 0,7	0,9 – 1,6	1.606.2502.50
M32 x 1,5	32	52	22 – 33	26	21,4	16	96	46/46	30	45	0 – 0,7	1,3 – 2	1.606.3202.50
M40 x 1,5	40	64	28 – 41	33,2	27,6	16	107	55/55	50	70	0 – 0,7	1,3 – 2	1.606.4002.50
M50 x 1,5	50	73	36 – 52,6	44,2	37,5	16	131,5	65/65	60	85	0 – 1	1,5 – 2,5	1.606.5002.50
M63 x 1,5	63	90	46 – 66	56,2	47,3	16	144,5	80/80	65	120	0 – 1	1,5 – 2,5	1.606.6302.50
M75 x 1,5	75	107	58 – 78	68,2	58	16	154	95/95	135	150	0 – 1	1,5 – 2,5	1.606.7502.50
NPT 3/8"	20-1	27	6 – 12	8,2	7,9	16	64	22/22	8	8	0 – 0,7	0,7 – 1,25	1.606.3802.70
NPT 1/2"	20-2	29	9 – 16	12	8,8	16	68	24/24	12	10	0 – 0,7	0,7 – 1,25	1.606.1202.70
NPT 1/2"	20-3	35	12,5 – 20,5	14	11,5	16	73	30/30	12	15	0 – 0,7	0,7 – 1,4	1.606.1202.71
NPT 3/4"	25	42	17 – 26	20	16,4	16	81,3	36/36	18	25	0 – 0,7	0,9 – 1,6	1.606.3402.70
NPT 1"	32	52	22 – 33	26	21,4	16	85,5	46/46	30	45	0 – 0,7	1,3 – 2	1.606.1002.70
NPT 1 1/4"	40	64	28 – 41	33,2	27,6	16	94,4	55/55	50	70	0 – 0,7	1,3 – 2	1.606.5402.70
NPT 1 1/2"	40	64	28 – 41	33,2	27,6	16	94,4	55/55	50	70	0 – 0,7	1,3 – 2	1.606.6402.70
NPT 2"	50	73	36 – 52,6	44,2	37,5	16	116,3	65/65	60	85	0 – 1	1,5 – 2,5	1.606.2002.70
NPT 2 1/2"	63	90	46 – 66	56,2	47,3	16	127,6	80/80	65	120	0 – 1	1,5 – 2,5	1.606.5202.70
NPT 3"	75	107	58 – 78	68,2	58	16	136,5	95/95	135	150	0 – 1	1,5 – 2,5	1.606.3002.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS A2F brass (metric, NPT)



Material	Brass
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	Class I Div 2 Groups A,B,C,D / II 2G Ex db eb IIC Gb / II 1D Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +105°C

RoHS

AG	Size	D mm	A1 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
M16 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.1600.50
M20 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.2000.50
M20 x 1,5	20-2	29	9 – 16	16	39,7	24/24	8	1.608.2000.51
M25 x 1,5	20-3	35	12,5 – 20,5	16	47,5	30/30	12	1.608.2500.50
M32 x 1,5	25	42	16,9 – 26	16	47,8	36/36	18	1.608.3200.50
M40 x 1,5	32	52	22 – 33	16	51,1	46/46	30	1.608.4000.50
M50 x 1,5	40	64	28 – 41	16	56,8	55/55	50	1.608.5000.50
M63 x 1,5	50	73	40 – 52,6	16	65,4	65/65	60	1.608.6300.50
M75 x 1,5	63	90	51 – 65,3	16	70,3	80/80	65	1.608.7500.50
M90 x 2,0	75	107	62 – 78	20	76,2	95/95	135	1.608.9000.50
NPT 3/8"	20-1	27	6 – 12	16	35,6	22/22	8	1.608.3800.70
NPT 1/2"	20-1	29	6 – 12	20	39,7	24/24	8	1.608.1200.70
NPT 1/2"	20-2	27	9 – 16	20	35,6	22/24	8	1.608.1200.71
NPT 3/4"	20-3	35	12,5 – 20,5	20,5	47,5	30/30	12	1.608.3400.70
NPT 1"	25	42	16,9 – 26	25	47,8	36/36	18	1.608.1000.70
NPT 1 1/4"	32	52	22 – 33	26	51,1	46/46	30	1.608.5400.70
NPT 1 1/2"	40	64	28 – 41	26,5	56,8	55/55	50	1.608.6400.70
NPT 2"	50	73	40 – 52,6	27	65,4	65/65	60	1.608.2000.70
NPT 2 1/2"	63	90	51 – 61	40	70,3	80/80	65	1.608.5200.70
NPT 3"	75	107	62 – 78	41,5	76,2	95/95	135	1.608.3000.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS A2F nickel-plated brass (metric, NPT)



Material	Nickel-plated brass
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	Class I Div 2 Groups A,B,C,D / II 2G Ex db eb IIC Gb / II 1D Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +105°C

RoHS

AG	Size	D mm	A1 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
M16 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.1603.50
M20 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.2003.50
M20 x 1,5	20-2	29	9 – 16	16	39,7	24/24	8	1.608.2003.51
M25 x 1,5	20-3	35	12,5 – 20,5	16	47,5	30/30	12	1.608.2503.50
M32 x 1,5	25	42	16,9 – 26	16	47,8	36/36	18	1.608.3203.50
M40 x 1,5	32	52	22 – 33	16	51,1	46/46	30	1.608.4003.50
M50 x 1,5	40	64	28 – 41	16	56,8	55/55	50	1.608.5003.50
M63 x 1,5	50	73	40 – 52,6	16	65,4	65/65	60	1.608.6303.50
M75 x 1,5	63	90	51 – 65,3	16	70,3	80/80	65	1.608.7503.50
M90 x 2,0	75	107	62 – 78	20	76,2	95/95	135	1.608.9003.50
NPT 1/2"	20-1	29	6 – 12	20	39,7	24/24	8	1.608.1203.70
NPT 1/2"	20-2	27	9 – 16	20	35,6	22/24	8	1.608.1203.71
NPT 3/4"	20-3	35	12,5 – 20,5	20,5	47,5	30/30	12	1.608.3403.70
NPT 1"	25	42	16,9 – 26	25	47,8	36/36	18	1.608.1003.70
NPT 1 1/4"	32	52	22 – 33	26	51,1	46/46	30	1.608.5403.70
NPT 1 1/2"	40	64	28 – 41	26,5	56,8	55/55	50	1.608.6403.70
NPT 2"	50	73	40 – 52,6	27	65,4	65/65	60	1.608.2003.70
NPT 2 1/2"	63	90	51 – 61	40	70,3	80/80	65	1.608.5203.70
NPT 3"	75	107	62 – 78	41,5	76,2	95/95	135	1.608.3003.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"

EXIOS A2F INOX (metric, NPT)



Material	INOX 1.4404
Clamping insert	Polyamide 6
Seal	VMQ (silicone)
Material o-ring	VMQ (silicone)
Protection class	IP 67 / IP 66 / IP 68 - 5bar/30min
Ex-protection level	Class I Div 2 Groups A,B,C,D / II 2G Ex db eb IIC Gb / II 1D Ex ta IIIC Da / Class II Div 1 Groups E,F,G
Temperature range	-60°C to +105°C

RoHS

AG	Size	D mm	A1 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No
M16 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.1602.50
M20 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.2002.50
M20 x 1,5	20-2	29	9 – 16	16	39,7	24/24	8	1.608.2002.51
M25 x 1,5	20-3	35	12,5 – 20,5	16	47,5	30/30	12	1.608.2502.50
M32 x 1,5	25	42	16,9 – 26	16	47,8	36/36	18	1.608.3202.50
M40 x 1,5	32	52	22 – 33	16	51,1	46/46	30	1.608.4002.50
M50 x 1,5	40	64	28 – 41	16	56,8	55/55	50	1.608.5002.50
M63 x 1,5	50	73	40 – 52,6	16	65,4	65/65	60	1.608.6302.50
M75 x 1,5	63	90	51 – 65,3	16	72	80/80	65	1.608.7502.50
M90 x 1,5	75	107	62 – 78	20	76,2	95/95	135	1.608.9002.50
NPT 3/8"	20-1	27	6 – 12	16	35,6	22/22	8	1.608.3802.70
NPT 1/2"	20-1	29	6 – 12	20	39,7	24/24	8	1.608.1202.70
NPT 1/2"	20-2	27	9 – 16	20	35,6	22/22	8	1.608.1202.71
NPT 3/4"	20-3	35	12,5 – 20,5	20,5	47,5	30/30	12	1.608.3402.70
NPT 1"	25	42	16,9 – 26	25	47,8	36/36	18	1.608.1002.70
NPT 1 1/4"	32	52	22 – 33	26	51,1	46/46	30	1.608.5402.70
NPT 1 1/2"	40	64	28 – 41	26,5	56,8	55/55	50	1.608.6402.70
NPT 2"	50	73	40 – 52,6	27	65,4	65/65	60	1.608.2002.70
NPT 2 1/2"	63	90	51 – 61	40	70,3	80/80	65	1.608.5202.70
NPT 3"	75	107	62 – 78	41,5	76,2	95/95	135	1.608.3002.70



to the product video




to the assembly
instruction



EXIOS cable glands for "Hazardous Areas"


Thread seal ring (metric, NPT)



Material	Plastic, glass fiber reinforced
Temperature range	-60°C to +105°C

RoHS

Suitable for AG	D mm	d mm	s mm	Item-No
M16 x 1,5	25	16,5	1,5	1.326.1600.50
M20 x 1,5	28,7	20,5	1,5	1.326.2000.50
M25 x 1,5	36	25,5	1,5	1.326.2500.50
M32 x 1,5	42,5	32,5	1,5	1.326.3200.50
M40 x 1,5	52	40,5	1,5	1.326.4000.50
M50 x 1,5	65	50,5	1,5	1.326.5000.50
M63 x 1,5	79,4	63,5	1,5	1.326.6300.50
M75 x 1,5	90,5	75,5	1,5	1.326.7500.50
NPT 3/8"	22,2	17,5	1,5	1.326.3800.70
NPT 1/2"	30	22	1,5	1.326.1200.70
NPT 3/4"	38	27,2	1,5	1.326.3400.70
NPT 1"	46	33,7	1,5	1.326.1000.70
NPT 1 1/4"	55,5	42,8	1,5	1.326.5400.70
NPT 1 1/2"	58,8	48,6	1,5	1.326.6400.70
NPT 2"	79,4	60,9	1,5	1.326.2000.70
NPT 2 1/2"	90,5	74	1,5	1.326.5200.70
NPT 3"	114,3	90,5	1,5	1.326.3000.70



Material

PVC

RoHS

Suitable for size	d mm	H1 mm	H2 mm	Item-No
20-1	26	115	60	1.802.2000.50
20-2	28	125	70	1.802.2000.51
20-3	34	130	65	1.802.2000.52
25	42	160	90	1.802.2500.50
32	51	165	95	1.802.3200.50
40	63	200	110	1.802.4000.50
50	72	210	115	1.802.5000.50
63	88	245	140	1.802.6300.50
75	108	245	140	1.802.7500.50


EXIOS cable glands for "Hazardous Areas"

Earthtag (metric, NPT)

Material

Brass

RoHS




Suitable for AG	D mm	d mm	s mm	H mm	Item-No
M16 x 1,5	16,2	6,7	1,5	49	1.022.1600.50
M20 x 1,5	21	7	1,5	54	1.022.2000.50
M25 x 1,5	25,5	10,5	1,5	61,5	1.022.2500.50
M32 x 1,5	32,5	12,2	1,5	73	1.022.3200.50
M40 x 1,5	40,5	13,5	1,5	86,5	1.022.4000.50
M50 x 1,5	51	13,5	1,5	112	1.022.5000.50
M63 x 1,5	64	13,5	1,5	126	1.022.6300.50
M75 x 1,5	76,2	13,5	1,5	138	1.022.7500.50
NPT 3/8"	17,5	7	1,5	53,8	1.022.3800.70
NPT 1/2"	21,5	7	1,5	53,5	1.022.1200.70
NPT 3/4"	26,7	10,5	1,5	61,5	1.022.3400.70
NPT 1"	34,5	12,2	1,5	73	1.022.1000.70
NPT 1 1/4"	43,5	13,5	1,5	86,5	1.022.5400.70
NPT 1 1/2"	51	13,5	1,5	112	1.022.6400.70
NPT 2"	61,2	13,5	1,5	126	1.022.2000.70
NPT 2 1/2"	76,2	13,5	1,5	138	1.022.5200.70

Material

Stainless steel

RoHS



Suitable for AG	D mm	d mm	s mm	Item-No
M16 x 1,5	26,5	17	1,5	1.329.1600.50
M20 x 1,5	33,5	21,5	1,5	1.329.2000.50
M25 x 1,5	39	26	1,5	1.329.2500.50
M32 x 1,5	48	30,5	1,5	1.329.3200.50
M40 x 1,5	59,5	40,5	1,5	1.329.4000.50
M50 x 1,5	71	51,5	1,5	1.329.5000.50
M63 x 1,5	87	64	1,5	1.329.6300.50
M75 x 1,5	102,5	76,5	1,5	1.329.7500.50
NPT 3/8"	30	19,5	1,5	1.329.3800.70
NPT 1/2"	39	23,5	1,5	1.329.1200.70
NPT 3/4"	42	29,5	1,5	1.329.3400.70
NPT 1"	49,5	35	1,5	1.329.1000.70
NPT 1 1/4"	59,5	44	1,5	1.329.5400.70
NPT 1 1/2"	71	51,5	1,5	1.329.6400.70
NPT 2"	86,6	61,5	1,5	1.329.2000.70
NPT 2 1/2"	102,5	76,5	1,5	1.329.5200.70

CABLE PROTECTION SYSTEMS

Reliable protection for cables: Cables and data lines in the industry are subjected to high loads. Heat and cold, tensile and pressure load as well as abrasion damage the cables and can lead to malfunctions and production losses. HUMMEL cable protecting hoses provide reliable protection against these.


The plastic series made of polyamide provide a suitable solution for every application. A large selection of fittings makes it easy for planners and designers to find the right answer for every requirement.

// Polyamide Conduit – the flexible cable conduit made of polyamide

// Polyamide Fitting – cable protection for polyamide conduit, which are able to cope with all installation situations



Polyamide conduit




Material	Polyamide
Temperature range	-40°C to +120°C
Colour	black
RAL	9005

RoHS

// Raw material according to UL94

Size DN	d mm	D mm	 mm	Item-No
10	10	13	25	1.510.0901.14
12	12	15,8	35	1.510.1101.14
14	14,2	18,4	35	1.510.1301.14
17	16,5	21,2	40	1.510.1601.14
23	23	28,4	45	1.510.2101.14
29	29	34,5	55	1.510.2901.14
37	36	42,5	65	1.510.3601.14



Material	Polyamide
Protection class	IP 55
Temperature range	-30°C to +80°C
Colour	black
RAL	9005

RoHS

- // Raw material according to UL94
- // Locknut optional
- // Easy disassembly without tools

AG	d mm	D mm	GL mm	H mm	SW mm	Suitable for polyamide hose DN	Item-No
M16	10,9	21,7	11	26	18	10	1.533.1601.51
M16	10,9	26	11	26,5	20	12	1.533.1601.50
M20	14,7	28	11	31	23	14	1.533.2001.51
M20	15,2	32	13	33	27	17	1.533.2001.50
M25	18,7	39,5	16	39	34	23	1.533.2501.50
M32	25,7	46,5	16	43	40	29	1.533.3201.50

Polyamide fitting clip




Material	Polyamide
Temperature range	-30°C to +80°C
Colour	black
RAL	9005

RoHS

// Raw material according to UL94

Size DN	d mm	D mm	H mm	H1 mm	L mm	Suitable for polyamide hose DN	Item-No
10	5	7	15,75	27,5	28,7	10	1.534.0901.00
12	5,3	8,3	13,1	24	29,8	12	1.534.1101.00
14	5,3	8,5	17,75	29,3	35,2	14	1.534.1401.00
17	5,3	8,5	19,75	33,2	40,2	17	1.534.1601.00
23	5,3	8,7	23,5	40,5	52,6	23	1.534.2101.00
29	6,5	11	27	48	60,7	29	1.534.2901.00
37	6,5	11	30,4	57	69	37	1.534.3601.00




Material	Nickel-plated brass
Clamping insert	Polyamide
Seal	NBR
Protection class	IP 68 / IP 69 K / IP68 - 10bar/30min
Temperature range	-40°C to +100°C

RoHS

- // 2 in 1 cable gland and conduit fitting
- // Easy disassembly without tools

AG	Ø* mm	D mm	GL mm	H mm	SW mm	Suitable for polyamide hose DN	Item-No
M16	5 – 10	23	6	36	20	10	1.547.1610.50
M20	5 – 9	25	6	39,5	22	12	1.547.2012.51
M20	6 – 12	25	6	39,5	22	12	1.547.2012.50
M20	7 – 12	29	6	40,5	28	14	1.547.2014.51
M20	10 – 14	29	6	40,5	28	14	1.547.2014.50
M25	9 – 16	30	7	44,5	30	17	1.547.2517.51
M25	13 – 18	30	7	44,5	30	17	1.547.2517.50
M32	13 – 20	39	8	50,5	40	23	1.547.3223.51
M32	18 – 24	39	8	50,5	40	23	1.547.3223.50
M40	20 – 26	45	8	56,5	50	29	1.547.4029.51
M40	22 – 31	45	8	56,5	50	29	1.547.4029.50
M50	25 – 31	52	9	57,5	57	37	1.547.5037.51
M50	32 – 36	52	9	57,5	57	37	1.547.5037.50

Polyamide fitting Duo-PA (metric)




Material	Polyamide
Seal	NBR
Protection class	IP 54 / IP 68 with additional O-ring: IP 68 - 10bar/30min / IP 69 K
Temperature range	-40°C to +100°C
Colour	black
RAL	9005

RoHS

- // 2 in 1 cable gland and conduit fitting
- // Easy disassembly without tools
- // Other sizes on request
- // NPT connection thread on request

AG	Ø* mm	D mm	GL mm	H mm	SW mm	Suitable for polyamide hose DN	Item-No
M16	3 – 7	23	8	40	22	10	1.542.1610.51
M16	5 – 10	23	8	40	22	10	1.542.1610.50
M20	5 – 9	25	10	44	24	12	1.542.2012.51
M20	6 – 12	25	10	44	24	12	1.542.2012.50
M20	7 – 12	29	10	46	27	14	1.542.2014.51
M20	10 – 14	29	10	46	27	14	1.542.2014.50
M25	9 – 16	30	11	50	33	17	1.542.2517.51
M25	13 – 18	30	11	50	33	17	1.542.2517.50
M32	13 – 20	39	11	60	42	23	1.542.3223.51
M32	18 – 24	39	11	60	42	23	1.542.3223.50



Material	Polyamide
Protection class	IP 54 / IP 65 in case of fixed mounting and o-ring on the connection thread
Temperature range	-20°C to +80°C
Colour	black
RAL	9005


RoHS

// Protection against unintended disconnect. Use screwdriver to disassemble

// Other sizes on request

AG	D mm	GL mm	H mm	SW mm	Suitable for polyamide hose DN	Item-No
M16 x 1,5	20	8	23	17	10	1.511.1601.50
M20 x 1,5	26,5	9	28	24	14	1.511.2001.50
M25 x 1,5	38,5	11	32	35	23	1.511.2501.50
M32 x 1,5	46	11	35	42	29	1.511.3201.50
PG 9	19	8	23	17	10	1.511.0901.14
PG 11	23	8	25	21	12	1.511.1101.14
PG 13,5	26,5	9	28	24	14	1.511.1301.14
PG 16	30	10	29	27	17	1.511.1601.14
PG 21	38,5	11	32	35	23	1.511.2101.14
PG 29	46	11	35	42	29	1.511.2901.14
PG 36	54,5	13	41	50	37	1.511.3601.14
NPT 3/8"	19	15	23	17	10	1.511.3801.70
NPT 1/2"	30	13	29	27	17	1.511.1217.70
NPT 3/4"	38,5	13	32	35	23	1.511.3401.70
NPT 1"	46	15	35	42	29	1.511.1001.70

Polyamide fitting W (metric)



Material	Polyamide
Protection class	IP 54 / IP 65 in case of fixed mounting and o-ring on the connection thread / IP 65 in case of fixed mounting
Temperature range	-20°C to +80°C
Colour	black
RAL	9005

RoHS

// Protection against unintended disconnect. Use screwdriver to disassemble

AG	D mm	GL mm	H mm	L mm	SW mm	Suitable for polyamide hose DN	Item-No
M16 x 1,5	17	8	23	51,5	17	10	1.513.1601.50
M20 x 1,5	26,5	9	30,5	52	24	14	1.513.2001.50

Item-No	Description	Page	Item-No	Description	Page	Item-No	Description	Page
1.239.	Adapter E-M-PA type A (metric, PG)	89	1.691.	HSK-M-EMC (metric/-long)	46	1.542.	Polyamide fitting Duo-PA (metric)	166
1.239.	Adapter E-M-PA type C (metric, PG)	90	1.691.	HSK-M-EMC (NPT)	48	1.511.	Polyamide fitting N (metric, PG, NPT)	167
1.033.	Adapter E-Ms (metric, PG)	91	1.691.	HSK-M-EMC (PG/-long)	47	1.513.	Polyamide fitting W (metric, PG, NPT)	168
1.272.	Adapter R-FS type A (metric)	80	1.631.	HSK-M-EMC-D (metric/-long)	43	1.802.	PVC shroud	157
1.071.	Adapter R-H (metric, PG)	83	1.631.	HSK-M-EMC-D (PG, NPT)	44	1.273.	Reducer R-M-PA Type B (metric)	81
1.273.	Adapter R-M-PA type C (metric, PG)	82	1.636.	HSK-M-EMC-D-Ex (metric)	124	1.098.	Reducer RSD-INOX-Ex (metric)	143
1.039.	Adapter RE-Ms (metric, PG)	85	1.616.	HSK-M-EMC-Ex (metric)	125	1.316.	Rightangle snap elbow (metric)	92
1.171.	Adapter RE-Ms (metric, PG, NPT)	86	1.616.	HSK-M-EMC-Ex (NPT)	126	1.329.	Serrated Washer (metric, NPT)	159
1.094.	Adapter RS-INOX (metric, PG)	87	1.610.	HSK-M-Ex (NPT)	110	1.326.	Thread seal ring (metric, NPT)	156
1.097.	Adapter RSD-INOX (metric, PG)	88	1.610.	HSK-M-Ex (PG)	109	1.325.	Thread seal ring made of fibre composite material	96
1.898.	Adapter RSD-INOX-Ex d (metric)	144	1.622.	HSK-M-Ex d (metric, NPT)	117	1.325.	Thread seal ring made of polyethylene	95
1.077.	Adapter RSD-Ms (metric, PG)	84	1.689.	HSK-M-Flaka-Ex (metric)	113	1.750.	VariaPro Rail (metric)	57
1.078.	Adapter RSD-Ms-Ex (metric, PG)	140	1.623.	HSK-M-Flex (metric, PG, NPT)	31	1.751.	VariaPro Temp (metric)	58
1.879.	Adapter RSD-Ms-Ex d (metric)	142	1.624.	HSK-M-Flex-EMC (metric/-long)	50	1.106.	WADI-A-FKM (metric, PG)	39
1.079.	Adapter RSD-Ms-VMQ-Ex (metric, PG)	141	1.697.	HSK-M-Multi (metric, PG, NPT)	30			
1.213.	Breather drain KS (metric)	97	1.687.	HSK-M-Multi-Ex (metric, NPT)	112			
1.143.	Compression clamp KLE (metric, PG)	98	1.699.	HSK-M-PVDF (metric/-long)	28			
1.101.	DIN 46320 metal (PG)	62	1.699.	HSK-M-PVDF (PG, NPT)	29			
1.105.	DIN 46320 Z (metric, PG)	63	1.698.	HSK-M-PVDF-EMC (metric)	49			
1.022.	Earthtag (metric, NPT)	158	1.660.	HSK-M-PVDF-Ex (metric)	111			
1.608.	EXIOS A2F brass (metric, NPT)	153	1.634.	HSK-M-PVDF-Ex d (metric, NPT)	118			
1.608.	EXIOS A2F INOX (metric, NPT)	155	1.106.	HSK-Mini (metric)	33			
1.608.	EXIOS A2F nickel-plated brass (metric, NPT)	154	1.119.	HSK-Mini EMC (metric)	52			
1.606.	EXIOS Barrier brass (metric, NPT)	150	1.129.	HSK-Mini-INOX (metric)	34			
1.606.	EXIOS Barrier INOX (metric, NPT)	152	1.690.	HSK-MZ (metric)	32			
1.606.	EXIOS Barrier nickel-plated brass (metric, NPT)	151	1.692.	HSK-MZ-EMC (metric)	51			
1.675.	EXIOS MZ nickel plated brass (metric)	149	1.647.	HSK-MZ-EMC-Ex (metric)	127			
1.605.	EXIOS Standard brass (metric, NPT)	146	1.641.	HSK-MZ-Ex (metric)	114			
1.605.	EXIOS Standard INOX (metric, NPT)	148	1.628.	HSK-MZ-Ex d (metric)	119			
1.605.	EXIOS Standard nickel-plated brass (metric, NPT)	147	1.313.	HSK-W (metric, PG, NPT)	21			
1.695.	HSK-INOX (metric)	36	1.314.	HSK-W-Flex (metric, PG, NPT)	22			
1.695.	HSK-INOX (PG, NPT)	37	1.106.	HSK-XL (metric, G)	35			
1.693.	HSK-INOX-EMC (metric)	53	1.263.	Locknut for breather drain GM-KS (metric)	67			
1.673.	HSK-INOX-EMC-Ex (metric)	128	1.167.	Locknut GM-EMC (metric, PG)	69			
1.612.	HSK-INOX-Ex (metric)	115	1.262.	Locknut GM-FS (metric, PG, NPT)	66			
1.632.	HSK-INOX-Ex d (metric, NPT)	120	1.161.	Locknut GM-INOX (metric, PG)	70			
1.740.	HSK-INOX-HD-Pro (metric)	59	1.161.	Locknut GM-Ms (metric, PG, G)	68			
1.676.	HSK-INOX-PVDF (metric, PG)	38	1.607.	METRICA-M-EMC-E (metric)	45			
1.662.	HSK-INOX-PVDF-Ex (metric)	116	1.089.	Multiple cable insertion HSK-ME	93			
1.633.	HSK-INOX-PVDF-Ex d (metric, NPT)	121	1.321.	O-Rings	94			
1.209.	HSK-K (metric)	11	1.280.	Plug HSK-V	74			
1.209.	HSK-K (metric-long)	12	1.296.	Plug HSK-V-Ex	131			
1.209.	HSK-K (NPT)		1.296.	Plug HSK-V-Ex (MZ version)	132			
1.209.	HSK-K (PG)	13	1.297.	Plug V-Ex (metric, PG)	130			
1.209.	HSK-K (PG-long)	14	1.153.	Plug V-INOX metric (metric, PG)	79			
1.292.	HSK-K-Ex-Active (metric long)	103	1.192.	Plug V-INOX-Ex (metric)	137			
1.292.	HSK-K-Ex-Active (metric)	102	1.897.	Plug V-INOX-Ex d (metric)	138			
1.292.	HSK-K-Ex-Active (NPT)	104	1.897.	Plug V-INOX-Ex d (NPT)	139			
1.587.	HSK-K-Flaka (metric, NPT)	17	1.197.	Plug V-Ms-Ex (metric, PG)	133			
1.293.	HSK-K-Flex (metric, PG, NPT)	20	1.875.	Plug V-Ms-Ex d (metric)	135			
1.597.	HSK-K-Multi (metric, PG, NPT)	16	1.877.	Plug V-Ms-Ex d (NPT)	136			
1.581.	HSK-K-Multi-Ex-Active (metric, NPT)	105	1.198.	Plug V-Ms-FKM-Ex (metric)	134			
1.215.	HSK-K-MZ-Ex (metric, PG)	106	1.251.	Plug V-N-FS (metric, PG)	71			
1.299.	HSK-K-PVDF (metric, NPT)	18	1.052.	Plug V-N-Ms (metric)	75			
1.299.	HSK-K-PVDF (PG)	19	1.052.	Plug V-N-Ms-SD (metric, PG)	76			
1.609.	HSK-M (metric/-long)	25	1.255.	Plug V-NE (metric, PG)	72			
1.609.	HSK-M (NPT)	27	1.155.	Plug V-NE-Ms (metric, PG)	77			
1.609.	HSK-M (PG/-long)	26	1.157.	Plug V-NE-Ms-SD (metric, PG)	78			
1.640.	HSK-M Ex (metric)	107	1.256.	Plug V-NE-SD (metric, PG)	73			
1.610.	HSK-M Ex (metric-long)	108	1.533.	Polyamid-Fitting (metric)	163			
			1.510.	Polyamide conduit	162			
			1.534.	Polyamide fitting clip	164			
			1.547.	Polyamide fitting Duo-Ms (metric)	165			




Item-No	Description	Page	Item-No	Description	Page
1.022.	Earhtag (metric, NPT)	158	1.534.	Polyamide fitting clip	164
1.033.	Adapter E-Ms (metric, PG)	91	1.542.	Polyamide fitting Duo-PA (metric)	166
1.039.	Adapter RE-Ms (metric, PG)	85	1.547.	Polyamide fitting Duo-Ms (metric)	165
1.052.	Plug V-N-Ms (metric)	75	1.581.	HSK-K-Multi-Ex-Active (metric, NPT)	105
1.071.	Adapter R-H (metric, PG)	83	1.587.	HSK-K-Flaka (metric, NPT)	17
1.076.	Adapter R-H (metric, PG)	83	1.597.	HSK-K-Multi (metric, PG, NPT)	16
1.077.	Adapter RSD-Ms (metric, PG)	84	1.605.	EXIOS Standard brass (metric, NPT)	146
1.078.	Adapter RSD-Ms-Ex (metric, PG)	140	1.606.	EXIOS Barrier brass (metric, NPT)	150
1.079.	Adapter RSD-Ms-VMQ-Ex (metric, PG)	141	1.607.	METRICA-M-EMC-E (metric)	45
1.089.	Multiple cable insertion HSK-ME	93	1.608.	EXIOS A2F brass (metric, NPT)	153
1.094.	Adapter RS-INOX (metric, PG)	87	1.609.	HSK-M (metric/-long)	25
1.097.	Adapter RSD-INOX (metric, PG)	88	1.610.	HSK-M Ex (metric)	107
1.098.	Reducer RSD-INOX-Ex (metric)	143	1.612.	HSK-INOX-Ex (metric)	115
1.101.	DIN 46320 metal (PG)	62	1.616.	HSK-M-EMC-Ex (metric)	125
1.105.	DIN 46320 Z (metric, PG)	63	1.617.	HSK-MZ-EMC-Ex (metric)	127
1.106.	HSK-Mini (metric)	33	1.622.	HSK-M-Ex d (metric, NPT)	117
1.112.	HSK-Mini (metric)	33	1.623.	HSK-M-Flex (metric, PG, NPT)	31
1.119.	HSK-Mini EMC (metric)	52	1.624.	HSK-M-Flex-EMC (metric/-long)	50
1.129.	HSK-Mini-INOX (metric)	34	1.628.	HSK-MZ-Ex d (metric)	119
1.143.	Compression clamp KLE (metric, PG)	98	1.631.	HSK-M-EMC-D (metric/-long)	43
1.152.	Plug V-INOX metric (metric, PG)	79	1.632.	HSK-INOX-Ex d (metric, NPT)	120
1.153.	Plug V-INOX metric (metric, PG)	79	1.633.	HSK-INOX-PVDF-Ex d (metric, NPT)	121
1.154.	Plug V-INOX metric (metric, PG)	79	1.634.	HSK-M-PVDF-Ex d (metric, NPT)	118
1.155.	Plug V-NE-Ms (metric, PG)	77	1.636.	HSK-M-EMC-D-Ex (metric)	124
1.156.	Plug V-NE-Ms-SD (metric, PG)	78	1.637.	HSK-M-EMC-D-Ex (metric)	124
1.157.	Plug V-NE-Ms-SD (metric, PG)	78	1.640.	HSK-M Ex (metric)	107
1.161.	Locknut GM-Ms (metric, PG, G)	68	1.641.	HSK-MZ-Ex (metric)	114
1.167.	Locknut GM-EMC (metric, PG)	69	1.646.	HSK-M-EMC-Ex (metric)	125
1.171.	Adapter RE-Ms (metric, PG, NPT)	86	1.647.	HSK-MZ-EMC-Ex (metric)	127
1.192.	Plug V-INOX-Ex (metric)	137	1.660.	HSK-M-PVDF-Ex (metric)	111
1.197.	Plug V-Ms-Ex (metric, PG)	133	1.662.	HSK-INOX-PVDF-Ex (metric)	116
1.198.	Plug V-Ms-FKM-Ex (metric)	134	1.673.	HSK-INOX-EMC-Ex (metric)	128
1.199.	Plug V-Ms-FKM-Ex (metric)	134	1.675.	HSK-INOX (metric)	36
1.209.	HSK-K (metric)	11	1.676.	HSK-INOX-PVDF (metric, PG)	38
1.213.	Breather drain KS (metric)	97	1.687.	HSK-M-Multi-Ex (metric, NPT)	112
1.215.	HSK-K-MZ-Ex (metric, PG)	106	1.689.	HSK-M-Flaka-Ex (metric)	113
1.219.	HSK-K (metric)	11	1.690.	HSK-MZ (metric)	32
1.239.	Adapter E-M-PA type A (metric, PG)	89	1.691.	HSK-M-EMC (metric/-long)	46
1.251.	Plug V-N-FS (metric, PG)	71	1.692.	HSK-MZ-EMC (metric)	51
1.255.	Plug V-NE (metric, PG)	72	1.693.	HSK-INOX-EMC (metric)	53
1.256.	Plug V-NE-SD (metric, PG)	73	1.695.	HSK-INOX (metric)	36
1.262.	Locknut GM-FS (metric, PG, NPT)	66	1.696.	HSK-INOX-PVDF (metric, PG)	38
1.263.	Locknut for breather drain GM-KS (metric)	67	1.697.	HSK-M-Multi (metric, PG, NPT)	30
1.272.	Adapter R-FS type A (metric)	80	1.698.	HSK-M-PVDF-EMC (metric)	49
1.273.	Reducer R-M-PA Type B (metric)	81	1.699.	HSK-M-PVDF (metric/-long)	28
1.280.	Plug HSK-V	74	1.625.	EXIOS MZ nickel plated brass (metric)	149
1.292.	HSK-K-Ex-Active (metric)	102	1.740.	HSK-INOX-HD-Pro (metric)	59
1.293.	HSK-K-Flex (metric, PG, NPT)	20	1.750.	VariaPro Rail (metric)	57
1.294.	HSK-K-Flex (metric, PG, NPT)	20	1.751.	VariaPro Temp (metric)	58
1.296.	Plug HSK-V-Ex	131	1.802.	PVC shroud	157
1.297.	Plug V-Ex (metric, PG)	130	1.875.	Plug V-Ms-Ex d (metric)	135
1.299.	HSK-K-PVDF (metric, NPT)	18	1.876.	Plug V-Ms-Ex d (metric)	135
1.313.	HSK-W (metric, PG, NPT)	21	1.877.	Plug V-Ms-Ex d (metric)	135
1.314.	HSK-W-Flex (metric, PG, NPT)	22	1.878.	Adapter RSD-Ms-Ex d (metric)	142
1.316.	Rightangle snap elbow (metric)	92	1.879.	Adapter RSD-Ms-Ex d (metric)	142
1.321.	O-Rings	94	1.895.	Plug V-INOX-Ex d (metric)	138
1.325.	Thread seal ring made of polyethylene	95	1.897.	Plug V-INOX-Ex d (metric)	138
1.326.	Thread seal ring (metric, NPT)	156	1.898.	Adapter RSD-INOX-Ex d (metric)	144
1.329.	Serrated Washer (metric, NPT)	159			
1.510.	Polyamide conduit	162			
1.511.	Polyamide fitting N (metric, PG, NPT)	167			
1.513.	Polyamide fitting W (metric, PG, NPT)	168			
1.533.	Polyamid-Fitting (metric)	163			

TECHNICAL INFORMATION


Thread Specifications

Metric ISO Thread Specifications




Size	Pitch (S) mm	Outside-Ø (D1) mm	Inside-Ø (D2) mm	Through hole mm
M 12 x 1.5	1.5	12	10.38	12.2
M 16 x 1.5	1.5	16	14.38	16.2
M 20 x 1.5	1.5	20	18.38	20.2
M 25 x 1.5	1.5	25	23.38	25.2
M 32 x 1.5	1.5	32	30.38	32.2
M 40 x 1.5	1.5	40	38.38	40.2
M 50 x 1.5	1.5	50	48.38	50.2
M 63 x 1.5	1.5	63	61.38	63.2

PG Thread Specifications



Size	Pitch (S) mm	Outside-Ø (D1) mm	Inside-Ø (D2) mm	Through hole mm
PG 7	1.270	12.5	11.28	12.7
PG 9	1.410	15.2	13.86	15.4
PG 11	1.410	18.6	17.26	18.8
PG 13.5	1.410	20.4	19.06	20.7
PG 16	1.410	22.5	21.16	22.8
PG 21	1.588	28.3	26.78	28.6
PG 29	1.588	37.0	35.48	37.4
PG 36	1.588	47.0	45.48	47.5
PG 42	1.588	54.0	52.48	54.5
PG 48	1.588	59.3	57.78	59.8

NPT Thread Specifications



Size	Pitch (S) mm	Outside-Ø (D1) mm	Number of pitches n
NPT 1/4"	1.411	13.716	18
NPT 3/8"	1.411	17.145	18
NPT 1/2"	1.814	21.336	14
NPT 3/4"	1.814	26.67	14
NPT 1"	2.208	33.4	11 1/2
NPT 1 1/4"	2.208	42.164	11 1/2
NPT 1 1/2"	2.208	48.26	11 1/2
NPT 2"	2.208	60.325	11 1/2
NPT 2 1/2"	3.175	73.025	8
NPT 3"	3.175	88.9	8
NPT 3 1/2"	3.175	101.6	8

EUROPE

HUMMEL Germany

HUMMEL AG
Lise-Meitner-Straße 2
79211 Denzlingen/Germany
Tel. +49 (0) 7666 / 91110 - 0
Fax +49 (0) 7666 / 91110 - 9420
E-Mail info@hummel.com
www.hummel.com

HUMMEL France

HUMMEL CONNECTEURS SAS
ZI – Rue de l'Acqueline
51800 Sainte Ménéhould / France
Tel. +33 (0) 3 89 / 55 37 20
Fax +33 (0) 3 89 / 53 80 27
E-Mail info.fr@hummel.com
www.hummel.com

HUMMEL UK

HUMMEL UK Limited
Office 3, Momentum House
Enterprise Way, Lowton St Marys,
Warrington, Cheshire, WA3 2BP
United Kingdom
Tel. +44 (0) 19 42 / 60 56 95
Fax +44 (0) 19 42 / 26 93 24
E-Mail info.uk@hummel.com
www.hummel.com

HUMMEL Italy

HUMMEL S.r.l.
Via Enrico Fermi 61
10091 Alpignano (Torino) / Italy
Tel. +39 (0) 11 / 9 68 26 38
Fax +39 (0) 11 / 9 78 55 50
E-Mail info.it@hummel.com
www.hummelsrl.it

HUMMEL Poland

HUMMEL Sales Office Poland
Al. 23 Stycznia 26 lok. 20
86-300 Grudziadz / Poland
Tel. +48 (0) 6 62 / 38 27 99
Fax +48 (0) 56 / 6 43 00 11
E-Mail info.pl@hummel.com
www.hummel.com

HUMMEL Scandinavia

HUMMEL Connector Systems AB
Tel. +46 (0) 73 / 8 00 12 00
E-Mail info.se@hummel.com
www.hummel.com

ASIA

HUMMEL China

HUMMEL Connector Systems (Shanghai)
Co., Ltd.
Room 1701 Central Plaza
No.227 Huang Pi (N) Road
200003 Shanghai / P.R. China
Tel. +86 (0) 21 / 63 75 85 51
Fax +86 (0) 21 / 63 75 85 53
E-Mail info.hcs.cn@hummel.com
www.hummel.com

HUMMEL India

HUMMEL Connector Systems Price Limited
307, Surya Kiran Building
19 Kasturba Gandhi Marg
New Delhi – 110001 / India
Tel. +91 (0) 11 / 43 00 75-21 / -23
Fax +91 (0) 11 / 43 00 75-22
E-Mail info.in@hummel.com
www.hummel.com

HUMMEL South Korea

HUMMEL AG KOREA
#1114-5, the First Tower2, 614, Dongtan
Giheung-ro, Hwaseong-si, Gyeonggi-do
18469 Korea
Tel. +82 (0) 2 / 4 70 27 62
Fax +82 (0) 2 / 4 70 27 63
E-Mail info.kr@hummel.com
www.hummelkorea.co.kr

SOUTH AMERICA

HUMMEL Brazil

HUMMEL Connector Systems Ltda.
Rua Derville Gabriel Pereira, 280
Barro Preto – Centro Empresarial Tatuí I
CEP 18280-614 – Tatuí / SP / Brazil
Tel. +55 (0) 15 / 33 22 70 00
Fax +55 (0) 15 / 33 22 70 26
E-Mail vendas@hummel.com.br
www.hummel.com.br



ELECTRIC COMPONENTS

Cable Glands

Polyamide-, Brass- and Stainless steel cable glands,
EMC-connections, Protection Ex e, Ex d, Ex ta

Circular Connectors

M 8 to M 40, INOX, TWILOCK, Industrial Ethernet,
Power, Signal, Hybrid-Connector, Moulded Cordsets

Conduit Systems

Corrugated Conduit Systems, Conduit Cable Glands, Angled Systems,
combined Cable Glands, Accessories

Cable Assembly

Moulded Signal- and Power Circular Connectors, Servo Cables, Cable Sets



HUMMEL AG

Lise-Meitner-Straße 2
79211 Denzlingen
Germany

Tel. +49 (0) 76 66 / 9 11 10 - 0
Fax +49 (0) 76 66 / 9 11 10 - 9420
E-Mail info@hummel.com

www.hummel.com