

HUMMEL offers the great variety of cable glands

The right solution for all industrial requirements



Product series	Size	Temperature range	Protection class	optional insert	flexible cable outlet	Fire protection	UV protection	Ex-protection	Hygienic protection	Chemical resistance	Impact protection	EMC protection
HSK-K	M12 - M63 PG 7 - PG 48 NPT 3/8" - NPT 1 1/2"	-40°C - 100°C	IP54 without O-Ring IP68 10bar / 30min IP69K		HSK-K-Flex	UL94 V0	ULF1					
HSK-K-PVDF	M12 - M32 PG 7 - PG 48 NPT 3/8" - NPT 3/4"	-35°C - 150°C	IP54 without O-Ring IP68 10bar / 30min IP69K			UL94 V0	through PVDF					
HSK-M	M12 - M63 PG 7 - PG 48 NPT 3/8" - NPT 1"	-40°C - 100°C	IP68 10bar / 30min IP69K		HSK-M-Flex	UL94 V0						
HSK-M-PVDF	M12 - M40 PG 7 - PG 48 NPT 3/8" - NPT 3/4"	-35°C - 150°C	IP68 10bar / 30min IP69K			UL94 V0	through PVDF					
HSK-M-EMV	M12 - M63 PG 7 - PG 48 NPT 3/8" - NPT 3/4"	-40°C - 100°C	IP68 10bar / 30min IP69K		HSK-M-Flex-EMV	UL94 V0						
HSK-M-EMV-D	M12 - M63 PG 7 - PG 48 PT 3/8" - NPT 3/4"	-40°C - 100°C	IP68 10bar / 30min IP69K									
HSK-K-Ex-Active	M12 - M63 NPT 3/8" - NPT 1 1/2"	-20°C - 85°C	IP68 10bar / 30min									
HSK-M-Ex	M12 - M63 PG 7 - PG 48 NPT 3/8" - NPT 1"	-20°C - 95°C	IP68 10bar / 30min IP69K			UL94 V0						
HSK-INOX-HD-Pro	M12 - M32	-40°C - 120°C	IP66 IP68 10bar / 30min IP69K									
VariaPro Rail	M12 - M63	-40°C - 100°C	IP68 10bar / 30min			EN 45545						
VariaPro Temp	M12 - M63	-60°C - 200°C	IP68 10bar / 30min									
VariaPro FKM	M12 - M63	-20°C - 180°C	IP68 10bar / 30min									
EXIOS	M16 - M75 NPT 3/8" - NPT 3"	-60°C - 105°C	IP 66, IP 67, IP 68 - 5 bar / 30min									